

# Windows XP Deployment Guide

*A Guide to deploying Windows XP with VMware View*



# Contents

<b>Introduction to VMware View.....</b>	<b>2</b>
<b>About This Guide.....</b>	<b>2</b>
<b>Creating the Initial Virtual Machine.....</b>	<b>2</b>
<b>Installing Windows XP .....</b>	<b>3</b>
<b>Preparation.....</b>	<b>3</b>
Pre-installation Virtual Machine Modifications .....	4
<b>Installation .....</b>	<b>4</b>
<b>Preparing the virtual machine for use as a master .....</b>	<b>5</b>
Preparing a virtual machine for use with linked clones.....	6
Preparing a virtual machine for use as a master template .....	6
Converting a Virtual Machine to a Template.....	6
Creating a Guest Customization Specification.....	6
<b>Managing VMware View-Based Windows XP Desktops.....</b>	<b>7</b>
Adding Users to the Local Remote Desktop Users Group.....	7
Common GPOs for Managing Virtual Desktops.....	8
Managing the VMware View Client Using GPOs.....	9
<b>Multi-Monitor Support .....</b>	<b>10</b>
<b>About the Author .....</b>	<b>10</b>
<b>References .....</b>	<b>11</b>

# Introduction to VMware View

VMware® View transforms the way customers use and manage desktop operating systems. Desktop instances can be deployed rapidly in secure data centers to facilitate high availability and disaster recovery, protect the integrity of enterprise information, and remove data from local devices that are susceptible to theft or loss. Isolating each desktop instance in its own virtual machine eliminates typical application compatibility issues and improves users' personal computing environments.

## About This Guide

This guide suggests best practices for creating Windows XP-based templates for VMware View based solutions and for preparing the templates for use with VMware® View Manager 3.

## Creating the Initial Virtual Machine

The initial virtual machine establishes a virtual hardware profile to be used for rapid deployment of other virtual desktop instances. You can create the initial virtual machine from scratch, as in this guide, or convert a physical machine to a virtual machine, using either the standalone version of VMware® Converter or the version integrated with VMware vCenter. VMware Converter images the target PC and migrates it into VMware® Virtual Infrastructure. Once the migration is complete, you can convert the virtual machine to a template and then use it as the baseline for deploying future virtual desktops.

To create the initial virtual machine from scratch:

- 1 Use the VMware Virtual Infrastructure Client to connect to your VMware vCenter server.
- 2 Use the console to configure the initial virtual machine or template.
- 3 Install the OS using the console.

When you establish a connection with your VMware Virtual Infrastructure datacenter, a new virtual machine should be created from inventory. When you create a new virtual machine, the New Virtual Machine Wizard appears. Use the ["Custom Configuration Parameters"](#) as baseline settings for the template. If you use VMware View Manager as your virtual desktop manager for deploying pooled virtual desktops, you can change these settings at deployment time when deploying template based virtual desktops using guest customization.

## Custom Configuration Parameters

Parameter	Comments
Name and Location	This can be a generic name such as xptemplate. The location can be any folder within your datacenter inventory.
Host/Cluster	Host/Cluster is the VMware VMWARE ESX server or cluster of server resources that will be used to run this virtual machine. It can be changed at anytime. The location of the initial virtual machine or template does not necessarily specify where future virtual machines created from this template will reside.
Resource Pool	If the physical VMware ESX server resources are divided granularly using resource pools, they can be assigned to this virtual machine
Datastore	This is the location where files associated with the virtual machine should be stored.
Guest Operating System	The operating system that will be installed.
CPUs	The number of virtual processors that will be presented to the virtual machine. For most VDI users, a single processor should be sufficient.
Memory	The amount of memory to allocate to each virtual machine e created from this template, in most cases, 512MB
Network	The number of virtual network adapters that will be used. One is usually enough. As a best practice, the network name should be consistent across virtual infrastructures. An incorrect network name in a template can cause failures during the instance customization phases.
I/O Adapters	The LSI Logic adapter issued for VDI-based deployments is recommended; however, the LSI Logic driver is not included as part of the Windows XP install procedure. Download and add it during the OS installation.
Disk	Create a new disk when creating the initial virtual machine or template, based on the amount of local storage you decide to allocate to each user. Allow at least enough for the OS installation, patches, and locally installed applications. Best Practice is to store as much of the user's information, profile, and documents on network shares rather than locally. Doing so can greatly reduce the need for disk space and management of the local data.

## Installing Windows XP

Virtual machines behave like physical machines, so Windows XP installation is essentially the same on both. Although it is possible to image your virtual machine using some type of legacy or existing cloning technology, this guide focuses on a fresh Windows XP installation.

### Preparation

- 1 LSI storage controller drivers are not available on the Windows XP installation CD, so be sure to complete the following items before starting the installation:
- 2 Download the LSI **LSI20320-R** drivers from the LSI Web site.
- 3 Using MagicISO or other third-party solutions, create a **.flp** image containing the LSI Logic drivers.
- 4 SCP the floppy image to the virtual machine's VMware ESX host.  
If you are using VMware vCenter, you can use the VIC to upload the file to the desired datastore.
- 5 Have a Windows XP CD or ISO image that is accessible from the virtual machine.

## Pre-installation Virtual Machine Modifications

Make the following modifications to the virtual machine hardware profile before starting the Windows XP installation:

- 1 Using the VMware Virtual Infrastructure Client (VIC), connect to VMware vCenter.
- 2 Locate the virtual machine that was initially created.
- 3 Edit the following hardware settings:
  - a Ensure there is a floppy drive present.
  - b Ensure the floppy drive is configured to connect at Power On.
  - c If using a floppy image, ensure the Device Type is set to use a floppy image and is pointing to the LSI Driver image.
  - d Ensure the CD/DVD drive is present and configured to connect at power on.
  - e Ensure the CD/DVD Device Type is configured to point at the Windows XP CD or ISO image.

## Installation

Once you complete the pre-installation preparation and modifications, you can install Windows XP:

- 1 From the Virtual Infrastructure client, connect to VMware vCenter.
- 2 Power on the virtual machine created earlier.
- 3 Use the console to view the boot process and to send input to the virtual machine.
- 4 As the Windows Setup process begins, press F6 to add an additional SCSI driver. This lets you specify the LSI Logic driver on the floppy image.

The Windows setup process copies all the necessary files to the virtual disk. Complete the setup just as you would for any normal Windows XP installation. Because this image will be used as a template, however, it is a good idea to make the configuration as generic as possible. For an instance of customization, (see [“Creating a Guest Customization”](#) on page 46).

After completing the Windows setup, perform the following tasks before you finalize the image. Some of these steps will vary from organization to organization, depending on your Windows imaging standards; some are optional and noted as such. Many can be managed using a group policy (see [“Common GPOs for Managing Virtual Desktops”](#) page 8).

### Recommended Steps

- 1 If not applied to the installation CD, Install SP2 and the most recent Microsoft updates.
- 2 Install and configure the VMware Tools.
- 3 If using VMware View Manager as your desktop manager, install the VMware View Manager agent.
- 4 Install and configure any additional third-party or in-house applications needed.

- 5 Set the Windows screensaver to blank.
- 6 Configure the default color setting for RDP.

By default, Windows XP uses 16-bit color for Remote Desktop. You can enable and manage 24-bit color centrally using group policy or by making the following registry change:

`HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp - Change the color depth to 4`

### Optional Steps

- 1 Disable any unused hardware, such as COM1 and COM2.
- 2 Turn off theme enhancements.
- 3 Adjust My Computer>Properties>Advanced Tab>Performance Section>Settings for best performance.
- 4 Set the blank screen saver to password protect on resume.
- 5 Ensure hardware acceleration is enabled.  
Start>Control Panel>Display>Settings Tab>Advanced Button>Troubleshooting Tab.
- 6 Delete any hidden update uninstall folders — C:\WINDOWS.  
For example: `$NtUninstallKB893756$`
- 7 Disable Indexing Services  
Indexing improves searches by cataloging files. For users who search a lot, this may be beneficial and should not be disabled.  
Start>Control Panel>Add Remove Windows Components>Indexing Service.
- 8 Disable indexing of the C: drive from the Properties.
- 9 Remove or minimize System Restore points.  
Start>Control Panel>System>System Restore.
- 10 Disable any unwanted services.
- 11 Run Disk Cleanup.  
My Computer>C: properties.
- 12 Run Disk Defrag.  
My Computer>C: properties>Tools.

After the preparations and installation are complete, you can power the virtual machine off and get ready to enable it as a deployment template for other virtual desktops or prepare it for use with VMware View Composer.

## Preparing the virtual machine for use as a master

Once the initial virtual machine has been created, additional steps are needed to prepare it for use as a master that will be used to deploy virtual desktops in a standard manor. Virtual Desktops can be deployed by manually cloning the master or by using a desktop manager such as VMware View Manager. VMware View manager supports two methods for provisioning desktops. One method deploys virtual desktops from a template and uses guest customization too individually customize each virtual desktop. Another method uses VMware View Manager, linked clones and its own customization quick prep.

## Preparing a virtual machine for use with linked clones

Once the virtual machine has been created, Windows XP, updates and all software installed. Preparing the virtual machine for use with linked clones is simple and straight forward.

- 1 Using the VIC connect to vCenter and select the desired Datacenter
- 2 Locate the virtual machine and establish a console connection
- 3 Login to the virtual machine as administrator
- 4 Join the Windows XP virtual machine to the desired domain
- 5 Allow Windows XP to reboot
- 6 Power down the virtual machine
- 7 Create a snapshot of the virtual machine

The virtual machine is now finished and ready to be used by VMware View Manager linked clones to rapidly deploy virtual machines.

## Preparing a virtual machine for use as a master template

When deploying virtual desktops from a template, each virtual desktop is created by cloning the master template for each desired virtual desktop. This process also uses guest customization for completing typical desktop deployment tasks such as joining each virtual desktop to the Windows domain.

### Converting a Virtual Machine to a Template

Templates standardize the creation of virtual desktops and reduces the risk of human error. Many organizations use separate templates for different types of users or workgroups, such as Finance, HR, and Sales, where each group typically uses a unique software or virtual hardware configuration. The use of templates helps to automate desktop provisioning and makes it easier to manage.

- Any virtual machine can be *converted* into a template: just connect to VirtualCenter using the VIC, locate the virtual machine in the inventory, and select Convert to Template.
- Any virtual machine can also be cloned to a template. Cloning creates a copy of the VM, leaving the original in place.

Cloning is helpful if you update the template and redeploy desktops often, for instance, if you deploy non-persistent desktops or if you use a profile solution to separate the user profiles from the desktop environment. Cloning enables you to convert a template to a virtual machine, update it, and then convert it back to a template at any time.

### Creating a Guest Customization Specification

Guest customization lets you customize virtual desktops as they are created. Using Microsoft sysprep, VMware vCenter guest customization automates several configuration tasks such as:

- Adding registration Information
- Assigning a unique computer name
- Adding your product key
- Setting the Administrator password

- Setting the time zone
- Adding any custom run-once scripts
- Defining the network configuration
- Joining a domain
- Generating a new SID

If you use VMware View Manager as your virtual desktop manager, it works in conjunction with any existing pre-defined guest customization specifications. You have the option of selecting which guest customization file to use, if any, to customize the pool of virtual desktops it will create.

To create a guest customization specification:

- 1 Connect with VMware vCenter using the VIC.
- 2 Select Edit, Customization Specifications.
- 3 Once the Customization Specification Manager starts, select New.

If you prefer, you may import an existing custom sysprep.ini file and use it in the guest customization wizard. As a best practice when using VMware View Manager and Guest Customization Specification, set the Computer Name portion of the guest specification to Use the Virtual Machine Name. This ensures that the computer name is consistent across VMware View Manager, VMware vCenter, Active Directory, and Local Computer Name.

When your initial virtual machine, template, and guest customization are complete, the virtual desktop template is ready, and you can use it when deploying virtual desktops.

## Managing VMware View-Based Windows XP Desktops

The following sections focus on best practices for simplifying and standardizing some common desktop management tasks.

### Adding Users to the Local Remote Desktop Users Group

When you add users to the Windows XP local group, Remote Desktop Users, they will not be able to access individual or pooled desktops unless they belong to this local group. There are several ways to add users or groups to the local Remote Desktop Users. One is to use a login script. Another approach leverages the Restricted Groups GPO in Active Directory.

When leveraging Restricted Groups, you can add users individually or create a group, add users to it, then add that group to the Restricted Group you are managing. Here are the steps for configuring a Restricted Group using the Default Domain Policy:

- 1 Using a Microsoft Management Console (MMC) with Group Policy console for your domain, create a new group called VMware View Users under Active Directory>Users and Computers.
- 2 Add the users who need to access virtual desktops to this group.
- 3 Edit your Default Domain Policy.
- 4 Under Computer Configuration>Windows Settings>Restricted Groups, add the Remote Desktop Users Group.
- 5 Add the VMware View users group to the members of the Restricted Remote Desktop Users.

This approach ensures that the VMware View Users group is always added to the local Remote Desktop Users group of each virtual desktop joined to the domain. When provisioning new users, an administrator or help desk technician only needs to ensure that users are added to the VMware View Users group in Active Directory.

## Common GPOs for Managing Virtual Desktops

There are several GPOs that can be used for central control of the configuration of your virtual desktops. Because users access their virtual desktops with Remote Desktop, the most common and often used GPOs are the Terminal Server GPOs under Computer or User Configuration > Administrative Templates > Windows Components > Terminal Services. Several of the GPOs are specific to Terminal Server and do not apply to remote desktops sessions. Some of the more commonly used GPOs for deploying Windows XP in a VDI environment are described below. Many of these are optional but recommended. Naturally, use cases and environments vary depending on your organization's standards and policies.

**Table 2. GPOs Under Terminal Services**

Enforce Removal of Remote Desktop Wallpaper = Enable	This setting can greatly enhance the user experience, especially over low-bandwidth connections
Limit maximum color depth = Enable	This setting lets you set the color depth for Remote Desktop sessions.
Allow users to connect remotely using Terminal Services = Enable	This setting ensures that the local policy enabling Remote Desktop connections is configured.
Remote Windows Security Item from Start Menu = Disable	Setting this to Disable ensure that users have a log off mechanism.
Remove Disconnect option from Shut down dialog = Enable	This setting minimizes the possibility of users disconnecting rather than logging off.

**Table3.GPOs Under Terminal Services >Sessions**

Set time limit for disconnected sessions = Enable	This setting logs off any disconnected sessions that occur after the specified time. Combined with VDM 2 virtual machine power policies, this can be used to create a dynamic and powerful solution for suspending or powering off disconnected virtual desktops. When unneeded desktops are suspended or powered off, the resources are made available to other desktops.
Set a time limit for active but idle Terminal Services sessions = Enable	This setting logs off any idle sessions that occur after the specified time. Combined with VDM 2 virtual machine power policies, this can be used to create a dynamic and powerful solution for

suspending or powering off disconnected virtual desktops. When unneeded desktops are suspended or powered off, the resources are made available to other desktops.

---

**Note:** Windows XP has a bug where the idle tracker will not work. A hotfix is available from Microsoft upon request. See KB890864.

## Managing the VMware View Client Using GPOs

One of the components provided with VMware View Manager is the VMware View Client, a Win32 application that can be installed on most Windows platforms, such as XP Embedded, Windows 2000 Pro, XP Professional, and Vista. It provides the client side component for connecting with virtual desktops. On Embedded XP, Windows XP, and Vista clients, it also enables the ability to redirect additional USB devices not supported by native RDP device redirection.

Also included with VMware View is a Group Policy Administrative Template for managing and configuring the VMware View Client settings from a central location with Group Policy. The client side settings that can be managed using this administrative template are:

- Enable the shade
- Pin the shade
- Don't check monitor alignment on spanning
- Color depth
- Desktop background
- Show contents of window while dragging
- Menu and window animation
- Themes
- Cursor shadow
- Font smoothing
- Desktop composition
- Audio redirection
- Redirect drives
- Redirect printers
- Redirect serial ports
- Redirect smart cards
- Redirect clipboard
- Redirect supported plug-and-play devices
- Bitmap caching

- Shadow bitmaps
- Cache persistence active
- Enable compression
- Windows key combination redirection
- Bitmap cache file size

Take the following steps to start configuring the VMware View Client settings:

- 1 Locate the **view\_client.adm** file in C:\Program Files\VMware\VMware View\Server\ADM. This is located on any connection broker that has been installed.
- 2 Copy this file to the management station you use to manage Group Policy Objects. By default, Group Policy looks for administration templates in C:\WINDOWS\inf. You can copy the **view\_client.vdm** file to that location or any other location accessible from your management station.
- 3 Using your Microsoft Management Console (MMC) with the Group Policy Editor snap-in loaded, locate the Group Policy you want to add the template to.
- 4 From the policy, expand User Configuration, Select Administrative Templates, and Add/Remove Templates.
- 5 Locate the **view\_client** template and add it to the policy.

Once you complete these steps, you are ready to configure your policy to set the VMware View Client settings. When managing the VMware View Client settings or another device, such as a thin client using its own RDP client and configuration, note that any GPO settings for the Remote Desktop will override the client side. For example, if the client is configured to use 24-bit color and the Remote Desktop GPO is configured for a maximum of 16-bit color, the connection will connect using 16-bit color.

## Multi-Monitor Support

Using the latest Microsoft Remote Desktop client command line option, **/span**, a Remote Desktop Session can span multiple displays with a maximum resolution of 4096 x 2048. However, spanning does not achieve the identical desktop experience to that of a workstation with a multi-port graphics card. In order to achieve a true multi-monitor experience, you need a third-party tool, such as SplitView or iShadow - Remote Desktop Manager.

The VMware View Client also provides the ability for users to configure their desktops by spanning the Remote Desktop session across multiple monitors. Individual users can configure this preference with the VMware View Client or VMware View Portal.

## About the Author

Warren Ponder is a Sr. Technical Marketing Manager at VMware. In this role, he works as part of the product marketing team developing alternative approaches to traditional desktop architectures and solutions. Much of his time is spent speaking, writing, and developing technical content focused on

thin client computing, Windows interoperability, and desktop solutions that leverage the benefits of VMware's leading virtualization technologies.

## References

<http://technet.microsoft.com/en-us/sysinternals/default.aspx>

<http://technet.microsoft.com/en-us/windowsxp/default.aspx?wt.svl=leftnav>

<http://technet2.microsoft.com/windowsserver/en/library/b9546edf-751f-4a09-835a-f3397caef2361033.msp?mfr=true>

<http://technet2.microsoft.com/windowsserver2008/en/library/fc0b405b-07ef-4767-8716-198d7f0949011033.msp?mfr=true>

<http://www.ishadow.com/>

<http://www.splitview.com/>

[http://www.vmware.com/files/pdf/viewmanager3\\_admin\\_guide.pdf](http://www.vmware.com/files/pdf/viewmanager3_admin_guide.pdf)

LSI Windows XP Driver

Revision: DG-043-PRD-02-01



VMware, Inc. 3401 Hillview Ave. Palo Alto CA 94304 USA Tel 650-475-5000 Fax 650-475-5001 [www.vmware.com](http://www.vmware.com)  
© 2007 VMware, Inc. All rights reserved. Protected by one or more of U.S. Patent Nos. 6,397,242, 6,496,847, 6,704,925, 6,711,672, 6,725,289, 6,735,601, 6,785,886, 6,789,156, 6,795,966, 6,880,022, 6,961,941, 6,961,806, 6,944,699, 7,069,413; 7,082,598, 7,089,377, 7,111,086, 7,111,145, 7,117,481, 7,149, 843, 7,155,558, 7,222,221, 7,260,815, 7,260,820, 7,269,683, 7,275,136, 7,277,998, 7,277,999, 7,278,030, and 7,281,102; patents pending. VMware, the VMware "boxes" logo and design, Virtual SMP and VMotion are registered trademarks or trademarks of VMware, Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

