

## VMware® VMmark® V2.5.1 Results

Vendor and Hardware Platform: Fujitsu PRIMERGY RX300 S7  
 Virtualization Platform: VMware ESX 4.1.0 U3 Build 800380  
 VMware vCenter Server : VMware vCenter Server 5.1.0 U1 Build 1064983

**VMmark V2.5.1 Score =  
12.51 @ 10 Tiles**

Number of Hosts: 2	Uniform Hosts [yes/no]: yes	Total sockets/cores/threads in test: 4/32/64
Tested By: Fujitsu		Test Date: 07-20-2013
Performance Section <a href="#">Performance</a>	Configuration Section <a href="#">Configuration</a>	Notes Section <a href="#">Notes for Workload</a>

### Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.73	0.99	63.00	4693.40	1.01	163.61	3990.00	1.81	64.95	3114.82	2.05	59.36	2248.60	2.13	61.32	1.51
p1	326.25	0.99	63.00	4659.27	1.00	176.30	3964.32	1.80	65.90	3238.57	2.13	58.37	2370.15	2.24	60.24	1.54
p2	329.15	1.00	63.35	4664.12	1.00	176.97	3947.78	1.80	66.76	3165.75	2.08	61.48	2411.88	2.28	63.78	1.54
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.77	0.99	54.05	4676.45	1.01	153.87	4043.32	1.84	63.07	3070.32	2.02	61.43	2226.18	2.10	62.84	1.51
p1	323.90	0.98	54.50	4669.55	1.01	177.37	3983.72	1.81	65.25	3307.62	2.18	59.82	2445.68	2.31	61.49	1.55
p2	324.15	0.98	63.52	4635.52	1.00	203.50	3903.03	1.77	68.25	3137.65	2.07	58.29	2384.22	2.25	59.30	1.52
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.55	0.99	64.00	4690.15	1.01	156.78	4237.20	1.93	56.55	3206.62	2.11	59.81	2337.55	2.21	62.22	1.55
p1	324.93	0.98	64.00	4654.82	1.00	179.54	4241.62	1.93	56.58	3188.45	2.10	60.61	2435.88	2.30	62.55	1.56
p2	327.50	0.99	64.00	4672.05	1.01	187.04	4171.27	1.90	58.88	3040.30	2.00	62.60	2202.97	2.08	64.47	1.51
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	322.12	0.98	56.85	4675.18	1.01	156.57	4190.18	1.91	58.12	3276.65	2.16	61.25	2415.93	2.28	63.53	1.56
p1	327.05	0.99	54.77	4671.45	1.01	174.07	4194.02	1.91	58.07	3057.85	2.01	61.74	2304.97	2.18	64.15	1.53
p2	326.50	0.99	64.00	4650.48	1.00	197.01	4212.38	1.92	57.48	3066.38	2.02	61.38	2214.12	2.09	63.90	1.52
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.12	0.98	63.98	4685.00	1.01	162.97	3973.72	1.81	65.68	3206.93	2.11	59.79	2456.90	2.32	61.34	1.55
p1	328.25	0.99	64.00	4679.15	1.01	175.13	3992.53	1.82	64.79	3162.90	2.08	56.69	2292.88	2.17	58.43	1.52
p2	328.40	0.99	64.00	4667.05	1.01	175.48	3959.68	1.80	66.27	3197.50	2.11	60.15	2339.55	2.21	62.14	1.53
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	330.02	1.00	61.25	4681.20	1.01	158.12	4075.12	1.85	61.70	3221.07	2.12	59.03	2356.05	2.23	60.98	1.55
p1	327.77	0.99	54.92	4680.12	1.01	175.48	3972.43	1.81	65.83	3092.97	2.04	60.40	2231.00	2.11	62.61	1.51

<b>p2</b>	328.75	1.00	64.00	4647.82	1.00	203.28	3906.00	1.78	68.27	3256.15	2.14	57.33	2496.97	2.36	58.72	1.55
<b>TILE_6</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	327.43	0.99	72.25	4659.43	1.00	158.13	4293.68	1.95	54.53	3239.75	2.13	58.03	2372.32	2.24	59.91	1.56
<b>p1</b>	323.45	0.98	64.00	4659.62	1.00	175.30	4277.82	1.95	54.97	3245.20	2.14	57.97	2378.65	2.25	59.62	1.56
<b>p2</b>	326.30	0.99	69.00	4669.23	1.01	182.95	4200.55	1.91	57.77	3063.10	2.02	61.51	2322.75	2.20	63.25	1.53
<b>TILE_7</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	327.88	0.99	66.10	4693.90	1.01	150.86	4173.95	1.90	58.60	3152.55	2.08	62.19	2308.57	2.18	64.18	1.54
<b>p1</b>	327.60	0.99	64.00	4665.90	1.01	173.01	4209.73	1.91	57.38	3183.72	2.10	60.67	2445.85	2.31	61.96	1.56
<b>p2</b>	328.05	0.99	64.00	4647.82	1.00	199.79	4278.60	1.95	54.87	3130.28	2.06	58.08	2282.88	2.16	59.25	1.54
<b>TILE_8</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.77	0.99	370.48	4683.48	1.01	167.84	3939.70	1.79	67.01	3170.95	2.09	61.35	2428.80	2.30	63.08	1.54
<b>p1</b>	326.07	0.99	210.00	4667.45	1.01	177.50	3957.47	1.80	66.13	3118.47	2.05	58.86	2372.80	2.24	59.83	1.52
<b>p2</b>	323.45	0.98	140.68	4678.12	1.01	192.73	3924.50	1.78	67.43	3051.53	2.01	62.12	2214.28	2.09	63.73	1.49
<b>TILE_9</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	326.12	0.99	265.90	4685.43	1.01	162.47	4016.85	1.83	64.23	3147.88	2.07	62.45	2411.05	2.28	63.97	1.54
<b>p1</b>	320.12	0.97	134.50	4663.62	1.00	186.42	3977.18	1.81	65.44	3088.88	2.03	60.22	2242.32	2.12	61.85	1.50
<b>p2</b>	325.50	0.99	104.00	4636.35	1.00	212.80	3869.85	1.76	69.53	3221.68	2.12	58.85	2370.97	2.24	59.93	1.52
<b>p0_score:</b>	15.40															
<b>p1_score:</b>	15.35															
<b>p2_score:</b>	15.25															

<b>Infrastructure_Operations_Scores:</b>	vmotion	svmotion	deploy
<b>Completed_Ops_PerHour</b>	17.00	11.00	5.00
<b>Avg_Seconds_To_Complete</b>	31.18	20.05	296.53
<b>Failures</b>	0.00	0.00	0.00
<b>Ratio</b>	1.06	1.22	1.25
<b>Number_Of_Threads</b>	1	1	1

<b>Summary</b>	Run_Is_Compliant	Turbo_Setting:0
	Number_Of_Compliance_Issues(0)*	Median_Phase(p1)
<b>Unreviewed_VMmark2_Applications_Score</b>	15.35	
<b>Unreviewed_VMmark2_Infrastructure_Score</b>	1.18	
<b>Unreviewed_VMmark2_Score</b>	12.51	

## Configuration

<b>Virtualization Software</b>	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESX 4.1.0 U3 Build 800380 / 08-30-2012
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 5.1.0 U1 Build 1064983 / 04-25-2013
Supplemental Software	none
<b>Servers</b>	
Quantity	2
Server Manufacturer and Model	Fujitsu PRIMERGY RX300 S7
Processor Vendor and Model	Eight-core Intel Xeon E5-2690
Processor Speed (GHz)	2.9
Total Sockets/Total Cores/Total Threads	2 Sockets / 16 Cores / 32 Threads
Primary Cache	32KB I + 32KB D on chip per core
Secondary Cache	256KB I+D on chip per core
Other Cache	20MB I+D on chip per chip L3
BIOS Version	V4.6.5.3 R1.24.0
Memory Size (in GB, Number of DIMMs)	256GB, 16
Memory Type and Speed	16GB DIMMs 2Rx4 L DDR3-1600 R ECC
Disk Subsystem Type	FC SAN
Number of Disk Controllers	1 (disabled)
Disk Controller Vendors and Models	Intel Patsburg SAS/SATA SCU
Number of Host Bus Adapters	1
Host Bus Adapter Vendors and Models	Dual-channel Emulex LPe12002
Number of Network Controllers	2
Network Controller Vendors and Models	Integrated Intel I350 Dual Port 1GbE Adapter, Fujitsu D2755 Dual Port 10GbE Adapter
Other Hardware	none
Other Software	none

Hardware Availability Date (MM-DD-YYYY)	07-01-2012
Software Availability Date (MM-DD-YYYY)	04-25-2013
<b>Network</b>	
Network Switch Vendors and Models	Fujitsu PRIMERGY BX600 GbE Switch Blade 30/12, CISCO 4900M
Network Speed	1Gbps for SUT management, Clients and VMotion, 10Gbps for all VMs
<b>Storage</b>	
Array Vendors, Models, and Firmware Versions	Fujitsu PRIMERGY RX300 S7, Firmware V4.6.5.1 R1.22.0
Fibre Channel Switch Vendors and Models	Brocade 5100
Disk Space Used	4060GB
Array Cache Size	1GB
Total Number of Physical Disks Used	12xSAS-SSDs, 2xPCIe-SSD
Total Number of Enclosures/Pods/Shelves Used	1
Number of Physical Disks Used per Enclosure/Pod/Shelf	Details in section Storage Notes
Total Number of Storage Groups Used	2
Number of LUNs Used	19
LUN Size and Number of Disks Per LUN	Details in section Storage Notes
RAID Type	0
Number of Members per RAID Set	Details in section Storage Notes
Disk Vendors, Models, and Speeds	12xSSD Seagate ST200FM0002, 2xFusion-io ioDrive2 1.2TB PCIe SSD
<b>Datacenter Management Server</b>	
System Model	PRIMERGY BX620 S5
Processor Vendor and Model	X5570
Processor Speed (GHz)	2.93
Total Sockets/Total Cores/Total Threads	2 Sockets / 8 Cores / 16 Threads

Memory	Hypervisor: 24GB Virtual Center VM: 8GB
Network Controller(s) Vendors and Models	3 Intel Dual port 82575EB
Operating System, Version, Bitness, and Service Pack	Hypervisor: VMware ESX 5.1.0 Build 799733 Virtual Center VM: Windows Server 2008 R2 Enterprise 64-bit
Other Hardware	none
Other Software	none
<b>Clients</b>	
Total Number of Clients / Total Physical Clients / Total Virtual Client Hosts	11 / 1 / 2
System Model(s)	PRIMERGY BX620 S5 (Prime Client) PRIMERGY RX600 S6 (Virtual Client Hosts)
Processor Vendor(s) and Model(s)	Prime Client: Intel Xeon X5570 Virtual Client Hosts: Intel Xeon E7-4870
Processor Speed(s) (GHz)	Prime Client: 2.93 Virtual Client Hosts: 2.4
Total Sockets/Total Cores/Total Threads	Prime Client: 2 Sockets / 8 Cores / 16 Threads Virtual Client Hosts: 4 Sockets / 40 Cores / 80 Threads
Memory per Physical Client	Prime Client: 12GB Virtual Client Hosts: 512GB
Network Controller(s) Vendors and Models	Prime Client: Three Intel Dual Port 82575EB Virtual Client Hosts: One Intel Quad Port 82571EB, two Intel Dual Port 82576NS
Operating System, Version, Bitness, and Service Pack	Clients: Windows Server 2008 Enterprise 64-bit SP2 Virtual Client Hosts: VMware ESX 4.1 U2 Build 502767
Number of Virtual Clients	10
Number of vCPUs Per Virtual Client	4
Number of vMem (GB) Per Virtual Client	4
Virtual Client Networking Notes	One vSwitch per virtual client
Virtual Client Storage Notes	none
Other Hardware	One Dual-channel Emulex LPe12002 for each virtual client host, one shared Fujitsu ETERNUS DX80 with 24x300GB disks
Other Software	none

## Notes for Workload

## Virtualization Software Notes

- Floppy and CDROM removed for all VMs (default enabled)
- Firewall disabled for the Console OS (default enabled)
- Hardware version 7 used for all VMs (default 7)
- Logging disabled for all VMs (default enabled)
- Logical CPU layout changed for all VMs (except Standby and Mailserver) to one socket with multiple cores (default: multiple sockets with one core per socket)
- SCSI adapter type PVSCSI used for all Standby VMs (default LSI Logic parallel)
- SCSI adapter type PVSCSI used for all Mailserver and Linux VMs (default LSI Logic SAS)
- VMXNET3 enabled for all VMs (default VMXNET2)

Changes in esx.conf:

- /adv/Cpu/CreditAgePeriod = 533 (default 3000)
- /adv/Cpu/HaltingIdleMsecPenalty = 0 (default 1)
- /adv/DataMover/HardwareAcceleratedInit = 0 (default 1)
- /adv/DataMover/HardwareAcceleratedMove = 0 (default 1)
- /adv/Irq/RoutingPolicy = 0 (default 2)
- /adv/Mem/BalancePeriod = 0 (default 15)
- /adv/Mem/SamplePeriod = 0 (default 60)
- /adv/Mem/ShareScanGHz = 0 (default 4)
- /adv/Misc/TimerMaxHardPeriod = 4000 (default 100)
- /adv/Misc/TimerMinHardPeriod = 2000 (default 100)
- /adv/Net/MaxNetifRxQueueLen = 500 (default 100)
- /adv/Net/MaxNetifTxQueueLen = 1000 (default 500)
- /adv/Net/NetTxCompletionWorldlet = 0 (default 2)
- /adv/Net/NetTxWorldlet = 0 (default 2)
- /adv/Numa/LTermFairnessInterval = 0 (default 5)
- /adv/Numa/MigImbalanceThreshold = 57 (default 10)
- /adv/Numa/MonMigEnable = 0 (default 1)
- /adv/Numa/PageMigEnable = 0 (default 1)
- /adv/Numa/RebalancePeriod = 60000 (default 2000)
- /adv/Numa/SwapLoadEnable = 0 (default 1)
- /adv/Numa/SwapLocalityEnable = 0 (default 1)
- /adv/VMFS3/HardwareAcceleratedLocking = 0 (default 1)
- /vmkernel/module/lpfc820.o/options = lpfc\_lun\_queue\_depth=64 (default 31)

## Server Notes

- Server BIOS settings:
  - Adjacent Cache Line Prefetch: Disabled (default enabled)
  - Energy Performance: Performance (default Energy Efficient)
  - Frequency Floor Override: Enabled (default disabled)
  - Hardware Prefetcher: Disabled (default enabled)
  - Intel VT-d: Disabled (default Enabled)
  - Memory refresh rate set to 1x Refresh (default 2x Refresh)
  - Onboard SAS/SATA SCU: Disabled (default enabled)

- Turbo Boost Technology: Enabled (Intel Turbo Boost up to 3.8GHz, default enabled)

## Networking Notes

- One dedicated VLAN for the systems under test, vCenter Server and Benchmark Controller (SUT-VLAN)
- One dedicated VLAN for the VMs and Clients (Load-VLAN)
- vSwitch Configuration:
  - vSwitch0 on vmnic0 for Service Console (1Gb)
  - vSwitch1 on vmnic1 for VMotion (1Gb)
  - vSwitch1 Jumbo frames enabled (default disabled)
  - vSwitch2 on vmnic2 (10Gb) for all DS2, Deploy and Standby VMs and for Olio VMs 2,3,6,7
  - vSwitch3 on vmnic3 (10Gb) for all Mailservers and Olio VMs 0,1,4,5,8,9

## Storage Notes

One PRIMERGY RX300 S7 configured as a Fibre Channel Target:

- Hardware details:
  - Two Intel Xeon E5-2690@2.9GHz processors
  - 64GB RAM (8x8 GB dual rank PC3-12800 Registered DDR3 / 1600 MHz DIMMs)
  - One QLogic QLE2562 8Gb FC HBA used as FC target controller
  - One Fujitsu RAID SAS 6G Controller with 1GB Cache (D3116)
  - 12x200GB SAS-SSDs Seagate ST200FM0002
  - 2xFusion-io ioDrive2 1.2TB PCIe-SSD
- Software details:
  - Operating System: SUSE Linux Enterprise Server 11 SP3 (64-bit)
  - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11 SP3)

RAID configuration:

- SAS-SSD 1..10: For each Tile one SSD (186GB) with all VMs except Standby, OlioDB and the second VHDs for the Mailserver and DS2DB VMs
- SAS-SSD 11:
  - LUN 1: Boot/Console OS for SUT1 (11GB)
  - LUN 2: Boot/Console OS for SUT2 (11GB)
  - LUN 3: Target LUN for Storage VMotion (10GB)
  - LUN 4: Source LUN for Deploy (10GB)
  - LUN 5: Target LUN for Deploy (10GB)
- SAS-SSD 12: Boot OS for the storage system
- First PCIe-SSD:
  - LUN 1: The second VHD for all even numbered DS2DB VMs (537GB)
  - LUN 2: The second VHD for all odd numbered DS2DB VMs (537GB)
- Second PCIe-SSD:
  - LUN 1: Odd numbered OlioDB and Standby VMs and the second VHD for the odd numbered Mailserver VMs (537GB)
  - LUN 2: Even numbered OlioDB and Standby VMs and the second VHD for the even numbered Mailserver VMs (537GB)
- All LUNs were configured as block devices; no system memory was used for caching

## Datacenter Management Server Notes

Virtual Center VM configured with four vCPUs and 8GB vMEM

## Operating System Notes

Mailserver VMs: Microsoft Windows 2008 R2 Enterprise 64-bit.

Linux VMs : All SLES11 VMs were updated with SP2

The file systems of all Linux and Standby VMs were aligned to a 4KB boundary

## Software Notes

Mailserver VMs: Microsoft Exchange 2007 Enterprise x64 Edition updated with SP3.

## Client Notes

Prime Client was running VMware vSphere PowerCLI 5.1 Release 1 Build 793510.

Prime Client was updated via Windows Update.

## Other Notes

One client used as a dedicated Benchmark Controller.

---

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit [www.vmware.com/products/vmmark](http://www.vmware.com/products/vmmark).

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of [VMware, Inc.](http://www.vmware.com) VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.