VMware® VMmark® V2.5.2 Results

Vendor and Hardware Platform: Fujitsu PRIMEQUEST 2800E (partitioned as 4-ways) Virtualization Platform: VMware ESXi 5.5.0 Build 1331820 VMware vCenter Server : VMware vCenter Server 5.5.0 Build 1312298	VMmark V2.5.2 Score = 70.73 @ 60 Tiles

Number of Hosts: 4 (in two PRIMEQUEST 2800E)	Uniform Hosts [yes/no]: yes	Total sockets/cores/threads in test: 16/240/480

Tested By: Fujitsu	Test Date: 03-18-2014

Performance Section	Configuration Section	Notes Section
Performance	Configuration	Notes for Workload

Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.95	0.99	58.60	4709.57	1.01	143.23	3927.53	1.79	68.19	2900.15	1.91	75.09	2224.70	2.10	76.86	1.48
p1	329.95	1.00	67.75	4674.82	1.01	169.48	3926.72	1.79	68.18	2806.70	1.85	74.82	2034.38	1.92	76.69	1.45
p2	326.38	0.99	74.75	4685.35	1.01	171.98	3882.85	1.77	70.02	2878.97	1.90	76.10	2105.82	1.99	78.41	1.46
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	320.23	0.97	54.50	4699.62	1.01	142.33	3940.82	1.79	67.70	2811.85	1.85	74.66	2128.82	2.01	76.36	1.46
p1	327.98	0.99	65.50	4683.05	1.01	166.86	3905.47	1.78	69.32	2789.85	1.84	75.96	2016.88	1.91	78.52	1.44
p2	324.62	0.98	76.50	4659.55	1.00	172.50	3886.10	1.77	70.09	2873.97	1.89	76.42	2193.22	2.07	78.69	1.47
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.18	0.99	54.00	4695.88	1.01	137.85	3851.25	1.75	70.95	2822.03	1.86	74.16	2051.88	1.94	75.39	1.45
p1	324.18	0.98	59.65	4704.27	1.01	150.34	3800.82	1.73	72.97	2868.28	1.89	77.00	2111.07	2.00	78.06	1.45
p2	326.70	0.99	63.00	4682.75	1.01	150.92	3858.43	1.75	70.73	2856.65	1.88	77.73	2202.95	2.08	78.06	1.47
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.60	0.98	54.00	4683.73	1.01	135.95	3971.03	1.81	66.74	2846.70	1.87	73.13	2049.05	1.94	75.81	1.45
p1	325.82	0.99	61.75	4699.68	1.01	149.50	3929.88	1.79	68.27	3028.05	1.99	73.52	2230.65	2.11	76.34	1.50
p2	326.35	0.99	69.25	4679.75	1.01	159.00	3949.40	1.80	67.56	2834.57	1.87	73.69	2140.32	2.02	76.22	1.47
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.70	0.99	61.48	4682.15	1.01	143.60	4101.50	1.87	62.05	3034.70	2.00	68.27	2202.28	2.08	71.47	1.51
p1	324.45	0.98	72.00	4698.77	1.01	155.97	3936.90	1.79	68.68	2890.57	1.90	75.88	2195.43	2.07	79.35	1.48
p2	327.23	0.99	78.50	4674.68	1.01	174.15	3674.50	1.67	80.13	2581.90	1.70	89.72	1837.50	1.74	94.77	1.38
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.40	0.98	56.70	4701.62	1.01	135.97	4095.85	1.86	62.20	3041.05	2.00	67.93	2212.90	2.09	70.83	1.51

p1	327.32	0.99	64.75	4692.25	1.01	147.23	4017.12	1.83	65.26	2854.97	1.88	72.45	2144.75	2.03	75.76	1.47
p2	326.57	0.99	74.00	4680.52	1.01	165.75	3759.15	1.71	76.38	2643.82	1.74	85.53	1888.70	1.79	89.86	1.40
TILE_6	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.45	0.99	53.08	4694.32	1.01	136.72	3970.55	1.81	66.26	3047.30	2.01	67.56	2358.35	2.23	67.72	1.52
p1	327.93	0.99	60.70	4693.90	1.01	141.62	3882.47	1.77	69.75	2854.82	1.88	72.62	2092.62	1.98	72.96	1.46
p2	324.35	0.98	64.00	4689.27	1.01	140.92	3920.88	1.78	68.38	2930.47	1.93	73.69	2168.45	2.05	74.42	1.48
TILE_7	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.73	0.99	58.17	4703.23	1.01	139.93	4155.02	1.89	60.07	2971.07	1.96	66.35	2243.03	2.12	68.80	1.51
p1	326.18	0.99	64.25	4684.57	1.01	149.95	4126.45	1.88	60.92	3060.05	2.02	66.93	2232.20	2.11	69.41	1.51
p2	326.65	0.99	74.00	4685.82	1.01	160.20	4008.22	1.82	65.62	2976.65	1.96	71.66	2165.45	2.05	74.67	1.49
TILE_8	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.70	0.99	60.98	4695.95	1.01	142.69	3917.18	1.78	69.06	2902.28	1.91	75.41	2073.47	1.96	80.87	1.46
p1	326.45	0.99	69.50	4693.38	1.01	160.13	3912.95	1.78	68.86	2811.22	1.85	75.09	1982.25	1.87	80.92	1.44
p2	325.80	0.99	81.75	4690.88	1.01	170.56	3869.88	1.76	70.87	2875.12	1.89	76.92	2151.10	2.03	81.69	1.47
TILE_9	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.98	0.98	57.48	4703.35	1.01	134.04	3933.22	1.79	68.46	2817.97	1.86	75.02	1982.78	1.87	80.95	1.44
p1	325.90	0.99	66.75	4675.65	1.01	159.85	3898.50	1.77	69.92	2891.55	1.90	75.89	2064.88	1.95	81.90	1.46
p2	322.15	0.98	77.50	4677.43	1.01	176.76	3889.10	1.77	70.19	2779.03	1.83	77.02	2059.43	1.95	81.99	1.44
TILE_10	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.40	0.99	53.23	4702.20	1.01	147.81	3933.70	1.79	67.93	2798.62	1.84	75.84	2041.53	1.93	76.43	1.45
p1	326.68	0.99	62.25	4681.02	1.01	155.64	3891.07	1.77	69.61	2864.88	1.89	77.26	2219.78	2.10	77.26	1.48
p2	327.43	0.99	64.00	4675.15	1.01	160.65	3896.10	1.77	69.24	2906.47	1.91	74.95	2113.53	2.00	78.30	1.47
TILE_11	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	330.35	1.00	53.67	4687.18	1.01	136.95	3926.38	1.79	68.81	2922.30	1.92	74.59	2086.88	1.97	80.19	1.47
p1	321.98	0.97	63.17	4690.75	1.01	157.35	3931.50	1.79	68.40	2898.47	1.91	75.37	2183.65	2.06	79.79	1.47
p2	328.10	0.99	68.95	4683.35	1.01	165.62	3946.15	1.79	68.19	2817.75	1.86	74.79	1985.95	1.88	80.79	1.44
TILE_12	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	334.40	1.01	61.50	4681.35	1.01	143.49	4082.32	1.86	62.70	3159.50	2.08	67.35	2271.45	2.15	73.42	1.53
p1	326.45	0.99	71.75	4670.77	1.01	158.29	3973.30	1.81	67.27	2822.80	1.86	75.42	2066.25	1.95	81.94	1.46
p2	329.40	1.00	78.50	4653.30	1.00	178.20	3656.15	1.66	81.19	2613.03	1.72	88.63	1807.08	1.71	97.88	1.37
TILE_13	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	330.75	1.00	60.15	4720.25	1.02	138.24	4088.60	1.86	62.56	3055.18	2.01	67.75	2267.00	2.14	73.37	1.52
p1	320.45	0.97	65.00	4681.25	1.01	147.76	4026.03	1.83	65.18	2898.78	1.91	70.77	2024.12	1.91	77.86	1.46
p2	325.48	0.99	74.00	4687.98	1.01	165.23	3755.30	1.71	76.48	2787.15	1.84	83.24	1953.83	1.85	91.48	1.42
TILE_14	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

p0	331.00	1.00	54.00	4715.70	1.02	130.16	3940.50	1.79	67.57	2876.43	1.89	71.23	2165.55	2.05	74.43	1.48
p1	328.30	0.99	62.33	4700.62	1.01	134.30	3876.00	1.76	70.48	2827.25	1.86	74.47	2009.15	1.90	79.26	1.44
p2	328.70	1.00	63.65	4713.05	1.02	134.27	3899.12	1.77	69.81	2994.30	1.97	76.05	2178.88	2.06	80.65	1.49
TILE_15	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	330.10	1.00	59.33	4709.98	1.01	134.45	4157.35	1.89	59.97	3002.75	1.98	65.11	2113.97	2.00	71.12	1.50
p1	326.23	0.99	64.00	4680.02	1.01	147.76	4133.45	1.88	60.78	3102.43	2.04	65.56	2207.03	2.09	71.07	1.51
p2	325.10	0.98	73.50	4683.93	1.01	158.72	4023.95	1.83	65.29	2994.78	1.97	71.08	2222.57	2.10	76.69	1.50
TILE_16	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.07	0.99	86.50	4702.50	1.01	144.55	3911.88	1.78	68.83	2832.20	1.87	73.98	2007.17	1.90	78.88	1.44
p1	329.15	1.00	101.00	4692.27	1.01	161.97	3872.85	1.76	70.12	3004.75	1.98	74.58	2190.45	2.07	79.19	1.49
p2	325.12	0.98	117.00	4672.02	1.01	170.32	3882.20	1.77	69.89	2802.78	1.85	75.75	2088.32	1.97	79.68	1.45
TILE_17	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.73	0.98	89.25	4705.80	1.01	144.59	3932.47	1.79	68.13	2933.55	1.93	73.21	2125.78	2.01	77.25	1.47
p1	328.10	0.99	103.65	4660.38	1.00	172.13	3888.75	1.77	69.52	2920.88	1.92	74.23	2206.75	2.09	77.97	1.48
p2	327.43	0.99	122.60	4640.60	1.00	189.86	3900.93	1.77	69.27	2825.75	1.86	74.45	2020.97	1.91	78.38	1.44
TILE_18	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.45	0.99	81.45	4690.12	1.01	138.63	3830.10	1.74	71.98	2916.95	1.92	74.65	2115.32	2.00	78.03	1.46
p1	329.80	1.00	88.50	4706.88	1.01	151.50	3815.62	1.74	72.81	2791.85	1.84	76.14	2109.07	1.99	78.31	1.45
p2	326.32	0.99	95.50	4700.12	1.01	154.37	3886.70	1.77	69.85	2798.72	1.84	75.72	2007.17	1.90	78.86	1.44
TILE_19	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.55	0.99	80.50	4706.60	1.01	137.98	3951.38	1.80	67.45	2957.30	1.95	72.46	2228.55	2.11	76.44	1.49
p1	328.35	0.99	97.25	4687.65	1.01	153.78	3965.60	1.80	66.95	2860.70	1.88	72.47	2042.42	1.93	76.66	1.46
p2	320.68	0.97	110.50	4668.57	1.01	169.46	3964.90	1.80	66.81	2960.07	1.95	72.28	2135.88	2.02	76.49	1.47
TILE_20	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.98	0.98	93.88	4711.75	1.02	143.40	4115.50	1.87	61.08	3001.45	1.98	64.99	2258.05	2.13	67.95	1.51
p1	328.05	0.99	108.60	4692.10	1.01	159.75	3980.07	1.81	66.35	2994.25	1.97	70.69	2171.22	2.05	74.23	1.49
p2	324.68	0.98	123.00	4652.35	1.00	179.89	3666.38	1.67	79.56	2725.82	1.80	83.99	1992.00	1.88	88.75	1.41
TILE_21	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.73	0.99	94.50	4707.50	1.01	141.27	4125.15	1.88	60.75	3107.30	2.05	64.66	2262.60	2.14	67.54	1.52
p1	327.45	0.99	107.50	4689.82	1.01	152.20	4039.43	1.84	63.85	2956.40	1.95	67.51	2135.40	2.02	70.36	1.49
p2	327.23	0.99	120.75	4682.90	1.01	166.27	3764.85	1.71	74.91	2835.00	1.87	79.52	2145.05	2.03	82.98	1.45
TILE_22	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	332.35	1.01	83.00	4724.90	1.02	135.42	3978.60	1.81	66.20	2939.03	1.94	68.34	2090.95	1.98	72.73	1.48
p1	325.90	0.99	94.50	4694.82	1.01	144.68	3880.05	1.76	70.35	2967.80	1.95	72.46	2133.32	2.02	77.26	1.47
p2	323.60	0.98	104.00	4708.98	1.01	138.82	3872.85	1.76	70.53	2844.38	1.87	74.24	2109.53	1.99	79.02	1.46

TILE_23	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.65	0.99	89.00	4710.25	1.01	139.06	4176.25	1.90	59.11	3053.30	2.01	62.57	2194.80	2.07	65.46	1.51
p1	326.50	0.99	101.50	4677.07	1.01	156.96	4149.07	1.89	59.91	3126.78	2.06	63.59	2387.03	2.26	65.92	1.54
p2	323.60	0.98	114.75	4669.30	1.01	157.91	4043.65	1.84	63.83	3040.32	2.00	68.15	2215.97	2.09	71.07	1.50
TILE_24	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.02	0.98	88.75	4698.50	1.01	135.90	3934.30	1.79	67.49	2964.18	1.95	71.39	2165.43	2.05	73.74	1.48
p1	329.10	1.00	101.50	4673.43	1.01	157.86	3947.55	1.80	66.97	2966.25	1.95	71.48	2263.93	2.14	73.31	1.50
p2	323.60	0.98	115.50	4678.38	1.01	165.17	3931.68	1.79	67.63	2858.88	1.88	72.03	2066.07	1.95	74.20	1.45
TILE_25	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.18	0.99	90.10	4681.32	1.01	133.96	3929.07	1.79	67.67	3061.03	2.02	71.50	2270.28	2.15	73.24	1.50
p1	325.10	0.98	108.25	4693.23	1.01	163.82	3941.65	1.79	67.02	2865.68	1.89	71.54	2178.30	2.06	72.96	1.47
p2	329.05	1.00	124.25	4651.80	1.00	181.30	3933.82	1.79	67.55	2859.72	1.88	71.71	2075.47	1.96	73.36	1.46
TILE_26	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.90	0.99	86.50	4702.98	1.01	135.35	3837.43	1.74	71.69	2921.12	1.92	74.11	2219.68	2.10	76.99	1.48
p1	329.55	1.00	94.00	4678.95	1.01	148.17	3821.57	1.74	72.33	2818.62	1.86	74.72	2013.67	1.90	78.40	1.44
p2	319.57	0.97	99.45	4690.43	1.01	152.68	3870.38	1.76	70.37	2913.22	1.92	74.54	2113.25	2.00	77.97	1.46
TILE_27	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.32	0.99	89.00	4701.77	1.01	134.20	3984.32	1.81	65.62	2906.00	1.91	69.46	2203.68	2.08	71.38	1.49
p1	326.52	0.99	101.75	4685.68	1.01	148.39	3983.57	1.81	65.77	2900.03	1.91	69.66	2106.93	1.99	71.46	1.47
p2	330.77	1.00	114.00	4707.00	1.01	158.93	3974.68	1.81	66.03	3098.53	2.04	69.71	2295.20	2.17	71.22	1.52
TILE_28	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.48	0.99	94.50	4691.10	1.01	138.85	4150.12	1.89	59.31	3047.82	2.01	62.51	2237.45	2.11	62.20	1.52
p1	331.55	1.00	107.50	4687.68	1.01	152.52	3993.75	1.82	65.24	3029.00	1.99	68.55	2253.28	2.13	67.70	1.51
p2	328.43	0.99	119.75	4678.70	1.01	162.57	3699.15	1.68	77.24	2793.50	1.84	81.31	2162.10	2.04	81.20	1.45
TILE_29	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.40	0.99	95.40	4688.75	1.01	140.91	4148.57	1.89	59.25	3048.50	2.01	62.21	2242.10	2.12	61.89	1.52
p1	326.25	0.99	106.75	4677.80	1.01	154.71	4021.07	1.83	64.28	3147.03	2.07	67.46	2365.22	2.24	67.12	1.53
p2	327.27	0.99	119.25	4663.12	1.00	178.62	3810.60	1.73	72.61	2775.40	1.83	77.23	2127.25	2.01	77.14	1.45
TILE_30	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.40	1.00	88.25	4706.95	1.01	128.99	4009.88	1.82	64.45	3023.75	1.99	63.71	2301.93	2.18	65.05	1.52
p1	327.10	0.99	97.50	4722.32	1.02	136.59	3937.88	1.79	67.49	3046.43	2.01	67.51	2344.40	2.22	68.72	1.52
p2	333.98	1.01	104.00	4723.23	1.02	132.30	3923.95	1.78	67.88	2934.65	1.93	68.64	2130.03	2.01	70.37	1.48
TILE_31	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.88	0.98	89.85	4703.70	1.01	131.44	4182.52	1.90	58.24	3187.10	2.10	60.64	2368.18	2.24	60.64	1.55
p1	330.30	1.00	103.75	4692.30	1.01	148.58	4180.52	1.90	58.35	3075.97	2.03	61.03	2352.32	2.22	61.20	1.54

p2	325.80	0.99	117.50	4682.65	1.01	161.42	4089.00	1.86	61.87	3003.28	1.98	64.75	2201.62	2.08	65.21	1.50
TILE_32	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.43	0.99	81.25	4703.82	1.01	141.71	3902.47	1.77	68.95	2919.28	1.92	73.73	2237.38	2.11	75.55	1.48
p1	331.52	1.00	91.50	4675.85	1.01	171.05	3929.55	1.79	67.98	2831.15	1.86	73.57	2056.62	1.94	75.36	1.46
p2	324.57	0.98	99.75	4662.18	1.00	179.91	3918.43	1.78	68.52	2911.93	1.92	74.28	2141.82	2.02	75.78	1.47
TILE_33	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.70	0.99	77.75	4718.15	1.02	138.35	3917.90	1.78	68.41	2816.75	1.85	74.29	2140.97	2.02	75.88	1.46
p1	323.73	0.98	88.25	4688.40	1.01	163.17	3933.62	1.79	67.93	2916.18	1.92	73.96	2143.70	2.03	75.38	1.47
p2	324.43	0.98	98.25	4645.32	1.00	180.84	3898.95	1.77	69.12	2905.68	1.91	74.51	2147.53	2.03	75.33	1.47
TILE_34	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.65	0.99	76.75	4714.65	1.02	129.15	3912.95	1.78	68.84	2886.45	1.90	71.52	2126.18	2.01	77.05	1.47
p1	330.15	1.00	84.00	4702.10	1.01	134.83	3842.30	1.75	71.65	2822.43	1.86	74.76	1993.58	1.88	80.57	1.44
p2	325.75	0.99	84.00	4697.25	1.01	138.59	3870.55	1.76	70.84	2877.30	1.89	77.16	2125.80	2.01	82.05	1.46
TILE_35	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.38	0.99	76.50	4718.48	1.02	129.12	3967.50	1.80	66.74	2856.60	1.88	71.96	2083.90	1.97	73.23	1.46
p1	325.05	0.98	84.00	4696.18	1.01	147.57	3948.05	1.80	67.18	2960.18	1.95	71.90	2172.25	2.05	73.43	1.48
p2	329.68	1.00	90.25	4680.10	1.01	163.87	3968.03	1.80	66.61	2864.50	1.89	72.07	2184.18	2.06	72.80	1.48
TILE_36	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.43	0.98	81.80	4711.23	1.02	136.21	4098.50	1.86	61.89	2950.57	1.94	67.31	2141.72	2.02	69.47	1.49
p1	327.80	0.99	93.00	4680.85	1.01	150.15	3955.10	1.80	67.55	2947.97	1.94	72.92	2249.95	2.13	75.49	1.49
p2	327.27	0.99	99.25	4674.55	1.01	161.21	3693.15	1.68	79.16	2712.93	1.79	86.96	1986.88	1.88	89.09	1.41
TILE_37	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.90	0.98	77.42	4699.32	1.01	134.65	4109.25	1.87	61.57	3064.45	2.02	66.76	2244.60	2.12	68.33	1.51
p1	324.57	0.98	84.00	4688.40	1.01	146.18	4014.03	1.83	65.30	2982.03	1.96	70.68	2292.97	2.17	72.14	1.50
p2	331.12	1.00	91.50	4672.80	1.01	160.81	3780.32	1.72	74.82	2694.55	1.77	81.99	1953.38	1.85	83.79	1.42
TILE_38	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.02	0.99	75.25	4687.40	1.01	133.35	3487.75	1.59	88.49	2633.72	1.73	97.69	1923.88	1.82	101.92	1.38
p1	326.45	0.99	84.00	4709.85	1.01	144.38	3462.03	1.57	89.93	2429.18	1.60	101.09	1798.17	1.70	106.86	1.34
p2	326.05	0.99	84.00	4678.18	1.01	149.92	3487.40	1.59	89.03	2482.53	1.63	97.19	1727.58	1.63	105.86	1.33
TILE_39	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.15	0.98	76.00	4684.90	1.01	135.08	4132.15	1.88	60.49	3082.95	2.03	65.76	2373.30	2.24	66.96	1.53
p1	328.90	1.00	84.00	4693.85	1.01	152.28	4156.30	1.89	59.82	2993.85	1.97	65.01	2186.12	2.07	65.99	1.51
p2	325.98	0.99	88.75	4681.50	1.01	163.54	4032.38	1.83	64.39	3003.60	1.98	69.88	2211.78	2.09	70.74	1.50
TILE_40	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.65	1.00	85.75	4698.27	1.01	137.38	3886.03	1.77	70.05	2778.05	1.83	77.14	2063.55	1.95	81.57	1.45

p1	321.32	0.97	94.00	4683.55	1.01	168.00	3899.82	1.77	69.69	2783.35	1.83	76.42	1986.60	1.88	80.70	1.43
p2	326.12	0.99	102.25	4671.12	1.01	168.40	3855.60	1.75	71.09	2965.57	1.95	76.86	2158.07	2.04	81.12	1.47
TILE_41	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.07	0.99	83.25	4691.98	1.01	141.20	3894.00	1.77	69.92	2768.65	1.82	77.07	1974.70	1.87	81.65	1.43
p1	325.75	0.99	93.00	4668.48	1.01	168.31	3881.93	1.77	70.50	2872.30	1.89	76.77	2065.57	1.95	81.34	1.45
p2	323.57	0.98	101.00	4662.35	1.00	188.40	3875.43	1.76	70.67	2859.40	1.88	77.76	2156.55	2.04	81.43	1.46
TILE_42	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.70	0.99	78.25	4706.30	1.01	131.16	3498.10	1.59	88.18	2573.05	1.69	96.22	1834.70	1.73	102.93	1.36
p1	330.45	1.00	84.00	4688.48	1.01	144.67	3430.97	1.56	91.78	2536.45	1.67	98.98	1789.97	1.69	106.96	1.35
p2	324.55	0.98	84.00	4695.05	1.01	154.49	3483.60	1.58	89.18	2434.72	1.60	100.46	1788.97	1.69	107.31	1.34
TILE_43	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.62	0.99	73.00	4709.93	1.01	126.58	3934.95	1.79	68.56	2811.85	1.85	75.20	1996.30	1.89	80.02	1.44
p1	324.93	0.98	79.33	4694.95	1.01	141.89	3915.40	1.78	69.00	2905.55	1.91	75.06	2196.22	2.08	78.78	1.48
p2	326.27	0.99	85.25	4700.93	1.01	155.23	3943.97	1.79	67.86	2828.38	1.86	74.45	2009.58	1.90	78.74	1.45
TILE_44	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.90	1.00	88.00	4694.43	1.01	142.93	4049.10	1.84	64.03	3009.12	1.98	69.68	2123.55	2.01	75.24	1.49
p1	324.32	0.98	94.00	4681.20	1.01	162.26	3928.93	1.79	69.23	2798.88	1.84	76.42	2037.08	1.93	82.03	1.44
p2	325.45	0.99	102.00	4658.62	1.00	179.84	3659.97	1.66	81.10	2583.55	1.70	90.15	1789.65	1.69	99.18	1.36
TILE_45	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.27	0.98	83.25	4699.98	1.01	133.79	4049.90	1.84	64.15	2992.45	1.97	70.37	2243.20	2.12	75.15	1.50
p1	327.25	0.99	87.50	4699.27	1.01	146.90	3995.22	1.82	66.20	2858.18	1.88	72.83	2101.78	1.99	79.14	1.47
p2	330.80	1.00	94.00	4695.27	1.01	158.60	3731.10	1.70	77.60	2737.00	1.80	85.74	1851.72	1.75	92.95	1.40
TILE_46	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.55	0.99	81.75	4693.32	1.01	136.53	3518.78	1.60	86.90	2582.75	1.70	95.54	1918.00	1.81	102.10	1.38
p1	329.38	1.00	84.00	4688.93	1.01	158.59	3484.95	1.58	88.78	2469.47	1.63	97.97	1720.17	1.63	106.68	1.33
p2	326.90	0.99	84.00	4674.90	1.01	155.79	3454.62	1.57	90.56	2540.70	1.67	99.01	1791.42	1.69	107.42	1.35
TILE_47	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.50	0.99	84.00	4702.23	1.01	127.62	4126.52	1.88	61.34	2954.18	1.95	68.02	2182.07	2.06	73.16	1.50
p1	327.23	0.99	85.00	4703.80	1.01	145.86	4117.27	1.87	61.34	2979.90	1.96	66.38	2107.78	1.99	71.36	1.49
p2	328.90	1.00	94.00	4689.38	1.01	156.60	4014.25	1.83	65.79	2967.05	1.95	72.31	2230.43	2.11	76.78	1.50
TILE_48	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.93	0.99	70.33	4693.55	1.01	138.16	3905.53	1.78	69.64	2793.28	1.84	76.22	1975.08	1.87	81.85	1.44
p1	326.57	0.99	76.67	4671.82	1.01	164.54	3908.45	1.78	69.26	2872.05	1.89	74.56	2091.28	1.98	79.59	1.46
p2	324.35	0.98	84.00	4675.45	1.01	172.15	3882.60	1.77	70.26	2790.88	1.84	76.52	2073.85	1.96	80.99	1.44
TILE_49	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

p0	323.43	0.98	69.75	4715.15	1.02	134.24	3905.18	1.78	69.31	2802.10	1.85	75.76	1979.58	1.87	81.57	1.44
p1	324.70	0.98	74.50	4679.55	1.01	159.10	3873.88	1.76	70.78	2978.45	1.96	75.96	2158.57	2.04	81.72	1.48
p2	327.45	0.99	84.00	4670.38	1.01	171.47	3897.25	1.77	69.76	2791.40	1.84	76.36	2070.68	1.96	81.22	1.45
TILE_50	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.75	0.99	63.00	4706.95	1.01	135.44	3487.62	1.59	88.15	2570.10	1.69	96.26	1832.10	1.73	103.00	1.36
p1	325.82	0.99	67.40	4710.88	1.01	144.66	3420.28	1.56	92.40	2503.47	1.65	101.37	1855.80	1.75	108.51	1.35
p2	328.85	1.00	74.00	4675.85	1.01	151.02	3455.45	1.57	90.20	2459.07	1.62	98.82	1713.30	1.62	107.21	1.33
TILE_51	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	321.90	0.97	69.38	4697.98	1.01	132.68	3909.75	1.78	69.32	3002.28	1.98	74.69	2175.72	2.06	80.20	1.48
p1	328.25	0.99	74.00	4696.98	1.01	148.40	3928.82	1.79	68.50	2811.22	1.85	75.31	2083.82	1.97	80.36	1.46
p2	324.65	0.98	78.50	4680.73	1.01	160.16	3941.60	1.79	68.11	2835.50	1.87	74.03	2001.83	1.89	79.52	1.44
TILE_52	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.68	0.99	104.00	4698.73	1.01	139.19	4073.82	1.85	62.91	3046.72	2.01	67.76	2296.28	2.17	72.15	1.52
p1	322.43	0.98	114.00	4678.02	1.01	165.13	3962.32	1.80	67.57	2843.80	1.87	73.98	2002.08	1.89	80.36	1.44
p2	326.70	0.99	124.75	4650.55	1.00	190.17	3649.32	1.66	81.35	2722.57	1.79	87.01	1935.97	1.83	94.15	1.40
TILE_53	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.93	1.00	107.75	4708.77	1.01	130.95	4083.15	1.86	62.40	2965.90	1.95	67.21	2202.72	2.08	71.67	1.50
p1	326.23	0.99	118.75	4699.93	1.01	143.80	4023.55	1.83	65.05	2917.07	1.92	69.54	2073.88	1.96	74.52	1.47
p2	326.57	0.99	128.75	4679.82	1.01	164.83	3747.05	1.70	76.58	2878.90	1.90	82.46	2081.53	1.97	88.04	1.45
TILE_54	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.85	0.98	97.97	4707.10	1.01	130.89	3495.22	1.59	88.01	2493.12	1.64	95.99	1757.10	1.66	102.51	1.34
p1	324.90	0.98	105.25	4691.45	1.01	140.99	3425.43	1.56	92.09	2520.88	1.66	100.16	1784.72	1.69	108.04	1.34
p2	324.95	0.98	114.00	4700.70	1.01	147.63	3460.43	1.57	90.28	2505.80	1.65	101.62	1879.65	1.78	106.28	1.36
TILE_55	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	322.98	0.98	108.50	4705.30	1.01	130.92	4144.80	1.88	60.34	3098.97	2.04	65.40	2230.15	2.11	69.84	1.52
p1	325.05	0.98	116.00	4684.90	1.01	147.19	4114.20	1.87	61.38	3106.50	2.05	65.08	2243.57	2.12	69.04	1.52
p2	325.43	0.99	127.50	4693.15	1.01	156.54	4027.85	1.83	64.85	2908.50	1.92	70.33	2164.72	2.05	74.75	1.48
TILE_56	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.18	0.99	88.25	4703.82	1.01	138.84	3920.65	1.78	68.15	2837.72	1.87	73.24	2028.42	1.92	77.45	1.45
p1	328.95	1.00	94.00	4674.12	1.01	154.70	3913.57	1.78	68.64	2889.72	1.90	75.62	2197.68	2.08	78.16	1.48
p2	327.00	0.99	100.75	4667.73	1.01	166.60	3928.65	1.79	67.89	2739.85	1.80	78.79	1978.80	1.87	81.15	1.43
TILE_57	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.43	0.99	84.50	4708.43	1.01	135.83	3905.62	1.78	68.68	2937.38	1.93	73.14	2132.53	2.02	76.20	1.47
p1	325.45	0.99	94.00	4691.88	1.01	146.18	3919.45	1.78	68.05	2815.22	1.85	74.51	2123.28	2.01	77.04	1.46
p2	329.90	1.00	103.75	4667.85	1.01	166.08	3920.85	1.78	67.92	2851.20	1.88	77.70	2086.22	1.97	80.25	1.46

TILE_58	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.73	1.00	84.00	4700.55	1.01	130.19	3879.93	1.76	69.85	2889.68	1.90	75.69	2169.65	2.05	80.88	1.47
p1	329.00	1.00	84.00	4707.65	1.01	142.49	3874.30	1.76	70.41	2859.07	1.88	77.42	2064.12	1.95	82.23	1.46
p2	325.88	0.99	84.00	4669.15	1.01	154.14	3888.45	1.77	69.80	2775.65	1.83	76.96	2011.50	1.90	78.90	1.44
TILE_59	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.82	0.99	83.75	4701.95	1.01	131.23	3946.78	1.79	67.36	2951.12	1.94	72.34	2236.85	2.11	75.63	1.49
p1	331.10	1.00	84.03	4682.02	1.01	147.07	3962.32	1.80	66.57	2864.25	1.89	72.10	2047.62	1.94	76.01	1.46
p2	330.30	1.00	94.00	4668.38	1.01	163.66	3899.18	1.77	69.12	2899.72	1.91	75.47	2105.85	1.99	78.41	1.47

p0_score:	88.51
p1_score:	87.83
p2_score:	86.59

Infrastructure_Operations_Scores:	vmotion	svmotion	deploy
Completed_Ops_PerHour	33.00	22.00	10.00
Avg_Seconds_To_Complete	42.57	25.85	346.14
Failures	0.00	0.00	0.00
Ratio	2.06	2.44	2.50
Number_Of_Threads	2	2	2

Summary	Run_Is_Compliant	Turbo_Setting:0
	Number_Of_Compliance_Issues(0)*	Median_Phase(p1)
Unreviewed_VMmark2_Applications_Score	87.83	
Unreviewed_VMmark2_Infrastructure_Score	2.33	
Unreviewed_VMmark2_Score	70.73	

Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESXi 5.5.0 Build 1331820 / 09-22-2013
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 5.5.0 Build 1312298 / 09-22-2013
Supplemental Software	none

Servers	
Quantity	4 (realized as completely independent system partitions in two PRIMEQUEST 2800E systems)
Server Manufacturer and Model	Fujitsu PRIMEQUEST 2800E
Processor Vendor and Model	Intel Xeon E7-8890 v2
Processor Speed (GHz)	2.8
Total Sockets/Total Cores/Total Threads	4 Sockets / 60 Cores / 120 Threads (per system partition)
Primary Cache	32KB I + 32KB D on chip per core
Secondary Cache	256KB I+D on chip per core
Other Cache	37.5MB I+D on chip per chip L3
BIOS Version	1.39
Memory Size (in GB, Number of DIMMs)	1TB, 64 (per system partition)
Memory Type and Speed	16GB DIMMs 2Rx4 L DDR3-1600 R ECC
Disk Subsystem Type	FC SAN
Number of Disk Controllers	0
Disk Controller Vendors and Models	
Number of Host Bus Adapters	1 (per system partition)
Host Bus Adapter Vendors and Models	Dual port Emulex LPe16002
Number of Network Controllers	2 (per system partition)
Network Controller Vendors and Models	One Emulex OneConnect Dual Port 10GbE Adapter One Intel I350 Dual Port 1GbE Adapter
Other Hardware	One IO unit per system partition
Other Software	none
Hardware Availability Date (MM-DD-YYYY)	06-29-2014
Software Availability Date (MM-DD-YYYY)	09-22-2013
Network	
Network Switch Vendors and Models	Cisco Catalyst 4900M
Network Speed	1Gbps for SUT management, Clients and VMotion, 10Gbps for all VMs
Storage	

Array Vendors, Models, and Firmware Versions	3xFujitsu PRIMERGY RX300 S8, Firmware V4.6.5.4 R1.1.0 1xFujitsu ETERNUS DX80, Firmware version V10L20-0000
Fibre Channel Switch Vendors and Models	Brocade 5100
Disk Space Used	17.3TB
Array Cache Size	1GB(PRIMERGY RX300 S8), 2GB(ETERNUS DX80)
Total Number of Physical Disks Used	4 HDDs, 32xSAS-SSDs, 6xPCIe-SSD
Total Number of Enclosures/Pods/Shelves Used	4 (one per storage system)
Number of Physical Disks Used per Enclosure/Pod/Shelf	Details in section Storage Notes
Total Number of Storage Groups Used	0
Number of LUNs Used	82
LUN Size and Number of Disks Per LUN	Details in section Storage Notes
RAID Type	0
Number of Members per RAID Set	Details in section Storage Notes
Disk Vendors, Models, and Speeds	4xSeagate, ST3450856SS, 32krpm; 32xSSD Toshiba PX02SMF040; 6xFusion-io ioDrive2 1.2TB PCIe SSD

Datacenter Management Server	
System Model	PRIMERGY BX620 S5
Processor Vendor and Model	Intel Xeon X5570
Processor Speed (GHz)	2.93
Total Sockets/Total Cores/Total Threads	2 Sockets / 8 Cores / 16 Threads
Memory	Hypervisor: 24GB Virtual Center VM: 10GB
Network Controller(s) Vendors and Models	3 Intel Dual port 82575EB
Operating System, Version, Bitness, and Service Pack	Hypervisor: VMware ESXi 5.1.0 Build 799733 Virtual Center VM: Windows Server 2008 R2 Enterprise 64-bit
Other Hardware	none
Other Software	none

Clients

Total Number of Clients / Total Physical Clients / Total Virtual Client Hosts	61 / 1 / 4
System Model(s)	1xPRIMERGY BX620 S5 (Prime Client) 2xPRIMERGY RX600 S6 (Virtual Client Hosts) 2xPRIMERGY RX500 S7 (Virtual Client Hosts)
Processor Vendor(s) and Model(s)	Prime Client: Intel Xeon Intel Xeon X5570 Virtual Client Hosts: PRIMERGY RX600 S6: Intel Xeon E7-4870 PRIMERGY RX500 S7: Intel Xeon E5-4650
Processor Speed(s) (GHz)	Prime Client: 2.93 Virtual Client Hosts: PRIMERGY RX600 S6: 2.4 PRIMERGY RX500 S7: 2.7
Total Sockets/Total Cores/Total Threads	Prime Client: 2 Sockets / 8 Cores / 16 Threads Virtual Client Hosts: PRIMERGY RX600 S6: 4 Sockets / 40 Cores / 80 Threads PRIMERGY RX500 S7: 4 Sockets / 32 Cores / 64 Threads
Memory per Physical Client	Prime Client: 12GB Virtual Client Hosts: 512GB
Network Controller(s) Vendors and Models	Prime Client: Three Intel Dual Port 82575EB Virtual Client Hosts: PRIMERGY RX600 S6: Intel Quad Port 82571EB, two Intel Dual Port 82576NS PRIMERGY RX500 S7: Embedded Intel I350 Dual Port, Intel Quad Port 82571EB, Intel Dual Port 82571EB
Operating System, Version, Bitness, and Service Pack	Clients: Windows Server 2008 Enterprise 64-bit SP2 Virtual Client Hosts: PRIMERGY RX600 S6: VMware ESX 4.1 U2 Build 502767 PRIMERGY RX500 S7: VMware ESX 4.1 U3 Build 800380
Number of Virtual Clients	60
Number of vCPUs Per Virtual Client	4
Number of vMem (GB) Per Virtual Client	4
Virtual Client Networking Notes	All virtual clients were distributed evenly over 6 vSwitches per Virtual Client Host
Virtual Client Storage Notes	none
Other Hardware	One Dual Port Emulex LPe12002 for each virtual client host, two shared Fujitsu ETERNUS DX80 each with 24x300GB disks
Other Software	none

Notes for Workload

Virtualization Software Notes

- Floppy and CDROM removed for all VMs (default enabled)
- Hardware version 7 used for all VMs
- VMware Tools build 9344 used for all VMs (default 9344)
- Logging disabled for all VMs (default enabled)
- Logical CPU layout changed for all VMs (except Standby and Mailserver) to one socket with multiple cores (default: multiple sockets with one core per socket)
- SCSI adapter type PVSCSI used for all Standby VMs (default LSI Logic parallel)
- SCSI adapter type PVSCSI used for all Mailserver and Linux VMs (default LSI Logic SAS)
- VMXNET3 enabled for all VMs (default VMXNET2)
- vSphere DRS Migration Threshold set to Fully Automated level 2

Changes in esx.conf:

- /adv/Cpu/CreditAgePeriod = 1000 (default 3000)
- /adv/Cpu/HTWholeCoreThreshold = 0 (default 200)
- /adv/DataMover/HardwareAcceleratedInit = 0 (default 1)
- /adv/DataMover/HardwareAcceleratedMove = 0 (default 1)
- /adv/Mem/BalancePeriod = 0 (default 15)
- /adv/Mem/SamplePeriod = 0 (default 60)
- /adv/Mem/ShareScanGHz = 0 (default 4)
- /adv/Misc/TimerMaxHardPeriod = 4000 (default 100000)
- /adv/Net/MaxNetifRxQueueLen = 500 (default 100)
- /adv/Net/MaxNetifTxQueueLen = 1000 (default 500)
- /adv/Net/NetTxCompletionWorldlet = 0 (default 1)
- /adv/Net/NetTxWorldlet = 1 (default 2)
- /adv/Numa/LTermFairnessInterval = 0 (default 5)
- /adv/Numa/MigImbalanceThreshold = 57 (default 10)
- /adv/Numa/MonMigEnable = 0 (default 1)
- /adv/Numa/PageMigEnable = 0 (default 1)
- /adv/Numa/RebalancePeriod = 60000 (default 2000)
- /adv/Numa/SwapLoadEnable = 0 (default 1)
- /adv/Numa/SwapLocalityEnable = 0 (default 1)
- /adv/Power/CpuPolicy = static (default balanced)
- /adv/VMFS3/HardwareAcceleratedLocking = 0 (default 1)

Server Notes

- The PRIMEQUEST 2800E can be split up into 1 to 4 completely independent system partitions with dedicated HW. Each partition is treated as a separate ESXi host.
  For this VMmark result two partitions (containing two system boards and one IO Unit) were configured on each of two PRIMEQUEST 2800E.

  Partition settings:
  - Memory Operation Mode: Performance Mode (default Normal Mode)
  - PCI Address Mode: PCI Bus Mode (default PCI Segment Mode)

- Server/Partition BIOS settings:
  - Adjacent Cache Line Prefetch: Disabled (default enabled)

- DIMM Speed: Performance Mode (default Normal Mode)
- Energy Performance: Performance (default Energy Efficient)
- Hardware Prefetcher: Disabled (default enabled)
- Turbo Boost Technology: Enabled (Intel Turbo Boost up to 3.4GHz, default enabled)

Networking Notes

- One dedicated VLAN for the systems under test, vCenter Server and Benchmark Controller (SUT-VLAN)
- One dedicated VLAN for the VMs and Clients (Load-VLAN)

- vSwitch Configuration:
  - vSwitch0 on vmnic0 for Service Console (1Gb)
  - vSwitch1 on vmnic1 for VMotion (1Gb)
  - vSwitch2 on vmnic2 (10Gb) DS2, Deploy and Standby VMs for all tiles
  - vSwitch3 on vmnic3 (10Gb) Mailserver and Olio VMs for all tiles

Storage Notes

- First PRIMERGY RX300 S8 configured as a Fibre Channel Target:

  - Hardware details:
    - Two Intel Xeon E5-2667@3.3GHz processors
    - 128GB RAM (8x16 GB dual rank PC3-12800 Registered DDR3 / 1600 MHz DIMMs)
    - One QLogic QLE2562 8Gb FC HBA used as FC target controller
    - One Fujitsu RAID SAS 6G Controller with 1GB Cache and BBU (D3116)
    - 11x400GB SAS-SSDs Toshiba PX02SMF040
    - 2xFusion-io ioDrive2 1.2TB PCIe-SSD

  - Software details:
    - Operating System: SUSE Linux Enterprise Server 11 SP3 - 3.0.101-0.8 (64-bit)
    - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11 SP3)

RAID configuration:

  - SAS-SSD 1:
    - LUN 1: Storage system OS (12GB, this LUN is not counted in the Storage section)
    - LUN 2: First Target LUN for Storage VMotion (10GB)
    - LUN 3: First Source LUN for Deploy (10GB)
    - LUN 4: First Target LUN for Deploy (10GB)

  - SAS-SSD 2:
    - LUN 1: All VMs for Tile 0 except DS2DB, Standby and second Mailserver VHD (186GB)
    - LUN 2: All VMs for Tile 1 except DS2DB, Standby and second Mailserver VHD (186GB)

  - SAS-SSD 3:
    - LUN 1: All VMs for Tile 2 except DS2DB, Standby and second Mailserver VHD (186GB)
    - LUN 2: All VMs for Tile 3 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 4:
        - LUN 1: All VMs for Tile 4 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 5 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 5:
        - LUN 1: All VMs for Tile 6 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 7 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 6:
        - LUN 1: All VMs for Tile 8 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 9 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 7:
        - LUN 1: All VMs for Tile 10 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 11 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 8:
        - LUN 1: All VMs for Tile 12 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 13 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 9:
        - LUN 1: All VMs for Tile 14 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 15 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 10:
        - LUN 1: All VMs for Tile 48 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 49 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 11:
        - LUN 1: All VMs for Tile 50 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 51 except DS2DB, Standby and second Mailserver VHD (186GB)

    - First PCIe-SSD:
        - LUN 1: DS2DB VMs for tiles 0, 2, 4, 6, 8, 10, 12, 14, 48, 50 (537GB)
        - LUN 2: DS2DB VMs for tiles 1, 3, 5, 7, 9, 11, 13, 15, 49, 51 (537GB)

    - Second PCIe-SSD:
        - LUN 1: Mailserver and Standby VMs for tiles 0, 2, 4, 6, 8, 10, 12, 14, 48, 50 (537GB)
        - LUN 2: Mailserver and Standby VMs for tiles 1, 3, 5, 7, 9, 11, 13, 15, 49, 51 (537GB)

    - All LUNs were configured as block devices; no system memory was used for caching

- Second PRIMERGY RX300 S8 configured as a Fibre Channel Target:

    - Hardware details:
        - Two Intel Xeon E5-2667@3.3GHz processors
        - 128GB RAM (8x16 GB dual rank PC3-12800 Registered DDR3 / 1600 MHz DIMMs)
        - One QLogic QLE2562 8Gb FC HBA used as FC target controller

        - One Fujitsu RAID SAS 6G Controller with 1GB Cache and BBU (D3116)
        - 11x400GB SAS-SSDs Toshiba PX02SMF040
        - 2xFusion-io ioDrive2 1.2TB PCIe-SSD

    - Software details:
        - Operating System: SUSE Linux Enterprise Server 11 SP3 - 3.0.101-0.8 (64-bit)
        - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11 SP3)

RAID configuration:

    - SAS-SSD 1:
        - LUN 1: Storage system OS (12GB, this LUN is not counted in the Storage section)
        - LUN 2: Second Target LUN for Storage VMotion (10GB)
        - LUN 3: Second Source LUN for Deploy (10GB)
        - LUN 4: Second Target LUN for Deploy (10GB)

    - SAS-SSD 2:
        - LUN 1: All VMs for Tile 16 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 17 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 3:
        - LUN 1: All VMs for Tile 18 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 19 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 4:
        - LUN 1: All VMs for Tile 20 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 21 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 5:
        - LUN 1: All VMs for Tile 22 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 23 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 6:
        - LUN 1: All VMs for Tile 24 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 24 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 7:
        - LUN 1: All VMs for Tile 26 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 27 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 8:
        - LUN 1: All VMs for Tile 28 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 29 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 9:
        - LUN 1: All VMs for Tile 30 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 31 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 10:
        - LUN 1: All VMs for Tile 52 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 53 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 11:
        - LUN 1: All VMs for Tile 54 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 55 except DS2DB, Standby and second Mailserver VHD (186GB)

    - First PCIe-SSD:
        - LUN 1: DS2DB VMs for tiles 16, 18, 20, 22, 24, 26, 28, 30, 52, 54 (537GB)
        - LUN 2: DS2DB VMs for tiles 17, 19, 21, 23, 25, 27, 29, 31, 53, 55 (537GB)

    - Second PCIe-SSD:
        - LUN 1: Mailserver and Standby VMs for tiles 16, 18, 20, 22, 24, 26, 28, 30, 52, 54 (537GB)
        - LUN 2: Mailserver and Standby VMs for tiles 17, 19, 21, 23, 25, 27, 29, 31, 53, 55 (537GB)

    - All LUNs were configured as block devices; no system memory was used for caching

- Third PRIMERGY RX300 S8 configured as a Fibre Channel Target:

    - Hardware details:
        - Two Intel Xeon E5-2667@3.3GHz processors
        - 128GB RAM (8x16 GB dual rank PC3-12800 Registered DDR3 / 1600 MHz DIMMs)
        - One QLogic QLE2562 8Gb FC HBA used as FC target controller
        - One Fujitsu RAID SAS 6G Controller with 1GB Cache and BBU (D3116)
        - 11x400GB SAS-SSDs Toshiba PX02SMF040
        - 2xFusion-io ioDrive2 1.2TB PCIe-SSD

    - Software details:
        - Operating System: SUSE Linux Enterprise Server 11 SP3 - 3.0.101-0.8 (64-bit)
        - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11 SP3)

RAID configuration:

    - SAS-SSD 1: (this SSD is not counted in the Storage section)
        - LUN 1: Storage system OS (12GB, this LUN is not counted in the Storage section)

    - SAS-SSD 2:
        - LUN 1: All VMs for Tile 32 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 33 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 3:
        - LUN 1: All VMs for Tile 34 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 35 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 4:
        - LUN 1: All VMs for Tile 36 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 37 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 5:
        - LUN 1: All VMs for Tile 38 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 39 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 6:
        - LUN 1: All VMs for Tile 40 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 41 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 7:
        - LUN 1: All VMs for Tile 42 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 43 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 8:
        - LUN 1: All VMs for Tile 44 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 45 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 9:
        - LUN 1: All VMs for Tile 46 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 47 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 10:
        - LUN 1: All VMs for Tile 56 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 57 except DS2DB, Standby and second Mailserver VHD (186GB)

    - SAS-SSD 11:
        - LUN 1: All VMs for Tile 58 except DS2DB, Standby and second Mailserver VHD (186GB)
        - LUN 2: All VMs for Tile 59 except DS2DB, Standby and second Mailserver VHD (186GB)

    - First PCIe-SSD:
        - LUN 1: DS2DB VMs for tiles 32, 34, 36, 38, 40, 42, 44, 46, 56, 58 (537GB)
        - LUN 2: DS2DB VMs for tiles 33, 35, 37, 39, 41, 43, 45, 47, 57, 59 (537GB)

    - Second PCIe-SSD:
        - LUN 1: Mailserver and Standby VMs for tiles 32, 34, 36, 38, 40, 42, 44, 48, 56, 58 (537GB)
        - LUN 2: Mailserver and Standby VMs for tiles 33, 35, 37, 39, 41, 43, 45, 47, 57, 59 (537GB)

    - All LUNs were configured as block devices; no system memory was used for caching

- ETERNUS DX80 (4 disks)
    - RAID set 0: (4 disks)
        - LUN 0: Boot/Console OS for SUT1 (11GB)
        - LUN 1: Boot/Console OS for SUT2 (11GB)
        - LUN 2: Boot/Console OS for SUT3 (11GB)
        - LUN 3: Boot/Console OS for SUT4 (11GB)

Datacenter Management Server Notes

- Virtual Center VM configured with four vCPUs and 10GB vMEM

Operating System Notes

- Mailserver VMs: Microsoft Windows 2008 R2 Enterprise 64-bit.

- Linux VMs : All SLES11 VMs were updated with SP2
  VMXNET3 driver configured to use one receive and one request queue (default: number of queues matches the number of vCPUs)
  Paravirtualized drivers (VMXNET3, PVSCSI, VMMEMCTL) compiled with gcc 4.3.4

- The file systems of all Linux and Standby VMs were aligned to a 4KB boundary

Software Notes

- Mailserver VMs: Microsoft Exchange 2007 Enterprise x64 Edition updated with SP3.

Client Notes

- Prime Client was running VMware vSphere PowerCLI 5.1 Release 1 Build 793510.
- Prime Client was updated via Windows Update.
- Virtual Client Hosts:
  - System 1 (PRIMERGY RX600 S6): Clients 0, 4, 8, 12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56
  - System 2 (PRIMERGY RX600 S6): Clients 1, 5, 9, 13, 17, 21, 25, 29, 33, 37, 41, 45, 49, 53, 57
  - System 3 (PRIMERGY RX500 S7): Clients 2, 6, 10, 14, 18, 22, 26, 30, 34, 38, 42, 46, 50, 54, 58
  - System 4 (PRIMERGY RX500 S7): Clients 3, 7, 11, 15, 19, 23, 27, 31, 35, 39, 43, 47, 51, 55, 59

Other Notes

- One client used as a dedicated Benchmark Controller.

- TILEDELAY reduced to 48 seconds (default 60 seconds)

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit www.vmware.com/products/vmmark.

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of VMware, Inc. VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.