

## VMware® VMmark® V2.5.2 Results

Vendor and Hardware Platform: Huawei FusionServer CH121 V3  
 Virtualization Platform: VMware ESXi 6.0.0 Build 2494585  
 VMware vCenter Server : VMware vCenter Server 6.0.0 Build 2559268

**VMmark V2.5.2 Score =  
26.64 @ 22 Tiles**

Number of Hosts: 2

Uniform Hosts [yes/no]: yes

Total sockets/cores/threads in test: 4/72/144

Tested By: Huawei Technologies Co.,Ltd.

Test Date: 7-21-2015

Performance Section

[Performance](#)

Configuration Section

[Configuration](#)

Notes Section

[Notes for Workload](#)

### Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.60	1.00	64.00	4760.27	1.03	79.48	4239.15	1.93	56.60	3233.93	2.13	63.82	2329.22	2.20	69.27	1.56
p1	330.38	1.00	71.00	4726.27	1.02	120.98	4030.40	1.83	63.77	2980.12	1.96	66.61	2162.43	2.04	74.33	1.50
p2	328.60	1.00	79.75	4701.07	1.01	150.13	3942.88	1.79	67.20	2939.70	1.94	74.22	2072.85	1.96	81.38	1.47
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.45	0.99	84.00	4701.12	1.01	141.04	3858.62	1.75	72.64	2972.90	1.96	73.12	2317.18	2.19	70.64	1.50
p1	320.12	0.97	103.50	4677.05	1.01	171.86	3916.28	1.78	66.90	2895.65	1.91	68.73	2146.30	2.03	67.14	1.46
p2	329.62	1.00	105.50	4643.62	1.00	216.85	3792.62	1.72	72.08	2910.57	1.92	73.48	2177.45	2.06	72.08	1.47
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.45	0.99	93.47	4690.55	1.01	138.20	4010.55	1.82	63.38	3039.18	2.00	61.82	2253.22	2.13	67.12	1.51
p1	327.98	0.99	104.95	4652.10	1.00	202.83	3793.32	1.72	71.66	2830.68	1.86	72.72	2091.50	1.98	70.95	1.45
p2	326.18	0.99	117.50	4577.55	0.99	248.93	3694.45	1.68	75.52	3021.75	1.99	72.88	2218.78	2.10	75.51	1.47
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.40	0.99	108.00	4675.27	1.01	166.21	3893.55	1.77	70.25	2846.38	1.87	73.99	2162.82	2.04	73.26	1.47
p1	324.40	0.98	114.00	4662.77	1.00	179.94	3903.82	1.78	67.62	2866.75	1.89	70.61	2036.10	1.92	75.59	1.45
p2	322.50	0.98	114.00	4579.40	0.99	295.99	3793.50	1.72	71.98	2866.28	1.89	75.62	2163.57	2.04	79.26	1.45
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.12	1.00	88.95	4681.12	1.01	143.23	3958.12	1.80	65.16	3001.25	1.98	63.58	2150.85	2.03	66.61	1.49
p1	331.10	1.00	94.97	4681.07	1.01	167.50	3918.45	1.78	66.72	2965.43	1.95	70.74	2217.95	2.10	68.99	1.49
p2	325.95	0.99	108.00	4607.65	0.99	246.80	3777.53	1.72	72.96	2812.57	1.85	73.73	2119.18	2.00	76.57	1.44
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

<b>p0</b>	329.10	1.00	80.25	4676.98	1.01	146.50	3934.88	1.79	67.83	3005.40	1.98	65.30	2082.05	1.97	72.68	1.48
<b>p1</b>	327.82	0.99	103.75	4668.68	1.01	157.05	3958.47	1.80	65.22	2978.78	1.96	70.00	2150.88	2.03	73.55	1.48
<b>p2</b>	330.18	1.00	105.25	4665.02	1.01	175.38	3873.62	1.76	68.38	2766.35	1.82	76.19	2054.50	1.94	80.80	1.44
<b>TILE_6</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	327.32	0.99	94.00	4701.45	1.01	141.04	4079.18	1.85	61.38	2954.68	1.95	65.97	2098.78	1.98	70.79	1.48
<b>p1</b>	330.15	1.00	100.25	4673.88	1.01	172.25	4049.45	1.84	62.60	3004.75	1.98	68.21	2220.15	2.10	76.08	1.50
<b>p2</b>	327.05	0.99	112.50	4592.20	0.99	249.83	3919.50	1.78	67.75	2804.93	1.85	74.07	1918.75	1.81	85.02	1.42
<b>TILE_7</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	329.45	1.00	74.00	4750.98	1.02	81.75	4221.00	1.92	59.31	3056.55	2.01	63.43	2232.05	2.11	63.10	1.53
<b>p1</b>	331.38	1.00	74.00	4751.98	1.02	99.40	4160.73	1.89	60.25	3163.22	2.08	62.18	2352.78	2.22	68.64	1.55
<b>p2</b>	328.73	1.00	74.00	4714.40	1.02	135.21	4011.40	1.82	66.01	3081.82	2.03	66.26	2141.47	2.02	76.35	1.50
<b>TILE_8</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.82	0.99	74.60	4734.35	1.02	89.80	4099.12	1.86	62.30	3035.03	2.00	68.68	2231.53	2.11	70.20	1.51
<b>p1</b>	325.62	0.99	76.00	4726.48	1.02	105.81	4032.53	1.83	64.83	2928.00	1.93	74.19	2233.05	2.11	76.90	1.50
<b>p2</b>	327.77	0.99	84.00	4672.43	1.01	181.18	3887.55	1.77	71.27	2740.35	1.80	79.78	1972.53	1.86	82.76	1.43
<b>TILE_9</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.52	0.99	64.00	4752.95	1.02	89.55	3991.47	1.81	68.57	3221.00	2.12	60.09	2319.22	2.19	64.89	1.53
<b>p1</b>	329.40	1.00	64.00	4719.95	1.02	125.00	3982.57	1.81	66.01	3001.20	1.98	65.40	2272.43	2.15	67.30	1.51
<b>p2</b>	326.35	0.99	68.50	4637.60	1.00	216.09	3853.62	1.75	71.16	2971.82	1.96	71.69	2203.35	2.08	72.34	1.48
<b>TILE_10</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.70	0.99	60.25	4752.90	1.02	84.55	4267.98	1.94	55.91	3279.75	2.16	62.20	2416.68	2.28	64.49	1.57
<b>p1</b>	327.55	0.99	64.00	4734.23	1.02	103.03	4061.25	1.85	63.17	2968.75	1.95	67.67	2275.12	2.15	67.57	1.51
<b>p2</b>	327.02	0.99	75.25	4675.57	1.01	187.95	3988.93	1.81	65.87	2888.70	1.90	72.19	2073.07	1.96	75.33	1.46
<b>TILE_11</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	329.93	1.00	118.38	4752.88	1.02	88.22	3984.43	1.81	69.15	3037.53	2.00	70.06	2361.40	2.23	69.58	1.53
<b>p1</b>	326.60	0.99	88.00	4739.73	1.02	93.43	3974.32	1.81	66.37	2969.40	1.96	67.03	2058.35	1.95	76.12	1.47
<b>p2</b>	325.27	0.98	76.75	4716.35	1.02	120.47	3824.68	1.74	72.23	2980.20	1.96	71.52	2059.85	1.95	83.21	1.46
<b>TILE_12</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	328.00	0.99	74.88	4730.55	1.02	91.07	4375.25	1.99	53.60	3104.50	2.04	60.17	2328.10	2.20	63.60	1.55
<b>p1</b>	329.32	1.00	74.00	4719.27	1.02	110.17	4111.18	1.87	62.31	3100.47	2.04	65.19	2195.85	2.08	72.54	1.52
<b>p2</b>	327.60	0.99	74.75	4641.77	1.00	180.19	4056.45	1.84	64.78	3011.30	1.98	69.62	2166.78	2.05	74.72	1.49
<b>TILE_13</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	326.12	0.99	64.67	4737.38	1.02	91.77	4158.18	1.89	61.55	3041.68	2.00	64.93	2298.47	2.17	65.95	1.53
<b>p1</b>	326.68	0.99	64.00	4747.20	1.02	99.05	4279.70	1.95	56.04	3025.43	1.99	64.51	2222.20	2.10	63.92	1.52
<b>p2</b>	328.12	0.99	70.90	4702.62	1.01	146.26	4198.77	1.91	58.81	3111.72	2.05	69.97	2350.97	2.22	68.43	1.54
<b>TILE_14</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

<b>p0</b>	325.88	0.99	139.97	4749.70	1.02	83.09	4066.05	1.85	62.95	3138.35	2.07	58.96	2239.72	2.12	62.97	1.52
<b>p1</b>	324.45	0.98	99.50	4749.62	1.02	105.37	3956.72	1.80	66.92	3068.32	2.02	67.31	2195.70	2.08	72.30	1.50
<b>p2</b>	323.32	0.98	102.25	4708.23	1.01	148.19	3812.82	1.73	73.35	3015.62	1.99	69.96	2256.12	2.13	75.10	1.49
<b>TILE_15</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	326.30	0.99	74.00	4762.85	1.03	79.85	4236.77	1.93	58.84	2943.43	1.94	72.74	2376.95	2.25	61.14	1.53
<b>p1</b>	321.80	0.97	74.00	4732.07	1.02	109.04	4182.77	1.90	59.50	3077.72	2.03	66.58	2376.25	2.25	60.24	1.54
<b>p2</b>	326.57	0.99	81.25	4684.57	1.01	171.60	4012.95	1.82	65.56	2882.97	1.90	72.06	2302.90	2.18	64.99	1.50
<b>TILE_16</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.98	0.99	62.33	4747.18	1.02	83.90	4075.53	1.85	62.85	2986.45	1.97	66.21	2163.22	2.04	67.83	1.50
<b>p1</b>	328.55	0.99	63.00	4725.52	1.02	127.60	3918.28	1.78	68.90	3117.35	2.05	69.52	2342.68	2.21	69.09	1.52
<b>p2</b>	325.80	0.99	70.97	4663.48	1.00	173.70	3807.85	1.73	73.41	2775.18	1.83	77.82	2159.68	2.04	75.67	1.45
<b>TILE_17</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	324.48	0.98	74.10	4736.93	1.02	88.45	4029.97	1.83	64.74	3087.53	2.03	68.40	2269.00	2.14	67.60	1.52
<b>p1</b>	319.20	0.97	64.00	4749.18	1.02	98.40	3923.03	1.78	68.33	3100.28	2.04	65.49	2323.03	2.20	70.19	1.51
<b>p2</b>	327.73	0.99	68.42	4674.07	1.01	180.77	3794.10	1.73	73.47	2956.93	1.95	68.23	2057.32	1.94	75.97	1.46
<b>TILE_18</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	330.88	1.00	77.22	4756.95	1.02	91.58	4155.75	1.89	60.45	3111.95	2.05	65.11	2239.38	2.12	69.23	1.53
<b>p1</b>	326.00	0.99	73.97	4730.85	1.02	110.35	4101.38	1.86	62.85	2959.70	1.95	72.81	2255.12	2.13	74.92	1.51
<b>p2</b>	326.18	0.99	75.00	4641.95	1.00	209.39	3984.15	1.81	67.55	2803.25	1.85	76.27	1984.12	1.88	81.56	1.44
<b>TILE_19</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	325.98	0.99	56.25	4773.52	1.03	79.31	4099.90	1.86	62.12	3258.50	2.15	62.67	2438.12	2.30	63.44	1.56
<b>p1</b>	331.30	1.00	70.25	4732.15	1.02	98.46	4110.70	1.87	61.16	2938.60	1.94	68.42	2365.65	2.24	61.46	1.53
<b>p2</b>	321.62	0.97	69.00	4695.80	1.01	141.61	4017.45	1.83	65.04	2834.22	1.87	74.45	2239.78	2.12	63.36	1.48
<b>TILE_20</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	331.65	1.00	96.25	4756.18	1.02	90.34	4195.90	1.91	58.90	3090.80	2.04	66.24	2392.82	2.26	65.77	1.55
<b>p1</b>	327.70	0.99	83.75	4719.27	1.02	108.60	3963.15	1.80	67.17	2924.18	1.93	69.68	2084.65	1.97	73.64	1.47
<b>p2</b>	324.15	0.98	75.75	4662.62	1.00	211.52	3890.78	1.77	69.95	2931.97	1.93	74.49	2152.35	2.03	75.75	1.47
<b>TILE_21</b>	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
<b>p0</b>	331.05	1.00	101.72	4758.48	1.03	85.53	4171.75	1.90	60.87	3141.72	2.07	65.31	2340.85	2.21	70.31	1.55
<b>p1</b>	329.88	1.00	84.00	4714.68	1.02	119.53	4084.57	1.86	63.08	3152.85	2.08	58.09	2109.82	1.99	72.02	1.51
<b>p2</b>	325.07	0.98	92.75	4622.62	1.00	217.30	3909.80	1.78	69.58	3213.25	2.12	60.52	2129.97	2.01	77.29	1.49
<b>p0_score:</b>	33.50															
<b>p1_score:</b>	33.00															
<b>p2_score:</b>	32.31															
<b>Infrastructure_Operations_Scores:</b>										vmotion			svmotion			deploy
<b>Completed_Ops_PerHour</b>										17.50			11.00			5.50

<b>Avg_Seconds_To_Complete</b>	24.71	18.99	247.85
<b>Failures</b>	0.00	0.00	0.00
<b>Ratio</b>	1.09	1.22	1.38
<b>Number_Of_Threads</b>	1	1	1
<b>Summary</b>	Run_Is_Compliant		Turbo_Setting:0
	Number_Of_Compliance_Issues(0)*		Median_Phase(p1)
<b>Unreviewed_VMmark2_Applications_Score</b>	33.00		
<b>Unreviewed_VMmark2_Infrastructure_Score</b>	1.22		
<b>Unreviewed_VMmark2_Score</b>	26.64		

## Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESXi 6.0.0 Build 2494585/03-12-2015
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 6.0.0 Build 2559268/ 3-12-2015
Supplemental Software	none
Servers	
Quantity	2
Server Manufacturer and Model	Huawei FusionServer CH121 V3
Processor Vendor and Model	Intel Xeon E5-2699 V3
Processor Speed (GHz)	2.3
Total Sockets/Total Cores/Total Threads	2 Sockets /36 Cores / 72 Threads
Primary Cache	32KB I + 32KB D on chip per core
Secondary Cache	256KB I+D on chip per core
Other Cache	45MB I+D on chip per chip L3
BIOS Version	Z.13
Memory Size (in GB, Number of DIMMs)	384,24
Memory Type and Speed	16GB-Dimms 2Rx4 PC4-2133P ECC
Disk Subsystem Type	FC SAN
Number of Disk Controllers	11
Disk Controller Vendors and Models	1 x LSI SAS2308 10 x AHCI controllers (not being used)

Number of Host Bus Adapters	2
Host Bus Adapter Vendors and Models	Emulex LPe16000 with Dual Port 16Gb Fibre Channel HBA
Number of Network Controllers	2
Network Controller Vendors and Models	Emulex OneConnect OCe15100 with Dual Port
Other Hardware	2 disks RAID0 for OS
Other Software	none
Hardware Availability Date (MM-DD-YYYY)	06-02-2015
Software Availability Date (MM-DD-YYYY)	06-02-2015
<b>Network</b>	
Network Switch Vendors and Models	HUAWEI E9000 CX911
Network Speed	10Gbps
<b>Storage</b>	
Array Vendors, Models, and Firmware Versions	2 x RH2288H V2 Server with Fusion-io ioDrive2 Duo 2.4TB PCIe SSD, 1 x HUAWEI OceanStor Dorado 2100 (FW version V1R1C00)
Fibre Channel Switch Vendors and Models	HUAWEI E9000 CX911
Disk Space Used	16800GB
Array Cache Size	HUAWEI OceanStor Dorado 2100:16GB
Total Number of Physical Disks Used	6xPCIe-SSD, 24 SSDS
Total Number of Enclosures/Pods/Shelves Used	3
Number of Physical Disks Used per Enclosure/Pod/Shelf	Enclosure: details in section Storage Notes
Total Number of Storage Groups Used	0
Number of LUNs Used	16
LUN Size and Number of Disks Per LUN	Details in section Storage Notes
RAID Type	0
Number of Members per RAID Set	Details in section Storage Notes
Disk Vendors, Models, and Speeds	24xHuawei Dorado 2100-HSSD-D3220AS0100; 6x Fusion-io ioDrive2 Duo 2.4TB PCIe SSD
<b>Datacenter Management Server</b>	
System Model	A Virtual Server on Huawei Tecal RH2288A V2
Processor Vendor and Model	Intel Xeon E5-2670 v2
Processor Speed (GHz)	2.5Ghz
Total Sockets/Total Cores/Total Threads	Hypervisor: 2 Sockets / 20 Cores / 40 Threads Virtual Center VM: 1 Sockets / 4 Cores / 4 Threads

Memory	Hypervisor: 128GB Virtual Center VM: 16GB
Network Controller(s) Vendors and Models	1 x Intel 10Gb 2-port 82599 Adapter
Operating System, Version, Bitness, and Service Pack	Hypervisor: VMware ESXi 5.5.0 Build 1331820 Virtual Center VM: Microsoft Windows 2008 R2 Enterprise SP1 (64bit)
Other Hardware	none
Other Software	none
<b>Clients</b>	
Total Number of Clients / Total Physical Clients / Total Virtual Client Hosts	22/1/3
System Model(s)	1xHuawei Tecal RH2288V2 (Prime Client) 1xHuawei Tecal RH2288AV2(Virtual Client Host for client 1,2,3,4,5,6) 1xHuawei Tecal RH2288HV2(Virtual Client Host for client 7,8,9,10,11,12,13) 1xHuawei Tecal RH2285V3(Virtual Client Host for client 14,15,16,17,18,19,20,21)
Processor Vendor(s) and Model(s)	1xPrime Client: Intel Xeon E5-2450 v2 1xVirtual Client Host: Intel Xeon E5-2670 v2 1xVirtual Client Host: Intel Xeon E5-2695 v2 1xVirtual Client Host: Intel Xeon E5-2670 v3
Processor Speed(s) (GHz)	1xPrime Client: 2.5GHz 1xVirtual Client Host: 2.5GHz 1xVirtual Client Host: 2.4GHz 1xVirtual Client Host: 2.3GHz
Total Sockets/Total Cores/Total Threads	1xPrime Client: 2 Socket / 16 Cores / 32 Threads 1xVirtual Client Host: 2 Socket / 20 Cores / 40Threads 1xVirtual Client Host: 2 Socket / 24 Cores / 48Threads 1xVirtual Client Host: 2 Socket / 24 Cores / 48Threads
Memory per Physical Client	1xPrime Client: 16GB 1xVirtual Client Host: 128GB 1xVirtual Client Host: 128GB 1xVirtual Client Host: 128GB
Network Controller(s) Vendors and Models	Prime Client: 1 x Intel 1Gb 2-port 82580 Adapter, 1 x Intel 10Gb 2-port 82599 Adapter Virtual Client Host: 1 x Intel 10Gb 2-port 82599 Adapter
Operating System, Version, Bitness, and Service Pack	Clients: Microsoft Windows 2008 R2 Enterprise SP1 (64bit) Virtual Client Host: VMware ESXi 5.5.0 (Build 1331820)
Number of Virtual Clients	21
Number of vCPUs Per Virtual Client	4
Number of vMem (GB) Per Virtual Client	12GB
Virtual Client Networking Notes	All client VMs attached to port 1 of Intel 82599 card running at speed of 10Gb/s

Virtual Client Storage Notes	All clients stored on local media respective to their ESXi host. 4x300GB ST300MM0006 6G 10K rpm SFF SAS disk per Physical Client with RAID 10
Other Hardware	none
Other Software	none

## Notes for Workload

### Virtualization Software Notes

All multiprocessor VMs are using the CPU-scheme single socket with multiple cores (default one core per multiple virtual sockets)

Logging was disabled for all VMs except Deploy template VM (default Enabled)

SCSI adapter type PVSCSI used for all VMs (default LSI Logic SAS)

Ethernet adapter type set to VMXNET 3 for all VMs (default E1000)

Floppy removed for all VMs (default enabled)

CDROM removed for all VMs except deploy template (default enabled)

Cluster DRS Automation Level set to Fully Automated level 2

Hardware version 10 used for all VMs (default 8)

VMware Tools build 9536 used for all VMs (default 9536)

All DS2DBVMs had CPU shares set to 7500 (default Normal)

All DS2DBVMs had Disk shares set to high (default Normal)

All StandbyVMs had CPU shares set to low (default Normal)

All VMs except deploy template, sched.mem.min and sched.mem.minsize were set to the VM's memory size (default 0)

sched.mem.pin = TRUE set for all VMs except Deploy template VM (locks all Guest memory into physical memory, default FALSE)

Multiqueue is disabled in the vmxnet3 driver on all linux VMs

The vmxnet3 driver version is 1.2.39.0 for all linux VMs

Firewall is disabled (default enabled)

### Advanced Setting

esxcfg-advcfg -s 1000 /Cpu/CreditAgePeriod (default 3000)

esxcfg-advcfg -s 0 /Cpu/HTWholeCoreThreshold (default 200)

esxcfg-advcfg -s 0 /DataMover/HardwareAcceleratedInit (default 1)

esxcfg-advcfg -s 0 /DataMover/HardwareAcceleratedMove (default 1)

esxcfg-advcfg -s 0 /Mem/CtlMaxpercent (default 65)

esxcfg-advcfg -s 0 /Mem/ShareScanGHz (default 4)

esxcfg-advcfg -s 500 /Net/MaxNetifRxQueueLen (default 100)

esxcfg-advcfg -s 1000 /Net/MaxNetifTxQueueLen (default 500)

esxcfg-advcfg -s 0 /Numa/LTermFairnessInterval (default 5)

esxcfg-advcfg -s 57 /Numa/MigImbalanceThreshold (default 10)

esxcfg-advcfg -s 0 /Numa/MonMigEnable (default 1)

esxcfg-advcfg -s 0 /Numa/PageMigEnable (default 1)

esxcfg-advcfg -s 60000 /Numa/RebalancePeriod (default 2000)

esxcfg-advcfg -s 0 /Numa/SwapLoadEnable (default 1)

esxcfg-advcfg -s 0 /Numa/SwapLocalityEnable (default 1)

esxcfg-advcfg -s static /Power/CpuPolicy (default balanced)

esxcfg-advcfg -s 0 /VMFS3/HardwareAcceleratedLocking (default 1)

esxcfg-advcfg -s 0 /Cpu/CoschedCrossCall (default 1)

esxcfg-advcfg -s 1 /Irq/BestVcpuRouting (default 0)

esxcfg-advcfg -s 1 /Numa/SwapInterval (default 3)

esxcfg-advcfg -s 1 /Numa/PreferHT (default 0)

esxcfg-advcfg -s 20000 /Irq/IRQRebalancePeriod (default 50)

esxcfg-advcfg -s 4000 /Misc/TimerMaxHardPeriod (default 100000)

esxcfg-advcfg -s 0 /Numa/LargeInterleave (default 1)

esxcfg-advcfg -s 1 /Disk/ReqCallThreshold (default 8)

Driver options:

/usr/sbin/esxcfg-module -s "ql2xmaxqdepth=256" qlnativefc (default 64)

/usr/sbin/esxcfg-module -s "lpfc\_lun\_queue\_depth=128 lpfc\_cr\_count=1 lpfc\_cr\_delay=0" lpfc (default lpfc\_lun\_queue\_depth=32 lpfc\_cr\_count=2 lpfc\_cr\_delay=1)

## Server Notes

Server BIOS settings:

Turbo Boost Technology: Enabled (Intel Turbo Boost up to 3.6GHz , default enabled)

Hardware Prefetcher : Disabled (default enable)

Adjacent Prefetcher : Disabled (default enable)

All C-States: disabled (default enable)

Cluster on die Enabled (default Early snoop mode)

## Networking Notes

vSwitch0 for the service Console at 10Gb/s on vmnic0

vSwitch1 for DS2-VMs workloads at 10Gb/s on vmnic1

vSwitch2 for all VMs except DS2-VMs at 10Gb/s on vmnic2

vSwitch3 for vMotion at 10Gb/s on vmnic3

## Storage Notes

ESXi was install on two disk configured as RAID1 in the internal server storage bay

Round robin policy was used for all storage except for host OS (default most recently used)

All LUNs were configured as block devices; no system memory was used for caching

SanDisk support for RH2288H V2 server using SanDisk ION Accelerator version 2.50 build 276 software is expected by 8/30/2015

## 1x HUAWEI OceanStor Dorado 2100 (24x100GB SATA-SSDs)

RAID configuration:

LUN 1: For All Standby VMs (6x100GB SATA-SSDs for RAID 0)

LUN 2: Source LUN for Deploy (6x100GB SATA-SSDs for RAID 0)

LUN 3: Target LUN for Deploy (6x100GB SATA-SSDs for RAID 0)

LUN 4: Target LUN for Storage VMtion (6x100GB SATA-SSDs for RAID 0)

## 1xRH2288H V2 configured as a Fibre Channel Target

Hardware details:

Two Intel Xeon E5-2690v2@3.0GHz processors

128GB RAM(8x16 GB dual rank PC3-14900 Registered DDR3/1866 MHz DIMMs)

Two Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

3xFusion-io ioDrive2 Duo 2.4TB PCIE-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details: SanDisk ION Accelerator version 2.50 build 276

RAID configuration: No RAID level used on PCIE-SSD

First PCIE-SSD:

LUN 1: For Tile 0,12 VMs except standby VMs (1200GB)

LUN 2: For Tile 1,13 VMs except standby VMs (1200GB)

Second PCIE-SSD:

LUN 1: For Tile 4,16 VMs except standby VMs (1200GB)

LUN 2: For Tile 5,17 VMs except standby VMs (1200GB)

Third PCIE-SSD:



LUN 1: For Tile 8,20 VMs except standby VMs (1200GB)

LUN 2: For Tile 9,21 VMs except standby VMs (1200GB)

### **1xRH2288H V2 configured as a Fibre Channel Target**

Hardware details:

Two Intel Xeon E5-2690v2@3.0GHz processors

128GB RAM(8x16 GB dual rank PC3-14900 Registered DDR3/1866 MHz DIMMs)

Two Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

3xFusion-io ioDrive2 Duo 2.4TB PCIe-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details: SanDisk ION Accelerator version 2.50 build 276

RAID configuration: No RAID level used on PCIe-SSD

First PCIe-SSD:

LUN 1: For Tile 2,14 VMs except standby VMs (1200GB)

LUN 2: For Tile 3,15 VMs except standby VMs (1200GB)

Second PCIe-SSD:

LUN 1: For Tile 6,18 VMs except standby VMs (1200GB)

LUN 2: For Tile 7,19,11 VMs except standby VMs (1200GB)

Third PCIe-SSD:

LUN 1: For Tile 10 VMs except standby VMs (1200GB)

LUN 2: For Tile 11 VMs except standby VMs (1200GB)

### **SUT storage notes**

2x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 1 used for hosts' OS.

### **Client storage notes**

1xPrime Client: 1x500GB Seagate ST9500620NS 6G 7200 rpm SFF SATA disk with no RAID used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

### **Datacenter Management Server Notes**

None

### **Operating System Notes**

All Mailserver VMs running Microsoft Windows Server 2008 R2 Enterprise SP1(64-bit)

All Standby VMs running Microsoft Windows Server 2003 R2 Enterprise SP2(32-bit)

All SLES11 VMs were updated with SP2

### **Software Notes**

Each Mailserver VM running Microsoft Exchange Server 2007 Enterprise SP3 (64-bit)

### **Client Notes**

Prime client was running VMware vSphere PowerCLI 5.8 Build 2057893

All virtual client hosts were installed with VMware ESXi 5.5.0 (Build 1331820)

### **Other Notes**

TILEDELAY reduced to 33 seconds (default: 60 seconds)

---

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit [www.vmware.com/products/vmmark](http://www.vmware.com/products/vmmark).

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of [VMware, Inc.](#) VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.