

VMware® VMmark® V2.5.2 Results

Vendor and Hardware Platform: Huawei FusionServer RH5885H V3
 Virtualization Platform: VMware ESXi 6.0.0 U1a Build 3073146
 VMware vCenter Server : VMware vCenter Server 6.0.0 U1 Build 3018524

**VMmark V2.5.2 Score =
47.16 @ 40 Tiles**

Number of Hosts: 2

Uniform Hosts [yes/no]: yes

Total sockets/cores/threads in test: 8/144/288

Tested By: Huawei Technologies Co.,Ltd.

Test Date: 1-26-2016

Performance Section
[Performance](#)

Configuration Section
[Configuration](#)

Notes Section
[Notes for Workload](#)

Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.62	0.99	74.00	4742.02	1.02	103.86	3987.07	1.81	65.71	2912.57	1.92	69.68	2093.85	1.98	72.56	1.47
p1	326.50	0.99	74.00	4714.85	1.02	123.62	3913.12	1.78	68.87	3064.53	2.02	71.64	2240.75	2.12	75.90	1.50
p2	326.45	0.99	76.50	4648.25	1.00	198.04	3705.65	1.69	77.58	2704.97	1.78	81.48	2099.55	1.98	79.36	1.43
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.48	0.99	64.08	4735.88	1.02	122.61	4090.90	1.86	63.28	2927.95	1.93	69.73	2154.20	2.04	68.23	1.49
p1	325.20	0.98	76.40	4689.65	1.01	164.20	3846.80	1.75	73.10	2835.07	1.87	80.02	2261.07	2.14	74.33	1.47
p2	327.55	0.99	92.50	4552.05	0.98	314.69	3789.65	1.72	75.49	2786.00	1.83	82.92	2112.82	2.00	78.50	1.44
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	322.62	0.98	64.75	4714.75	1.02	104.01	4028.45	1.83	64.98	3015.97	1.99	69.54	2232.78	2.11	70.24	1.50
p1	323.05	0.98	77.00	4705.50	1.01	111.50	3812.43	1.73	73.60	2838.82	1.87	79.41	2191.72	2.07	79.80	1.46
p2	324.98	0.98	84.00	4646.05	1.00	172.30	3779.03	1.72	74.60	2666.65	1.76	84.37	1963.58	1.86	83.78	1.41
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.23	0.99	68.33	4696.75	1.01	110.82	4075.12	1.85	64.19	3031.10	2.00	70.09	2133.40	2.02	77.38	1.50
p1	329.75	1.00	80.25	4667.60	1.01	157.07	3849.53	1.75	73.57	2736.00	1.80	81.03	1995.28	1.89	88.49	1.43
p2	327.30	0.99	95.25	4580.82	0.99	283.02	3792.62	1.72	75.92	2785.05	1.83	83.88	1965.90	1.86	91.22	1.42
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.57	1.00	84.00	4727.95	1.02	114.19	4039.20	1.84	63.94	3203.62	2.11	65.57	2279.32	2.15	73.27	1.53
p1	325.55	0.99	84.00	4678.80	1.01	172.43	3930.28	1.79	68.19	2831.18	1.86	74.70	2050.55	1.94	83.77	1.45
p2	327.50	0.99	86.75	4512.00	0.97	348.88	3757.22	1.71	75.16	2842.78	1.87	74.06	1912.90	1.81	87.84	1.41
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.95	0.99	74.00	4697.82	1.01	121.94	3999.50	1.82	65.48	3055.00	2.01	68.05	2306.75	2.18	72.17	1.52

p1	325.75	0.99	79.25	4664.85	1.01	187.43	3790.03	1.72	73.65	2852.20	1.88	73.84	1977.25	1.87	83.36	1.43
p2	325.73	0.99	88.00	4563.35	0.98	343.10	3702.95	1.68	77.52	2781.12	1.83	83.45	2022.40	1.91	86.88	1.42
TILE_6	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.27	0.99	65.95	4756.93	1.02	106.33	3980.28	1.81	66.42	3035.62	2.00	68.64	2352.43	2.22	68.53	1.52
p1	331.30	1.00	78.25	4684.07	1.01	157.60	3818.05	1.74	72.87	2912.00	1.92	69.97	2165.38	2.05	68.00	1.47
p2	329.45	1.00	93.00	4682.25	1.01	172.74	3656.75	1.66	79.91	2827.43	1.86	79.83	2119.35	2.00	79.14	1.44
TILE_7	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.12	0.99	81.88	4729.98	1.02	107.53	3931.85	1.79	67.85	2943.55	1.94	67.90	2176.57	2.06	73.98	1.48
p1	324.25	0.98	86.85	4671.50	1.01	178.12	3771.47	1.71	74.12	2838.43	1.87	73.68	2018.90	1.91	78.89	1.43
p2	327.57	0.99	94.00	4560.57	0.98	327.43	3593.93	1.63	82.11	2904.22	1.91	80.61	2139.88	2.02	83.65	1.44
TILE_8	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	331.10	1.00	74.00	4731.30	1.02	115.95	3947.70	1.80	67.47	2926.10	1.93	68.95	2241.47	2.12	68.87	1.50
p1	324.68	0.98	74.00	4706.85	1.01	123.09	3794.47	1.73	73.45	2834.43	1.87	74.16	2104.15	1.99	72.26	1.45
p2	325.38	0.99	75.25	4621.85	1.00	232.27	3707.30	1.69	77.37	2842.55	1.87	78.98	2205.80	2.08	78.42	1.45
TILE_9	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.45	0.98	63.90	4737.18	1.02	115.35	4068.28	1.85	62.70	3002.80	1.98	65.18	2145.90	2.03	68.78	1.49
p1	325.12	0.98	78.78	4671.27	1.01	175.80	3860.95	1.76	70.93	2949.22	1.94	72.74	2171.97	2.05	73.93	1.47
p2	327.73	0.99	92.00	4600.12	0.99	276.44	3779.78	1.72	74.38	2881.95	1.90	76.77	2189.30	2.07	79.69	1.46
TILE_10	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.35	0.99	67.50	4742.45	1.02	110.16	4025.97	1.83	65.32	2906.50	1.91	70.03	2048.35	1.94	76.57	1.47
p1	328.68	1.00	83.50	4739.00	1.02	113.73	4029.38	1.83	65.16	2900.12	1.91	75.76	2159.38	2.04	75.26	1.49
p2	323.68	0.98	98.75	4660.62	1.00	194.08	3738.35	1.70	77.35	2753.30	1.81	78.88	2010.65	1.90	87.43	1.42
TILE_11	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	332.30	1.01	84.00	4732.95	1.02	101.87	3924.03	1.78	68.23	2924.07	1.93	69.24	2105.60	1.99	71.67	1.48
p1	328.40	0.99	84.00	4711.73	1.02	132.51	3833.50	1.74	71.85	3007.05	1.98	74.86	2208.97	2.09	78.03	1.49
p2	326.30	0.99	92.05	4683.30	1.01	171.09	3679.45	1.67	78.26	2740.95	1.80	79.69	2043.22	1.93	83.87	1.42
TILE_12	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.32	0.98	84.00	4733.90	1.02	119.20	4003.25	1.82	65.61	2963.20	1.95	67.14	2118.95	2.00	70.98	1.48
p1	329.60	1.00	84.00	4677.98	1.01	163.15	3752.18	1.71	75.90	2999.97	1.98	70.56	2274.40	2.15	73.56	1.49
p2	324.18	0.98	88.25	4664.90	1.01	194.17	3661.97	1.67	79.68	2816.68	1.85	75.38	2002.15	1.89	80.23	1.42
TILE_13	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.77	0.99	67.40	4731.68	1.02	109.26	4039.57	1.84	64.69	3030.00	2.00	69.03	2217.53	2.10	70.85	1.51
p1	328.85	1.00	81.75	4711.73	1.02	137.50	3856.43	1.75	72.29	2852.90	1.88	78.80	2231.45	2.11	76.98	1.48
p2	328.93	1.00	100.00	4603.32	0.99	277.98	3775.10	1.72	75.34	2709.85	1.78	81.91	1920.05	1.81	87.11	1.41
TILE_14	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

p0	324.38	0.98	74.00	4731.55	1.02	101.18	4022.72	1.83	65.48	3050.68	2.01	67.88	2222.80	2.10	70.25	1.51
p1	327.07	0.99	74.00	4723.80	1.02	118.92	3774.85	1.72	75.10	2864.65	1.89	72.43	2166.62	2.05	74.67	1.46
p2	325.73	0.99	78.75	4654.85	1.00	189.69	3705.68	1.69	78.08	2776.47	1.83	77.71	2009.95	1.90	79.44	1.42
TILE_15	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.05	0.99	84.75	4722.62	1.02	103.69	3995.90	1.82	66.42	3083.40	2.03	70.94	2243.72	2.12	76.18	1.51
p1	329.25	1.00	85.50	4689.30	1.01	138.92	3810.50	1.73	74.31	2855.70	1.88	72.93	2028.85	1.92	85.70	1.44
p2	325.82	0.99	94.25	4573.20	0.99	287.63	3704.20	1.68	78.98	2721.88	1.79	80.58	1889.12	1.79	90.81	1.39
TILE_16	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.32	1.00	74.00	4723.15	1.02	107.06	4016.10	1.83	64.99	3010.35	1.98	69.81	2348.50	2.22	68.40	1.52
p1	328.27	0.99	74.00	4698.52	1.01	160.07	3850.95	1.75	71.70	2892.25	1.90	71.01	2057.43	1.94	75.02	1.46
p2	324.95	0.98	77.25	4656.55	1.00	188.56	3774.88	1.72	74.67	2794.75	1.84	82.34	2093.25	1.98	78.53	1.44
TILE_17	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.62	0.98	72.00	4731.80	1.02	116.21	3944.82	1.79	67.41	3020.75	1.99	69.69	2309.40	2.18	71.17	1.51
p1	328.52	0.99	83.00	4711.05	1.01	132.65	3831.38	1.74	72.02	2884.43	1.90	72.06	2030.17	1.92	77.98	1.45
p2	325.38	0.99	97.25	4659.30	1.00	176.37	3609.15	1.64	81.59	2869.10	1.89	77.94	2073.75	1.96	81.82	1.43
TILE_18	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.35	0.99	67.00	4725.45	1.02	109.12	4021.47	1.83	65.34	2905.45	1.91	70.57	2240.65	2.12	69.15	1.49
p1	324.70	0.98	81.75	4700.15	1.01	150.49	3977.05	1.81	66.88	2881.25	1.90	71.86	2054.40	1.94	76.23	1.46
p2	322.73	0.98	100.75	4597.77	0.99	267.16	3726.93	1.69	77.40	2873.82	1.89	82.93	2146.50	2.03	83.08	1.44
TILE_19	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.30	0.99	81.90	4737.98	1.02	104.99	3939.20	1.79	67.55	3045.62	2.01	68.40	2164.90	2.05	74.92	1.49
p1	318.65	0.96	84.00	4696.68	1.01	142.55	3777.97	1.72	74.05	2870.28	1.89	72.67	2005.03	1.90	79.70	1.43
p2	327.02	0.99	89.50	4643.00	1.00	188.74	3595.32	1.63	82.38	2870.25	1.89	77.98	2132.55	2.02	84.33	1.44
TILE_20	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.75	0.99	68.25	4746.07	1.02	98.26	4031.22	1.83	64.29	2997.97	1.97	65.48	2072.55	1.96	74.73	1.48
p1	325.02	0.98	83.25	4719.43	1.02	119.03	3845.65	1.75	71.76	3028.05	1.99	69.13	2148.43	2.03	75.94	1.48
p2	327.60	0.99	102.75	4667.68	1.01	178.12	3768.45	1.71	74.87	2848.10	1.88	78.84	2084.47	1.97	88.24	1.45
TILE_21	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.12	0.99	84.00	4743.10	1.02	99.33	3978.35	1.81	66.23	2912.35	1.92	69.77	2209.32	2.09	71.72	1.49
p1	331.40	1.00	85.75	4694.18	1.01	132.28	3888.35	1.77	69.74	2904.75	1.91	75.89	2121.88	2.01	77.97	1.47
p2	323.20	0.98	94.00	4673.38	1.01	161.37	3728.25	1.70	76.60	2664.30	1.75	84.49	2065.53	1.95	82.43	1.42
TILE_22	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.27	0.98	84.00	4727.65	1.02	115.07	3999.35	1.82	65.64	2967.78	1.95	67.12	2087.97	1.97	73.02	1.48
p1	327.35	0.99	84.00	4681.23	1.01	160.50	3747.10	1.70	75.78	3084.30	2.03	70.89	2250.28	2.13	75.40	1.49
p2	325.15	0.98	87.00	4540.82	0.98	345.30	3666.07	1.67	79.20	2779.25	1.83	77.07	2060.47	1.95	82.98	1.42

TILE_23	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.40	0.98	74.00	4731.50	1.02	108.08	4027.28	1.83	64.64	3024.85	1.99	69.08	2134.65	2.02	69.70	1.49
p1	325.05	0.98	85.50	4721.93	1.02	128.42	3902.60	1.77	69.59	2847.25	1.87	79.38	2235.57	2.11	76.52	1.48
p2	327.77	0.99	98.75	4659.45	1.00	184.11	3693.15	1.68	78.41	2696.90	1.78	82.40	1948.47	1.84	84.94	1.40
TILE_24	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.48	0.99	85.50	4737.48	1.02	103.60	4075.75	1.85	62.80	3020.68	1.99	69.44	2203.22	2.08	71.96	1.51
p1	327.02	0.99	84.00	4718.68	1.02	121.10	3997.35	1.82	65.59	2866.10	1.89	77.88	2200.20	2.08	79.31	1.48
p2	324.57	0.98	87.75	4627.07	1.00	217.66	3788.65	1.72	74.01	2670.15	1.76	84.32	1983.67	1.87	81.36	1.41
TILE_25	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.25	0.98	72.50	4735.45	1.02	104.16	3929.60	1.79	68.15	2998.85	1.97	71.05	2215.93	2.09	71.12	1.49
p1	328.50	0.99	81.50	4720.90	1.02	138.33	3854.85	1.75	71.24	2798.20	1.84	77.04	2155.05	2.04	75.13	1.46
p2	325.90	0.99	92.28	4667.12	1.01	179.35	3697.60	1.68	77.78	2754.18	1.81	85.41	1986.05	1.88	81.54	1.42
TILE_26	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.45	0.99	87.20	4724.98	1.02	104.91	4061.43	1.85	63.26	3199.95	2.11	65.64	2311.20	2.18	71.28	1.54
p1	327.68	0.99	83.83	4687.77	1.01	148.41	3896.47	1.77	69.77	3014.43	1.99	64.88	2104.35	1.99	79.02	1.48
p2	325.70	0.99	84.50	4646.98	1.00	180.09	3832.28	1.74	72.27	2811.50	1.85	76.30	1920.47	1.82	87.48	1.42
TILE_27	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	320.80	0.97	73.53	4727.73	1.02	107.76	4061.00	1.85	63.56	3032.50	2.00	68.81	2335.68	2.21	69.97	1.52
p1	326.88	0.99	83.00	4703.32	1.01	138.42	3963.43	1.80	67.57	2856.25	1.88	72.90	2090.80	1.98	73.42	1.46
p2	328.70	1.00	95.25	4564.20	0.98	306.70	3818.55	1.74	73.53	2857.93	1.88	78.24	2100.70	1.99	79.86	1.45
TILE_28	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.10	0.98	72.10	4732.98	1.02	96.30	3978.18	1.81	66.44	2959.47	1.95	68.15	2221.50	2.10	70.51	1.49
p1	323.15	0.98	79.88	4721.30	1.02	119.93	3780.35	1.72	74.32	2910.75	1.92	75.92	2167.55	2.05	74.63	1.46
p2	325.45	0.99	94.00	4680.80	1.01	185.35	3732.85	1.70	76.20	2819.38	1.86	80.97	2065.18	1.95	82.25	1.44
TILE_29	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.02	0.99	113.75	4727.75	1.02	107.00	4044.18	1.84	64.45	2921.95	1.92	70.04	2222.15	2.10	70.66	1.50
p1	327.70	0.99	96.25	4712.88	1.02	126.07	3903.90	1.78	70.05	2828.62	1.86	74.79	2096.28	1.98	72.78	1.46
p2	323.02	0.98	96.00	4680.75	1.01	170.66	3789.07	1.72	74.56	2944.95	1.94	78.62	2177.82	2.06	80.56	1.47
TILE_30	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.60	0.99	73.75	4742.90	1.02	108.56	3944.78	1.79	67.68	3056.03	2.01	67.99	2194.68	2.07	72.67	1.50
p1	329.20	1.00	79.50	4695.48	1.01	148.39	3772.68	1.72	74.25	2854.25	1.88	72.91	2082.75	1.97	73.52	1.45
p2	325.05	0.98	94.00	4575.00	0.99	284.24	3610.22	1.64	81.84	2814.97	1.85	80.53	2133.35	2.02	84.24	1.43
TILE_31	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.15	0.99	87.40	4722.07	1.02	108.33	4119.00	1.87	62.00	3052.03	2.01	63.91	2135.05	2.02	69.70	1.50
p1	327.38	0.99	86.12	4713.05	1.02	140.80	4013.82	1.83	65.82	3086.88	2.03	66.83	2177.18	2.06	74.00	1.50

p2_score:	57.12		
Infrastructure_Operations_Scores:		vmotion	svmotion
Completed_Ops_PerHour		17.00	11.00
Avg_Seconds_To_Complete		29.01	19.20
Failures		0.00	0.00
Ratio		1.06	1.22
Number_Of_Threads		1	1
Summary	Run_Is_Compliant	Turbo_Setting:0	
	Number_Of_Compliance_Issues(0)*	Median_Phase(p1)	
Unreviewed_VMmark2_Applications_Score	58.66		
Unreviewed_VMmark2_Infrastructure_Score	1.18		
Unreviewed_VMmark2_Score	47.16		

Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESXi 6.0.0 U1a Build 3073146/10-6-2015
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 6.0.0 U1 Build 3018524/ 9-10-2015
Supplemental Software	none
Servers	
Quantity	2
Server Manufacturer and Model	Huawei FusionServer RH5885H V3
Processor Vendor and Model	Intel Xeon E7-8890 V3
Processor Speed (GHz)	2.5
Total Sockets/Total Cores/Total Threads	4 Sockets /72 Cores / 144 Threads
Primary Cache	32KB I + 32KB D on chip per core
Secondary Cache	256KB I+D on chip per core
Other Cache	45MB I+D on chip per chip L3
BIOS Version	BLISV705
Memory Size (in GB, Number of DIMMs)	1024,32

Memory Type and Speed	32GB-DIMMs 2Rx4 PC4-2133P ECC
Disk Subsystem Type	FC SAN
Number of Disk Controllers	1
Disk Controller Vendors and Models	1 x LSI SAS2308
Number of Host Bus Adapters	3
Host Bus Adapter Vendors and Models	Qlogic ISP2532-based with Dual port 8Gb Fibre Channel x3
Number of Network Controllers	3
Network Controller Vendors and Models	1 x Intel 1Gb 2-port I350 Adapter, 2 x Intel 10Gb 2-port 82599 Adapter
Other Hardware	2 disks RAID1 for OS
Other Software	none
Hardware Availability Date (MM-DD-YYYY)	06-9-2015
Software Availability Date (MM-DD-YYYY)	10-6-2015
Network	
Network Switch Vendors and Models	HUAWEI E9000 CX911
Network Speed	10Gbps
Storage	
Array Vendors, Models, and Firmware Versions	2 x RH2288V2, Firmware version V9.31 2 x RH2288HV3, Firmware version V389
Fibre Channel Switch Vendors and Models	HUAWEI E9000 CX911
Disk Space Used	28.14TB
Array Cache Size	none
Total Number of Physical Disks Used	6 x Fusion-io ioDrive2 Duo 2.4TB PCIe SSD, 4 x HUAWEI ES3000 V2 3.2TB PCIe SSD, 2 x SAMSUNG-2.5-480GB-SATA-SSD
Total Number of Enclosures/Pods/Shelves Used	4
Number of Physical Disks Used per Enclosure/Pod/Shelf	Enclosure: details in section Storage Notes
Total Number of Storage Groups Used	0
Number of LUNs Used	20
LUN Size and Number of Disks Per LUN	Details in section Storage Notes
RAID Type	0
Number of Members per RAID Set	Details in section Storage Notes
Disk Vendors, Models, and Speeds	Details in section Storage Notes
Datacenter Management Server	

System Model	A Virtual Server on Huawei Tecal RH2288A V2
Processor Vendor and Model	Intel Xeon E5-2695 v2
Processor Speed (GHz)	2.4Ghz
Total Sockets/Total Cores/Total Threads	Hypervisor: 2 Sockets / 24 Cores / 48 Threads Virtual Center VM: 1 Sockets / 8 Cores / 8 Threads
Memory	Hypervisor: 128GB Virtual Center VM: 12GB
Network Controller(s) Vendors and Models	1 x Intel 10Gb 2-port 82599 Adapter
Operating System, Version, Bitness, and Service Pack	Hypervisor: VMware ESXi 5.5.0 Build 1331820 Virtual Center VM: Microsoft Windows 2008 R2 Standard SP1 (64bit)
Other Hardware	none
Other Software	none

Clients

Total Number of Clients / Total Physical Clients / Total Virtual Client Hosts	40/1/5
System Model(s)	1xHuawei Tecal RH2288V2 (Prime Client) 1x1xHuawei FusionServer RH2288HV3(Virtual Client Host for client 30,31,32,33,34,35,36,37,38,39) 1x1xHuawei FusionServer RH2288HV3 (Virtual Client Host for client 20,21,22,23,24,25,26,27,28,29) 1xHuawei Tecal RH2288AV2(Virtual Client Host for client 1,2,3,4,5,28) 1xHuawei Tecal RH2288HV2(Virtual Client Host for client 6,7,8,9,10,11) 1xHuawei Tecal RH2285V3(Virtual Client Host for client 12,13,14,15,16,17,18,19)
Processor Vendor(s) and Model(s)	1xPrime Client: Intel Xeon E5-2450 v2 1xVirtual Client Host: Intel Xeon E5-2699 v3 1xVirtual Client Host: Intel Xeon E5-2699 v3 1xVirtual Client Host: Intel Xeon E5-2670 v2 1xVirtual Client Host: Intel Xeon E5-2695 v2 1xVirtual Client Host: Intel Xeon E5-2670 v3
Processor Speed(s) (GHz)	1xPrime Client: 2.5GHz 1xVirtual Client Host: 2.3GHz 1xVirtual Client Host: 2.3GHz 1xVirtual Client Host: 2.5GHz 1xVirtual Client Host: 2.4GHz 1xVirtual Client Host: 2.3GHz
Total Sockets/Total Cores/Total Threads	1xPrime Client: 2 Socket / 16 Cores / 32 Threads 1xVirtual Client Host: 2 Socket / 36 Cores / 72Threads 1xVirtual Client Host: 2 Socket / 36 Cores / 72Threads 1xVirtual Client Host: 2 Socket / 20 Cores / 40Threads 1xVirtual Client Host: 2 Socket / 24 Cores / 48Threads 1xVirtual Client Host: 2 Socket / 24 Cores / 48Threads

Memory per Physical Client	1xPrime Client: 96GB 1xVirtual Client Host: 224GB 1xVirtual Client Host: 192GB 1xVirtual Client Host: 128GB 1xVirtual Client Host: 128GB 1xVirtual Client Host: 128GB
Network Controller(s) Vendors and Models	Prime Client: 1 x Intel 1Gb 2-port 82580 Adapter, 1 x Intel 10Gb 2-port 82599 Adapter Virtual Client Host: 1 x Intel 10Gb 2-port 82599 Adapter
Operating System, Version, Bitness, and Service Pack	Clients: Microsoft Windows 2008 R2 Enterprise SP1 (64bit) Virtual Client Host: VMware ESXi 5.5.0 (Build 1331820)
Number of Virtual Clients	39
Number of vCPUs Per Virtual Client	4
Number of vMem (GB) Per Virtual Client	12GB
Virtual Client Networking Notes	All client VMs attached to port 1 of Intel 82599 card running at speed of 10Gb/s
Virtual Client Storage Notes	All clients stored on local media respective to their ESXi host. 4x300GB ST300MM0006 6G 10K rpm SFF SAS disk per Physical Client with RAID 10
Other Hardware	none
Other Software	none

Notes for Workload

Virtualization Software Notes

All multiprocessor VMs are using the CPU-scheme single socket with multiple cores (default one core per multiple virtual sockets)

Logging was disabled for all VMs (default Enabled)

SCSI adapter type PVSCSI used for all VMs (default LSI Logic SAS)

Ethernet adapter type set to VMXNET 3 for all VMs (default E1000)

Floppy removed for all VMs (default enabled)

CDROM removed for all VMs (default enabled)

Cluster DRS Automation Level set to Fully Automated level 2

Hardware version 11 used for all VMs (default 8)

VMware Tools build 9541 used for all VMs (default 9536)

All DS2DB VMs had CPU shares set to 11500 (default Normal)

All DS2DB VMs had Disk shares set to high (default Normal)

All Standby VMs had CPU shares set to 10 (default Normal)

All Mailserver VMs had CPU shares set to 3300 (default Normal)

All OlioWeb VMs had CPU shares set to 3000 (default Normal)

All VMs except deploy template, sched.mem.min and sched.mem.minsize were set to the VM's memory size (default 0)

sched.mem.pin = TRUE set for all VMs except Deploy template VM (locks all Guest memory into physical memory, default FALSE)

sched.mem.maxmemctl= 0 set for all VMs except Deploy template and standby VMs (disables Ballooning, default enabled)

Multiqueue is disabled in the vmxnet3 driver on all linux VMs

The vmxnet3 driver version is 1.2.39.0 for all linux VMs

The host firewall was disabled on both SUT hosts (default Enabled)

Syslog.global.defaultSize set to 112 (default 1024)

Vpx.Vpxa.config.log.level and Config.HostAgent.log.level set to warning (default verbose)

Advanced Setting

esxcfg-advcfg -s 1961 /Cpu/CreditAgePeriod (default 3000)

esxcfg-advcfg -s 0 /Cpu/HTWholeCoreThreshold (default 200)

esxcfg-advcfg -s 0 /DataMover/HardwareAcceleratedInit (default 1)

esxcfg-advcfg -s 0 /DataMover/HardwareAcceleratedMove (default 1)

esxcfg-advcfg -s 0 /Mem/CtlMaxpercent (default 65)

esxcfg-advcfg -s 0 /Mem/ShareScanGHz (default 4)

esxcfg-advcfg -s 1000 /Net/MaxNetifRxQueueLen (default 100)

esxcfg-advcfg -s 2000 /Net/MaxNetifTxQueueLen (default 500)

esxcfg-advcfg -s 0 /Numa/LTermFairnessInterval (default 5)

esxcfg-advcfg -s 57 /Numa/MigImbalanceThreshold (default 10)

esxcfg-advcfg -s 0 /Numa/PageMigEnable (default 1)

esxcfg-advcfg -s 60000 /Numa/RebalancePeriod (default 2000)

esxcfg-advcfg -s 0 /Numa/SwapLoadEnable (default 1)

esxcfg-advcfg -s 0 /Numa/SwapLocalityEnable (default 1)

esxcfg-advcfg -s static /Power/CpuPolicy (default balanced)

esxcfg-advcfg -s 0 /VMFS3/HardwareAcceleratedLocking (default 1)

esxcfg-advcfg -s 1 /Disk/ReqCallThreshold (default 8)

esxcfg-advcfg -s 160 /Net/MaxPortRxQueueLen (default 80)

Driver options:

/usr/sbin/esxcfg-module -s "ql2xmaxqdepth=256" qlnativefc (default 64)

Server Notes

Server BIOS settings:

Turbo Boost Technology: Enabled (Intel Turbo Boost up to 3.3GHz , default enabled)

All C-States: disabled (default enable)

Networking Notes

vSwitch0 for the service Console at 1Gb/s on vmnic0

vSwitch1 for DS2-VMs workloads at 10Gb/s on vmnic2

vSwitch2 for all VMs except DS2-VMs at 10Gb/s on vmnic4

vSwitch3 for VMotion at 10Gb/s on vmnic5

Storage Notes

ESXi was install on two disk configured as RAID1 in the internal server storage bay

Round robin policy was used for FUSIONIO disk (default most recently used)

All LUNs were configured as block devices; no system memory was used for caching

The Fusion-io LUNs had “No. of outstanding IOs with competing worlds” set to 256 (default 32)

1xRH2288H V2 configured as a Fibre Channel Target

Hardware details:

Two Intel Xeon E5-2690v2@3.0GHz processors

128GB RAM(8x16 GB dual rank PC3-14900 Registered DDR3/1866 MHz DIMMs)

Two Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

3xFusion-io ioDrive2 Duo 2.4TB PCIE-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details: SanDisk ION Accelerator version 2.50 build 276

RAID configuration: No RAID level used on PCIe-SSD

First PCIe-SSD:

LUN 1: For Tile 0,1,24,25 DS2 VMs (1200GB)

LUN 2: For Tile 4,5,28,29 DS2 VMs (1200GB)

Second PCIe-SSD:

LUN 1: For Tile 8,9,32,33 DS2 VMs (1200GB)

LUN 2: For Tile 12,13,36,37 DS2 VMs (1200GB)

Third PCIe-SSD:

LUN 1: For Tile 16,17 DS2 VMs (1200GB)

LUN 2: For Tile 20,21 DS2 VMs (1200GB)

1xRH2288H V2 configured as a Fibre Channel Target

Hardware details:

Two Intel Xeon E5-2690v2@3.0GHz processors

128GB RAM(8x16 GB dual rank PC3-14900 Registered DDR3/1866 MHz DIMMs)

Two Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

3xFusion-io ioDrive2 Duo 2.4TB PCIE-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details: SanDisk ION Accelerator version 2.50 build 276

RAID configuration: No RAID level used on PCIe-SSD

First PCIe-SSD:

LUN 1: For Tile 2,3,26,27 DS2 VMs (1200GB)

LUN 2: For Tile 6,7,30,31 DS2 VMs (1200GB)

Second PCIe-SSD:

LUN 1: For Tile 10,11,34,35 DS2 VMs (1200GB)

LUN 2: For Tile 14,15,38,39 DS2 VMs (1200GB)

Third PCIe-SSD:

LUN 1: For Tile 18,19 DS2 VMs (1200GB)

LUN 2: For Tile 22,23 DS2 VMs (1200GB)

1xRH2288H V3 configured as a Fibre Channel Target

Hardware details:

Two Intel Xeon E5-2699v3@3.0GHz processors

128GB RAM(8x16 GB dual rank PC4-2133 Registered DDR4/2133MHz DIMMs)

One Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

2XHUAWEI ES3000 V2 3.2TB PCIE-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details:

Operating System: SUSE Linux Enterprise Server 11 SP3 – 3.0.101-0.8 (64-bit)

Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11SP3)

RAID configuration: No RAID level used on PCIe-SSD

First PCIe-SSD:

LUN 1: For Tile 0-9 Olio and mailserver VMs (2329GB)

Second PCIe-SSD:

LUN 1: For Tile 20-29 Olio and mailserver VMs (2329GB)

1xRH2288H V3 configured as a Fibre Channel Target

Hardware details:

Two Intel Xeon E5-2699v3@3.0GHz processors

128GB RAM(8x16 GB dual rank PC4-2133 Registered DDR4/2133MHz DIMMs)

One Qlogic QLE2562 8GB FC HBA user as FC target controllers

One LSI RAID SAS 6G Controller with 1GB Cache

2XHUAWEI ES3000 V2 3.2TB PCIE-SSD

2x400GB SAMSUNG-2.5-480GB-SATA-SSD

2x200GB SATA-SSDs (for the storage server' os)

Software details:

Operating System: SUSE Linux Enterprise Server 11 SP3 – 3.0.101-0.8 (64-bit)

Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 11SP3)

RAID configuration: No RAID level used on PCIe-SSD

Every 400GB SSD configured as raid0

First PCIe-SSD:

LUN 1: For Tile 10-19 Olio and mailserver VMs (2329GB)

Second PCIe-SSD:

LUN 1: For Tile 30-39 Olio and mailserver VMs (2329GB)

First 400GB SSD:

LUN 1: For standby VMs (300GB)

LUN 2: For DeployTemplate VMs (20GB)

First 400GB SSD:

LUN 1: Target LUN for Storage VMotion (200GB)

LUN 2: Target LUN for Storage Deploy (200GB)

Client storage notes

1xPrime Client: 1x500GB Seagate ST9500620NS 6G 7200 rpm SFF SATA disk with no RAID used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

1xVirtual Client Host: 4x300GB Seagate ST300MM0006 6G 10K rpm SFF SAS disk with RAID 10 used for hosts' OS.

Datacenter Management Server Notes

None

Operating System Notes

All Mailserver VMs running Microsoft Windows Server 2008 R2 Enterprise SP1(64-bit)

All Standby VMs running Microsoft Windows Server 2003 R2 Enterprise SP2(32-bit)

All SLES11 VMs were updated with SP2

Software Notes

Each Mailserver VM running Microsoft Exchange Server 2007 Enterprise SP3 (64-bit)

Client Notes

Prime client was running VMware vSphere PowerCLI 5.8 Build 2057893

All virtual client hosts were installed with VMware ESXi 5.5.0 (Build 1331820)

Other Notes

TILEDELAY reduced to 29 seconds (default: 60 seconds)

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit www.vmware.com/products/vmmark.

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of [VMware, Inc.](http://www.vmware.com) VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.