

# VMmark® 3.1.1 Results

**Server Vendor & Model:** HPE ProLiant DL380 Gen11  
**Storage Vendor & Model:** VMware vSAN 8.0 - All Flash  
**Hypervisor:** VMware ESXi 8.0a Patch, Build 20842819  
**Datacenter Management Software:** VMware vCenter Server 8.0 GA Build 20519528

**VMmark 3.1.1 Score =  
40.83 @ 42 Tiles**

Number of Hosts: 4	Uniform Hosts [yes/no]: yes	Total sockets/cores/threads in test: 8/448/896
Tested By: Hewlett Packard Enterprise		Test Date: 12-12-2022
<b>Performance Section</b> <a href="#">Performance</a>	<b>Configuration Section</b> <a href="#">Configuration</a>	<b>Notes Section</b> <a href="#">Notes for Workload</a>

## Performance

	weathervane			weathervaneE			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3583.74	1.00	0.57   0.00	564.02	0.99	0.47   0.19	930.98	1.27	776.08	663.50	1.33	887.63	470.75	1.36	959.27	1.18
<b>p1</b>	3568.66	0.99	0.59   0.00	561.32	0.98	0.46   0.13	913.65	1.24	822.69	669.30	1.34	927.76	480.45	1.39	1011.41	1.18
<b>p2</b>	3550.94	0.99	0.64   0.00	562.43	0.98	0.56   0.20	889.92	1.21	897.52	623.45	1.25	1042.09	457.12	1.32	1146.10	1.14
<b>TILE_1</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3580.52	1.00	0.54   0.00	564.37	0.99	0.49   0.14	962.20	1.31	700.13	686.77	1.37	795.30	489.27	1.41	859.48	1.20
<b>p1</b>	3559.21	0.99	0.55   0.00	555.83	0.97	0.47   0.17	945.67	1.29	735.25	700.62	1.40	828.80	504.85	1.46	889.28	1.20
<b>p2</b>	3549.42	0.99	0.55   0.00	555.47	0.97	0.47   0.13	947.75	1.29	736.88	679.42	1.36	828.36	507.48	1.46	882.82	1.20
<b>TILE_2</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3582.72	1.00	0.70   0.01	568.41	0.99	0.66   0.31	989.55	1.35	646.41	708.55	1.42	728.16	507.60	1.46	786.35	1.23
<b>p1</b>	3569.10	0.99	0.71   0.00	564.89	0.99	0.48   0.20	978.65	1.33	663.31	731.95	1.46	735.02	528.10	1.52	783.79	1.24
<b>p2</b>	3549.60	0.99	0.71   0.00	564.51	0.99	0.47   0.13	976.55	1.33	679.55	701.27	1.40	762.52	521.12	1.50	817.78	1.22
<b>TILE_3</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3574.33	0.99	0.52   0.00	569.59	1.00	0.46   0.23	1006.10	1.37	620.06	717.75	1.43	713.90	520.52	1.50	759.53	1.24
<b>p1</b>	3556.61	0.99	0.53   0.00	566.19	0.99	0.39   0.10	997.67	1.36	632.02	741.95	1.48	711.12	539.23	1.55	752.89	1.25
<b>p2</b>	3542.00	0.98	0.52   0.01	564.63	0.99	0.51   0.26	994.50	1.35	652.14	710.52	1.42	741.36	531.58	1.53	793.76	1.23
<b>TILE_4</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3573.44	0.99	0.66   0.00	566.27	0.99	0.62   0.33	915.27	1.25	838.39	637.65	1.27	999.61	449.05	1.29	1091.91	1.15
<b>p1</b>	3558.54	0.99	0.66   0.00	561.59	0.98	0.40   0.12	902.50	1.23	883.02	651.48	1.30	1023.63	461.05	1.33	1140.15	1.16
<b>p2</b>	3551.54	0.99	0.64   0.00	559.24	0.98	0.38   0.14	900.70	1.23	904.66	624.80	1.25	1053.73	432.85	1.25	1193.58	1.13
<b>TILE_5</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM

<b>p0</b>	3577.76	0.99	0.57   0.00	563.87	0.99	0.47   0.19	994.20	1.35	621.45	715.50	1.43	701.13	511.40	1.47	755.10	1.23
<b>p1</b>	3567.93	0.99	0.60   0.00	561.09	0.98	0.49   0.11	985.62	1.34	638.84	740.17	1.48	696.63	538.65	1.55	743.00	1.25
<b>p2</b>	3554.64	0.99	0.60   0.00	558.50	0.98	0.35   0.13	986.45	1.34	642.55	712.52	1.42	718.14	530.42	1.53	769.98	1.23
<b>TILE_6</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3576.29	0.99	0.64   0.00	568.72	0.99	0.61   0.18	927.33	1.26	790.62	652.23	1.30	915.87	458.30	1.32	1010.11	1.17
<b>p1</b>	3562.42	0.99	0.64   0.00	562.99	0.98	0.40   0.10	930.12	1.27	794.43	683.65	1.37	903.06	485.85	1.40	988.47	1.19
<b>p2</b>	3547.77	0.99	0.71   0.00	559.05	0.98	0.51   0.13	936.65	1.28	782.40	658.23	1.32	900.43	484.52	1.40	976.87	1.18
<b>TILE_7</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3583.19	1.00	0.54   0.00	569.62	1.00	0.56   0.21	965.48	1.31	695.06	689.92	1.38	789.31	489.57	1.41	855.43	1.20
<b>p1</b>	3570.51	0.99	0.56   0.00	566.83	0.99	0.46   0.13	959.83	1.31	708.89	710.02	1.42	798.90	511.52	1.47	850.79	1.22
<b>p2</b>	3562.31	0.99	0.59   0.00	566.53	0.99	0.48   0.14	962.55	1.31	706.08	684.73	1.37	801.64	510.10	1.47	860.49	1.21
<b>TILE_8</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3571.66	0.99	0.69   0.00	565.41	0.99	0.36   0.09	931.42	1.27	771.34	667.90	1.33	857.20	444.12	1.28	976.67	1.16
<b>p1</b>	3552.84	0.99	0.68   0.00	562.38	0.98	0.54   0.18	924.65	1.26	800.29	685.27	1.37	879.59	501.20	1.45	993.19	1.19
<b>p2</b>	3536.14	0.98	0.72   0.00	558.84	0.98	0.50   0.11	927.77	1.26	775.32	645.62	1.29	862.60	460.23	1.33	993.27	1.16
<b>TILE_9</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3573.37	0.99	0.91   0.01	568.69	0.99	0.43   0.12	994.40	1.35	637.40	724.02	1.45	696.06	481.07	1.39	781.57	1.22
<b>p1</b>	3564.58	0.99	0.79   0.00	567.65	0.99	0.47   0.14	988.23	1.35	650.52	746.83	1.49	695.47	556.83	1.61	775.35	1.26
<b>p2</b>	3555.20	0.99	0.73   0.00	563.34	0.98	0.34   0.09	1000.90	1.36	623.15	701.30	1.40	691.10	513.45	1.48	770.86	1.22
<b>TILE_10</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3571.42	0.99	0.97   0.03	568.06	0.99	0.37   0.17	992.65	1.35	644.52	688.48	1.38	732.99	483.27	1.39	794.27	1.21
<b>p1</b>	3559.24	0.99	0.81   0.00	563.96	0.99	0.53   0.14	985.60	1.34	653.27	753.02	1.50	743.09	550.08	1.59	799.25	1.26
<b>p2</b>	3533.58	0.98	0.80   0.00	560.41	0.98	0.45   0.08	996.48	1.36	638.05	685.48	1.37	732.88	504.88	1.46	794.17	1.21
<b>TILE_11</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3574.71	0.99	0.62   0.00	569.41	1.00	0.51   0.19	925.20	1.26	824.14	628.08	1.25	953.04	442.85	1.28	1102.47	1.15
<b>p1</b>	3557.25	0.99	0.62   0.01	565.82	0.99	0.43   0.13	926.70	1.26	807.14	675.45	1.35	927.52	495.40	1.43	1044.12	1.19
<b>p2</b>	3544.94	0.99	0.61   0.00	563.38	0.98	0.40   0.11	940.00	1.28	785.28	654.15	1.31	928.51	456.57	1.32	1037.45	1.16
<b>TILE_12</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3573.17	0.99	0.59   0.00	565.05	0.99	0.51   0.15	940.55	1.28	763.23	670.05	1.34	861.61	470.40	1.36	953.86	1.18
<b>p1</b>	3561.02	0.99	0.58   0.00	566.41	0.99	0.48   0.14	930.25	1.27	785.34	691.77	1.38	868.05	510.88	1.47	957.70	1.20
<b>p2</b>	3552.12	0.99	0.60   0.00	562.52	0.98	0.58   0.17	930.15	1.27	783.40	667.67	1.33	872.31	471.15	1.36	955.61	1.17
<b>TILE_13</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3576.09	0.99	0.72   0.01	567.14	0.99	0.56   0.29	951.95	1.30	752.04	680.15	1.36	836.53	470.55	1.36	953.95	1.19
<b>p1</b>	3559.39	0.99	0.64   0.00	567.29	0.99	0.52   0.22	938.25	1.28	772.82	697.65	1.39	850.70	508.12	1.47	972.22	1.21
<b>p2</b>	3539.95	0.98	0.60   0.00	562.20	0.98	0.46   0.16	946.23	1.29	757.65	676.65	1.35	851.54	466.07	1.34	972.63	1.18
<b>TILE_14</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM

<b>p0</b>	3570.54	0.99	0.53   0.00	565.61	0.99	0.41   0.16	932.90	1.27	798.10	646.27	1.29	955.59	450.90	1.30	1061.88	1.16
<b>p1</b>	3564.03	0.99	0.52   0.00	565.76	0.99	0.49   0.24	927.52	1.26	805.55	669.55	1.34	940.32	498.18	1.44	1032.42	1.19
<b>p2</b>	3557.95	0.99	0.50   0.00	556.89	0.97	0.42   0.07	935.90	1.27	782.60	651.62	1.30	932.98	453.65	1.31	1037.17	1.16
<b>TILE_15</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3574.18	0.99	0.74   0.00	568.53	0.99	0.76   0.29	949.30	1.29	747.90	674.83	1.35	866.30	464.55	1.34	999.30	1.18
<b>p1</b>	3559.03	0.99	0.70   0.00	568.60	0.99	0.74   0.33	943.02	1.28	776.63	687.55	1.37	892.66	505.05	1.46	1003.51	1.20
<b>p2</b>	3538.07	0.98	0.72   0.00	565.25	0.99	0.57   0.15	951.77	1.30	744.36	671.00	1.34	865.86	462.52	1.33	993.95	1.18
<b>TILE_16</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3576.30	0.99	1.06   0.00	567.96	0.99	0.85   0.42	982.83	1.34	666.62	704.05	1.41	751.32	491.48	1.42	844.19	1.21
<b>p1</b>	3565.28	0.99	1.04   0.01	567.85	0.99	0.71   0.40	938.42	1.28	773.11	695.73	1.39	858.44	512.15	1.48	955.07	1.21
<b>p2</b>	3554.03	0.99	1.15   0.00	564.07	0.99	0.75   0.28	952.85	1.30	720.58	689.38	1.38	799.46	478.90	1.38	901.37	1.19
<b>TILE_17</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3575.10	0.99	0.42   0.00	571.52	1.00	0.46   0.31	1010.77	1.38	611.55	720.98	1.44	700.20	506.75	1.46	780.13	1.24
<b>p1</b>	3558.38	0.99	0.44   0.00	567.52	0.99	0.63   0.31	988.08	1.35	665.82	725.90	1.45	754.78	543.30	1.57	831.85	1.25
<b>p2</b>	3548.37	0.99	0.45   0.00	561.46	0.98	0.40   0.08	1000.98	1.36	631.16	714.12	1.43	723.96	499.27	1.44	810.58	1.22
<b>TILE_18</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3570.14	0.99	0.95   0.01	565.18	0.99	0.38   0.15	987.12	1.34	671.12	702.48	1.40	763.36	489.18	1.41	863.73	1.21
<b>p1</b>	3559.91	0.99	0.79   0.00	563.02	0.98	0.50   0.14	967.40	1.32	711.80	712.58	1.42	811.92	523.40	1.51	909.60	1.22
<b>p2</b>	3551.87	0.99	0.74   0.00	562.17	0.98	0.42   0.10	977.95	1.33	686.79	692.70	1.38	795.80	480.60	1.39	907.52	1.20
<b>TILE_19</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3571.83	0.99	0.61   0.00	570.73	1.00	0.88   0.44	989.73	1.35	663.62	710.33	1.42	755.22	492.50	1.42	849.80	1.22
<b>p1</b>	3555.97	0.99	0.62   0.00	564.91	0.99	0.66   0.35	988.92	1.35	663.16	728.30	1.46	757.73	538.95	1.55	842.16	1.24
<b>p2</b>	3538.24	0.98	0.63   0.01	563.00	0.98	0.51   0.21	998.62	1.36	641.39	712.60	1.42	735.68	472.75	1.36	835.91	1.21
<b>TILE_20</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3588.47	1.00	0.62   0.00	568.86	0.99	0.59   0.29	945.67	1.29	745.96	668.45	1.34	855.31	471.93	1.36	937.28	1.18
<b>p1</b>	3570.61	0.99	0.75   0.00	565.99	0.99	0.57   0.21	955.65	1.30	726.24	687.67	1.37	863.37	493.48	1.42	937.31	1.20
<b>p2</b>	3556.08	0.99	0.73   0.00	559.22	0.98	0.53   0.20	948.95	1.29	740.24	660.85	1.32	891.21	466.95	1.35	957.46	1.17
<b>TILE_21</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3570.21	0.99	0.91   0.02	564.52	0.99	0.46   0.22	949.27	1.29	754.45	676.67	1.35	856.89	465.55	1.34	972.32	1.18
<b>p1</b>	3553.77	0.99	0.76   0.03	564.55	0.99	0.44   0.14	945.58	1.29	763.74	690.80	1.38	879.46	504.93	1.46	995.37	1.20
<b>p2</b>	3534.20	0.98	0.71   0.00	562.40	0.98	0.35   0.10	956.75	1.30	741.19	654.27	1.31	849.36	444.73	1.28	980.04	1.16
<b>TILE_22</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3573.11	0.99	0.47   0.00	564.07	0.99	0.42   0.15	922.08	1.26	813.89	660.85	1.32	914.56	472.55	1.36	1055.10	1.17
<b>p1</b>	3564.81	0.99	0.48   0.00	563.47	0.98	0.45   0.10	926.48	1.26	813.32	669.60	1.34	953.23	470.60	1.36	1058.02	1.17
<b>p2</b>	3548.31	0.99	0.46   0.00	561.83	0.98	0.37   0.11	927.12	1.26	811.96	632.40	1.26	933.72	448.30	1.29	1066.57	1.15
<b>TILE_23</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM

<b>p0</b>	3581.61	1.00	0.57   0.00	566.69	0.99	0.64   0.24	998.35	1.36	641.65	715.90	1.43	720.45	513.60	1.48	839.93	1.23
<b>p1</b>	3570.56	0.99	0.59   0.00	559.62	0.98	0.35   0.10	983.62	1.34	669.25	702.83	1.40	763.82	510.43	1.47	869.39	1.22
<b>p2</b>	3561.17	0.99	0.57   0.00	558.70	0.98	0.51   0.23	982.08	1.34	673.01	699.98	1.40	770.21	485.12	1.40	886.59	1.20
<b>TILE_24</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3582.39	1.00	0.57   0.00	565.72	0.99	0.47   0.19	962.75	1.31	711.88	687.50	1.37	814.10	503.12	1.45	895.64	1.21
<b>p1</b>	3568.88	0.99	0.61   0.00	560.73	0.98	0.50   0.13	957.20	1.30	724.20	677.80	1.35	837.51	500.82	1.44	909.93	1.20
<b>p2</b>	3558.74	0.99	0.63   0.00	557.08	0.97	0.53   0.13	949.85	1.29	749.64	675.73	1.35	859.00	471.82	1.36	945.13	1.18
<b>TILE_25</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3583.07	1.00	0.51   0.00	567.08	0.99	0.64   0.35	935.10	1.27	784.33	679.40	1.36	908.80	472.57	1.36	1047.78	1.18
<b>p1</b>	3572.50	0.99	0.51   0.00	562.52	0.98	0.34   0.14	935.58	1.27	780.69	657.45	1.31	911.72	471.32	1.36	1029.78	1.17
<b>p2</b>	3560.64	0.99	0.52   0.00	557.83	0.97	0.54   0.18	935.83	1.27	778.39	659.33	1.32	907.06	451.57	1.30	1039.77	1.16
<b>TILE_26</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3580.46	1.00	0.63   0.00	565.99	0.99	0.44   0.09	938.75	1.28	781.36	686.62	1.37	891.11	481.43	1.39	1001.75	1.19
<b>p1</b>	3565.60	0.99	0.61   0.00	562.83	0.98	0.35   0.08	934.83	1.27	783.46	665.90	1.33	883.83	481.30	1.39	993.62	1.18
<b>p2</b>	3551.66	0.99	0.63   0.00	562.01	0.98	0.47   0.19	938.42	1.28	777.42	667.58	1.33	884.79	459.15	1.32	1012.92	1.17
<b>TILE_27</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3573.55	0.99	1.45   0.12	563.13	0.98	0.33   0.17	961.17	1.31	710.30	715.33	1.43	790.04	500.48	1.44	896.81	1.21
<b>p1</b>	3566.33	0.99	0.89   0.02	565.17	0.99	0.43   0.10	962.27	1.31	709.60	685.98	1.37	807.54	495.45	1.43	925.06	1.20
<b>p2</b>	3552.10	0.99	0.81   0.01	560.90	0.98	0.47   0.24	969.10	1.32	699.23	690.67	1.38	799.47	473.07	1.36	927.64	1.19
<b>TILE_28</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3578.01	0.99	0.86   0.01	564.93	0.99	0.49   0.15	975.88	1.33	671.96	727.52	1.45	754.49	512.73	1.48	860.60	1.23
<b>p1</b>	3567.17	0.99	0.92   0.00	561.55	0.98	0.46   0.15	965.88	1.32	691.33	696.00	1.39	769.69	510.57	1.47	868.22	1.21
<b>p2</b>	3548.76	0.99	1.03   0.00	561.69	0.98	0.41   0.08	953.10	1.30	728.72	694.75	1.39	786.94	483.57	1.39	897.77	1.19
<b>TILE_29</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3578.95	0.99	1.04   0.03	564.55	0.99	0.42   0.15	928.38	1.26	785.90	679.95	1.36	906.55	479.95	1.38	1007.88	1.18
<b>p1</b>	3559.53	0.99	0.81   0.00	562.14	0.98	0.42   0.16	929.77	1.27	799.35	650.00	1.30	935.76	473.23	1.36	1035.35	1.17
<b>p2</b>	3548.36	0.99	0.76   0.00	561.73	0.98	0.52   0.17	933.58	1.27	780.62	660.38	1.32	902.86	456.25	1.32	1008.38	1.16
<b>TILE_30</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3584.07	1.00	0.43   0.00	568.00	0.99	0.80   0.39	957.08	1.30	728.86	712.50	1.42	809.96	503.93	1.45	911.14	1.22
<b>p1</b>	3565.57	0.99	0.46   0.00	562.93	0.98	0.46   0.13	948.88	1.29	751.07	679.75	1.36	842.31	496.93	1.43	943.12	1.20
<b>p2</b>	3555.37	0.99	0.48   0.00	560.40	0.98	0.50   0.23	957.58	1.30	733.21	679.60	1.36	842.21	471.20	1.36	956.23	1.18
<b>TILE_31</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3582.41	1.00	0.65   0.00	564.49	0.99	0.50   0.23	995.75	1.36	646.68	737.98	1.47	734.85	522.15	1.51	821.45	1.24
<b>p1</b>	3563.50	0.99	0.61   0.00	563.82	0.99	0.43   0.20	999.10	1.36	642.03	716.65	1.43	729.18	525.30	1.51	811.89	1.24
<b>p2</b>	3553.41	0.99	0.67   0.01	561.05	0.98	0.40   0.13	1004.58	1.37	625.48	721.10	1.44	722.51	502.12	1.45	816.84	1.23
<b>TILE_32</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM

<b>p0</b>	3578.66	0.99	0.53   0.00	562.28	0.98	0.39   0.13	922.20	1.26	835.47	680.85	1.36	933.55	472.52	1.36	1062.72	1.18
<b>p1</b>	3564.44	0.99	0.53   0.00	562.99	0.98	0.49   0.18	925.15	1.26	828.68	646.73	1.29	976.38	462.90	1.33	1122.81	1.16
<b>p2</b>	3549.84	0.99	0.55   0.00	563.30	0.98	0.46   0.19	874.45	1.19	964.16	624.20	1.25	1086.37	420.82	1.21	1253.68	1.12
<b>TILE_33</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3579.50	0.99	0.94   0.01	564.00	0.99	0.32   0.08	997.58	1.36	636.80	742.67	1.48	711.13	527.17	1.52	792.17	1.25
<b>p1</b>	3566.52	0.99	0.86   0.00	564.03	0.99	0.43   0.08	1008.25	1.37	607.26	719.80	1.44	703.76	526.02	1.52	788.57	1.24
<b>p2</b>	3551.31	0.99	0.80   0.00	562.41	0.98	0.52   0.17	994.23	1.35	636.12	720.95	1.44	697.08	504.12	1.45	785.53	1.22
<b>TILE_34</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3578.49	0.99	0.55   0.00	564.62	0.99	0.44   0.11	923.95	1.26	801.57	684.15	1.37	903.97	480.07	1.38	1025.08	1.19
<b>p1</b>	3568.12	0.99	0.58   0.00	563.81	0.99	0.57   0.21	945.02	1.29	767.98	641.88	1.28	891.10	463.77	1.34	1001.30	1.17
<b>p2</b>	3551.05	0.99	0.58   0.00	560.59	0.98	0.49   0.17	937.02	1.28	776.04	690.12	1.38	879.83	487.23	1.40	976.77	1.19
<b>TILE_35</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3581.44	1.00	0.54   0.00	562.33	0.98	0.47   0.20	965.20	1.31	711.01	713.77	1.43	808.98	524.23	1.51	913.06	1.23
<b>p1</b>	3562.94	0.99	0.56   0.00	564.60	0.99	0.50   0.17	970.10	1.32	701.96	678.83	1.36	848.28	478.90	1.38	933.58	1.19
<b>p2</b>	3556.10	0.99	0.54   0.00	563.32	0.98	0.52   0.23	953.08	1.30	754.83	677.60	1.35	854.86	492.95	1.42	967.43	1.19
<b>TILE_36</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3581.16	1.00	0.73   0.02	562.47	0.98	0.37   0.07	911.85	1.24	850.91	691.17	1.38	960.91	487.02	1.40	1095.25	1.19
<b>p1</b>	3564.42	0.99	0.76   0.01	562.36	0.98	0.41   0.09	916.88	1.25	840.73	620.88	1.24	986.00	446.65	1.29	1111.55	1.14
<b>p2</b>	3552.13	0.99	0.82   0.00	561.28	0.98	0.45   0.20	905.77	1.23	864.80	664.15	1.33	996.42	464.38	1.34	1120.71	1.16
<b>TILE_37</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3581.91	1.00	0.48   0.00	562.51	0.98	0.49   0.18	967.35	1.32	709.49	742.65	1.48	797.15	528.17	1.52	899.21	1.24
<b>p1</b>	3564.07	0.99	0.50   0.00	565.35	0.99	0.48   0.19	974.83	1.33	690.19	673.77	1.35	791.49	486.73	1.40	885.45	1.20
<b>p2</b>	3557.34	0.99	0.49   0.00	562.88	0.98	0.59   0.23	977.90	1.33	689.61	724.75	1.45	774.55	512.77	1.48	864.57	1.23
<b>TILE_38</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3579.81	0.99	0.65   0.00	564.52	0.99	0.37   0.08	1009.05	1.37	605.60	757.75	1.51	673.99	566.75	1.63	746.45	1.27
<b>p1</b>	3565.36	0.99	0.65   0.00	564.42	0.99	0.39   0.15	1012.20	1.38	599.78	734.20	1.47	677.23	513.73	1.48	759.83	1.24
<b>p2</b>	3554.56	0.99	0.67   0.00	560.01	0.98	0.47   0.13	1012.38	1.38	598.92	763.08	1.52	656.78	544.67	1.57	732.08	1.26
<b>TILE_39</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3582.74	1.00	0.48   0.00	563.82	0.99	0.42   0.16	960.35	1.31	706.65	715.77	1.43	790.63	527.15	1.52	886.19	1.23
<b>p1</b>	3570.46	0.99	0.48   0.00	563.98	0.99	0.51   0.14	971.80	1.32	684.40	697.38	1.39	774.22	483.52	1.39	880.25	1.20
<b>p2</b>	3552.89	0.99	0.48   0.00	562.72	0.98	0.52   0.15	958.17	1.30	710.34	718.45	1.44	779.34	500.80	1.44	895.82	1.21
<b>TILE_40</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM
<b>p0</b>	3580.01	1.00	0.80   0.00	562.63	0.98	0.46   0.21	902.08	1.23	886.47	661.95	1.32	1004.75	485.60	1.40	1127.65	1.17
<b>p1</b>	3563.13	0.99	0.78   0.01	563.08	0.98	0.57   0.25	907.45	1.24	859.69	644.60	1.29	988.23	444.32	1.28	1119.53	1.15
<b>p2</b>	3556.42	0.99	0.71   0.00	561.56	0.98	0.67   0.35	895.38	1.22	901.79	662.00	1.32	1018.69	461.10	1.33	1141.20	1.16
<b>TILE_41</b>	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(nRT MaxPctF)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	Actual	Ratio	QoS(ms)	GM

<b>p0</b>	3583.63	1.00	0.48   0.00	564.12	0.99	0.40   0.10	937.85	1.28	786.01	690.58	1.38	890.51	511.98	1.48	982.72	1.21
<b>p1</b>	3568.52	0.99	0.52   0.00	562.29	0.98	0.48   0.13	938.92	1.28	782.15	665.05	1.33	905.89	461.25	1.33	1011.79	1.17
<b>p2</b>	3552.34	0.99	0.50   0.00	560.37	0.98	0.55   0.21	935.25	1.27	787.71	685.80	1.37	895.59	486.88	1.40	992.33	1.19
<b>p0_score:</b>	50.49															
<b>p1_score:</b>	50.52															
<b>p2_score:</b>	49.89															
<b>Infrastructure_Operations_Scores:</b>							vMotion	SVMotion	XVMotion	Deploy						
<b>Completed_Ops_PerHour</b>							55.00	40.00	34.00	20.00						
<b>Avg_Seconds_To_Complete</b>							8.33	141.36	157.46	324.81						
<b>Failures</b>							0.00	0.00	0.00	0.00						
<b>Ratio</b>							2.12	2.22	1.89	2.50						
<b>Number_Of_Threads</b>							2	2	2	2						
<b>Summary</b>							Run_Is_Compliant			Turbo_Setting:0						
							Number_Of_Compliance_Issues(0)*			Median_Phase(p0)						
<b>Unreviewed_VMmark3_Applications_Score</b>							50.49									
<b>Unreviewed_VMmark3_Infrastructure_Score</b>							2.17									
<b>Unreviewed_VMmark3_Score</b>							40.83									

## Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESXi 8.0a Patch, Build 20842819 / 12-08-2022
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 8.0 GA Build 20519528 / 10-11-2022
Supplemental Software	None
Servers	
Number of Servers in System Under Test (all subsequent fields in this section are per server)	4
Server Manufacturer and Model	HPE ProLiant DL380 Gen11

Processor Vendor and Model	Intel(R) Xeon(R) Platinum 8480+
Processor Speed (GHz) / Turbo Boost Speed (GHz)	2.00 / 3.80
Total Sockets/Total Cores/Total Threads	2 Sockets / 112 Cores / 224 Threads
Primary CPU Cache	32 KB I + 48 KB D on chip per core
Secondary CPU Cache	2 MB I+D on chip per core
Other CPU Cache	105 MB I+D on chip per chip
BIOS Version	U54 v1.20 (11/24/2022)
Memory Size (in GB, Number of DIMMs)	2048, 32
Memory Type and Speed	64 GB 2Rx4 DDR5-4800 MHz RDIMM
Disk Subsystem Type	vSAN, FC SAN
Number of Disk Controllers	0
Disk Controller Vendors and Models	N/A
Total Number of Physical Disks for Hypervisor	1
Disk Vendors, Models, Capacities, and Speeds	HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
Number of Host Bus Adapters	1
Host Bus Adapter Vendors and Models	HPE SN1610Q 32Gb 2p FC HBA
Number of Network Controllers	2
Network Controller Vendors and Models	Mellanox MCX623106AS 100GbE 2p QSFP56 Adptr
Other Hardware	None
Other Software	None
Hardware Availability Date (MM-DD-YYYY)	03-10-2023
BIOS Availability Date (MM-DD-YYYY)	03-10-2023
Software Availability Date (MM-DD-YYYY)	03-10-2023
<b>Network</b>	
Network Switch Vendors and Models	HPE SN2700M 100GbE 32QSFP28
Network Speed	DSwitch-VM-Network: 100 Gbps DSwitch-Management-Network: 100 Gbps for SUT, 10 Gbps for Client1 and 1 Gbps for Client2-5

DSwitch-vMotion: 100 Gbps for SUT, 10 Gbps for Client1 and 1 Gbps for Client2-5

### Primary Storage

Storage Category	VMware vSAN
Storage Vendors, Models, and Firmware Versions	4 x HPE ProLiant DL380 Gen11 servers in a VMware vSAN 8.0 cluster
Storage Configuration Summary	<p>VMware vSAN</p> <ul style="list-style-type: none"><li>• 3 x Disk Groups per host</li><li>• 3 x HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD</li><li>• 9 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD</li></ul>

### Datacenter Management Server

System Model	HPE ProLiant DL360 Gen10
Processor Vendor and Model	Intel Xeon Gold 6258R
Processor Speed (GHz)	2.7
Total Sockets/Total Cores/Total Threads	2 Sockets / 56 Cores / 112 Threads
Memory Size (in GB, Number of DIMMs)	256, 16
Network Controller(s) Vendors and Models	HPE 1Gb Ethernet 4-Port 331 FLR Adapter
Operating System, Version, Bitness, and Service Pack	VMware ESXi 8.0 GA Build 20513097
Virtual Center VM Number of vCPUs	16
Virtual Center VM Virtual Memory (in GB)	39 GB
Virtual Center VM Operating System, Version, Bitness, and Service Pack	VMware vCenter Server 8.0 GA Build 20519528
Other Hardware	None
Other Software	None

### Clients

Total Number of Virtual Clients / Virtual Client Hosts	43 / 5
System Model(s)	Host 1: HPE ProLiant DL385 Gen10 Plus v2 Hosts 2-5: HPE ProLiant DL380 Gen10 Plus
Processor Vendor(s) and Model(s)	Host 1: AMD EPYC 7763 Hosts 2-5: Intel Xeon Platinum 8380
Processor Speed(s) (GHz)	Host 1: 2.45 Hosts 2-5: 2.3

Total Sockets/Total Cores/Total Threads	Host 1: 2 Sockets / 128 Cores / 256 Threads Hosts 2-5: 8 Sockets / 320 Cores / 640 Threads
Memory per Virtual Client Host	Host 1: 512 GB Hosts 2-5: 2 TB
Network Controller(s) Vendors and Models	Host 1: <ul style="list-style-type: none"> <li>1 x Mellanox MCX562A-ACAI Ethernet 10/25Gb 2-port SFP28 OCP3 Adapter for HPE</li> <li>1 x Mellanox ConnectX-5 EN 100Gb/s 2-port Ethernet Adapter</li> </ul> Hosts 2-5: <ul style="list-style-type: none"> <li>1 x Intel I350-T4 Ethernet 1Gb 4-port BASE-T OCP3 Adapter for HPE</li> <li>1 x Mellanox MCX623106AS-CDAT Ethernet 100Gb 2-port QSFP56 Adapter for HPE</li> </ul>
Virtual Client Networking Notes	Details in Networking Notes
Virtual Client Storage Notes	Details in Client Notes
Other Hardware	1 * HPE SN1610Q 32Gb 2p FC HBA
Other Software	VMware ESXi 8.0 GA Build 20513097

#### Security Mitigations

Vulnerability	CVE	Exploit Name	Public Vulnerability Name	Mitigated		
				Server Firmware	ESXi	Guest OS
Spectre	2017-5753	Variant 1	Bounds Check Bypass	N/A	Yes	Yes
Spectre	2017-5715	Variant 2	Branch Target Injection	Yes	Yes	Yes
Meltdown	2017-5754	Variant 3	Rogue Data Cache Load	N/A	Yes	Yes
Spectre-NG	2018-3640	Variant 3a	Rogue System Register Read	Yes	N/A	N/A
Spectre-NG	2018-3639	Variant 4	Speculative Store Bypass	N/A	Yes	Yes
Foreshadow	2018-3615	Variant 5	L1 Terminal Fault - SGX	N/A	N/A	N/A
Foreshadow-NG	2018-3620	Variant 5	L1 Terminal Fault - OS	N/A	N/A	Yes
Foreshadow-NG	2018-3646	Variant 5	L1 Terminal Fault - VMM	N/A	Yes	N/A

## Notes for Workload

Template deployed with disk type: Thick

### Virtualization Software Notes

- Cluster DRS Automation Level set to Fully Automated
- vSphere DRS Migration Threshold level set to 2

- vSphere DRS Advanced Option AggressiveCPUActive set to 1
- Logical CPU layout changed for all multi-CPU VMs to 1 socket with multiple cores (default single core per socket)
- Logging was disabled for all VMs (default enabled)
- All DS3DB, ElasticDB, and ElasticLB VMs had CPU shares set to High (default Normal)
- All Standby VMs had CPU shares set to Low (default Normal)
- All memory reserved (LockedToMax) for all DS3DB VMs
- sched.mem.lpage.enable1GPage set to TRUE for all DS3DB VMs (default FALSE)
- DS3DB0 was configured to not use the third virtual disk before building additional tiles.
- CD and floppy devices were removed from all VMs (default installed)
- PrimeClient's second virtual disk configured to be 1.2 TB (default: 200 GB)

#### Advanced Settings:

- Cpu.CoschedCrossCall = 0 (default 1)
- Cpu.CreditAgePeriod = 1000 (default 3000)
- Cpu.HTWholeCoreThreshold = 0 (default 800)
- DataMover.HardwareAcceleratedInit = 0 (default 1)
- DataMover.HardwareAcceleratedMove = 0 (default 1)
- Disk.IdleCredit = 64 (default 32)
- Disk.ReqCallThreshold = 1 (default 8)
- Mem.CtlMaxPercent = 0 (default 65)
- Mem.ShareScanGHz = 0 (default 4)
- Numa.LTermFairnessInterval = 0 (default 5)
- Numa.LargeInterleave = 0 (default 1)
- Numa.LocalityWeightActionAffinity = 0 (default 130)
- Numa.MigImbalanceThreshold = 57 (default 10)
- Numa.MigPreventLTermThresh = 20 (default 0)
- Numa.MigThreshold = 0 (default 2)
- Numa.MonMigEnable = 0 (default 1)
- Numa.PageMigEnable = 0 (default 1)
- Numa.PreferHT = 1 (default 0)
- Numa.RebalancePeriod = 60000 (default 2000)
- Numa.SwapLoadEnable = 0 (default 1)
- Numa.SwapLocalityEnable = 0 (default 1)
- Power.CpuPolicy = 'High Performance' (default Balanced)
- VMkernel.Boot.hyperthreadingMitigation = true (default false)
- UserVars.HostClientCEIPOptIn = 2 (default 0)

## Server Notes

#### Server BIOS settings

- HPE Workload Profile set to "Virtualization - Max Performance" (default: General Power Efficient Compute)
- Thermal Configuration set to Maximum Cooling (default: Optimal Cooling)
- Adjacent Sector Prefetch set to disabled (default: Enabled)

- DCU Stream Prefetcher set to disabled(default: Enabled)
- LLC deadline allocation set to disabled(default: Enabled)
- Memory Patrol Scrubbing set to disabled(default: Enabled)
- EPP set to Aggressive(default: Disabled)

## Networking Notes

Distributed vSwitch configuration:

- All SUT and client hosts were part of the same distributed vSwitch.
- The MTU of the distributed vSwitch was set to 9000 (default 1500). Except where noted differently below, the same change was made to all vmnics, vmk1, and vmk2.
- 'DSwitch-Management-Network' port group
  - Uplinks:
    - vmnic0 on SUT hosts
    - vmnic2 on client hosts
  - Usage:
    - vmk0(MTU 1500) on all SUT and client hosts - used for management
    - One virtual NIC port of PrimeClient VM
- 'DSwitch-vMotion' port group
  - Uplinks:
    - vmnic0 on SUT hosts
    - vmnic2 on client hosts
  - Usage:
    - vmk1 on all SUT hosts - used for vMotion
    - vmk1(MTU 1500) on all client hosts - used for vMotion
- 'DSwitch-VM-Network' port group
  - Uplinks:
    - SUT hosts: vmnic1, vmic2
    - client hosts: vmnic0, vmnic1
  - Usage:
    - All VMs - including one virtual NIC port of PrimeClient VM

HPE SN2700M switch was configured for RoCE lossless and LLDP.

## Storage Notes

OS Storage

- On each SUT host, VMware ESXi 8.0a patch was installed on HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD .
- On client host1, VMware ESXi 8.0 GA was installed on HPE NS204i-p Gen10 Plus Boot Controller, which provides a RAID1 volume on 2 x 480 GB NVMe M.2 SSDs.
- On client hosts2-5, VMware ESXi 8.0 GA was installed on a RAID1 volume on 2 x HPE 800GB SAS MU SFF SC SED FIPS PM6 SSD.
  - HPE Smart Array P408i-a SR Gen10

Primary Storage: VMware vSAN storage

- VMware vSAN 8.0 OSA
  - Capacity: 209.59 TB
  - Cache: 17.52 TB

- Hardware Configuration
  - Each host had 3 disk groups. Each disk group had:
    - Cache Tier: 1 x HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - Capacity Tier: 3 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
- Software Configuration
  - RDMA support service enabled (for vSAN over RDMA feature)
  - SUT vSAN Datastore was used for all SUT VMs and template VMs ,Following changes were made to "vSAN Default Storage Policy":
    - "Disable object checksum" set to enable (default: disable)
    - "Object space reservation" set to "Thick provisioning" (default: Thin provisioning)

Secondary Storage: FC Channel Target via SCSI Target Server (LIO)

- All SUT and client hosts were configured to use Round Robin path policy (default Most Recently Used) with iops = 1 (default 1000).
- Hardware details:
  - HPE ProLiant DL380 Gen10 Plus
    - 2 x Intel Xeon Platinum 8380 (2.30 GHz)
    - 2048 GB (32 x 64GB 2Rx4 3200 MHz DDR4 RDIMMs)
    - 3 x HPE SN1610Q 32Gb 2-port FC HBA used as FC target controller
    - 2 x HPE 1.6TB SAS MU SFF SC DS SSD
    - 2 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
- Software details:
  - Operating System: SUSE Linux Enterprise Server 15 SP4 - 5.14.21-150400.22-default x86\_64
  - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 15 SP4)
- LUN details:
  - 2 x HPE 1.6TB SAS MU SFF SC DS SSD configured as RAID1 Volume using HPE Smart Array P408i-a SR Gen10
    - 1 LUN(1.46 TB)
    - Storage system OS (not exported as FC target LUN)
  - 1 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - 1 LUN (1 TB): SVmotion Target LUN
    - 1 LUN (1 TB): DeployTarget LUN
  - 1 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - 1 LUN (5.82 TB): XVmotion Target LUN

## Datacenter Management Server Notes

VMware vCenter Server Appliance 8.0 GA, Build 20519528 was hosted on a HPE ProLiant DL360 Gen10 system that was not part of the client or SUT clusters.

## Operating System Notes

OS installation on SUT hosts was done using the HPE customized ESXi 8.0a patch ISO for ProLiant Gen11 servers. This is a pre-released version, which will be publicly released and available for customers to access by March 10, 2023. OS installation on client hosts was done using the VMware ESXi 8.0 GA, Build 20513097 ISO as released by VMware for OS installation. After the OS was installed, VIB packages were downloaded from the URLs listed below and were installed.

- <http://vibsdepot.hpe.com/hpe/oct2022/esxi-800-devicedrivers/>
- <http://vibsdepot.hpe.com/hpe/oct2022/esxi-800-bundles/>

## Software Notes

None

## Client Notes

Advanced ESXi settings:

- Power.CpuPolicy = High Performance (default Balanced)
- UserVars.HostClientCEIPOptIn = 2 (default 0)

Server BIOS settings:

- HPE Workload Profile set to "Virtualization - Max Performance" (default: General Power Efficient Compute)

The client VMs were distributed across the client hosts as follows:

- Client host 1: Client17,Client19,Client30,Client32,Client34,Client36,Client37,Client38,Client39
- Client host 2: Client1,Client3,Client5,Client7,Client9,Client11,Client13,Client15
- Client host 3: Client0,Client2,Client4,Client6,Client8,Client10,Client12,Client14,Client41
- Client host 4: Client21,Client23,Client25,Client27,Client29,Client31,Client33,Client35
- Client host 5: Client16,Client18,Client20,Client22,Client24,Client26,Client28,Client40,PrimeClient

Client Storage: FC Channel Target via SCSI Target Server (LIO)

- Hardware details:
  - HPE ProLiant DL380 Gen10 Plus
    - 2 x Intel Xeon Platinum 8380 (2.30 GHz)
    - 2048 GB (32 x 64GB 2Rx4 3200 MHz DDR4 RDIMMs)
    - 2 x HPE SN1610Q 32Gb 2-port FC HBA used as FC target controller
    - 2 x HPE 1.6TB SAS MU SFF SC DS SSD
    - 1 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - 1 x HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
- Software details:
  - Operating System: SUSE Linux Enterprise Server 15 SP4 - 5.14.21-150400.22-default x86\_64
  - Fibre Channel Target SW: LIO (part of SUSE Linux Enterprise Server 15 SP4)
- LUN details:
  - 2 x HPE 1.6TB SAS MU SFF SC DS SSD configured as RAID1 Volume using HPE Smart Array E208i-a SR Gen10
    - 1 LUN(1.46 TB)
    - Storage system OS (not exported as FC target LUN)
  - 1 x HPE 6.4TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - 1 LUN(5.82 TB): ClientVMs
  - 1 x HPE 1.6TB NVMe Gen4 High Performance Mixed Use SFF BC U.3 PM1735a SSD
    - 1 LUN(1.46 TB): PrimeClient VM

## Other Notes

VMmark3.properties file modifications:

- TileDelay = 5 (default 60)
- VCscratchDir = /root/VMmark3/results/scratch (default /root/VMmark3/samples)
- ErrorImmediate = true(default false)

---

This is a full disclosure report for a VMmark® benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit [www.vmware.com/products/vmmark](http://www.vmware.com/products/vmmark).

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMmark is a product of [VMware, Inc.](http://www.vmware.com) VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.