

# VMware® VMmark™ V1.1 Results

**Vendor and Hardware Platform: Dell PowerEdge R905**  
**Virtualization Platform: VMware ESX version 4.0 (build 159706)**

**VMmark V1.1 Score =**  
**22.70 @ 16 Tiles**

Tested By: Dell Inc.

Test Date: 04/27/2009

**Performance Section**  
[Performance](#)

**Configuration Section**  
[Configuration](#)

**Notes Section**  
[Notes for Workload](#)

## Performance

	webserver		javaserver		mailserver		fileserver		database		
<b>TILE_0</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1697.65	1.67	18115.40	1.09	1480.65	1.35	16.52	1.29	2296.05	1.54	1.37
<b>p1</b>	1696.95	1.67	18112.25	1.09	1531.78	1.40	16.73	1.30	2299.53	1.54	1.38
<b>p2</b>	1700.67	1.67	18118.83	1.09	1405.95	1.28	16.62	1.30	2300.20	1.54	1.36
<b>TILE_1</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1572.33	1.54	18106.35	1.09	1756.78	1.60	19.15	1.49	2331.12	1.56	1.44
<b>p1</b>	1589.20	1.56	18111.83	1.09	1788.40	1.63	19.19	1.50	2336.95	1.57	1.45
<b>p2</b>	1588.90	1.56	17654.20	1.06	1841.80	1.68	19.07	1.49	2341.57	1.57	1.45
<b>TILE_2</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	2004.60	1.97	18171.72	1.09	1499.00	1.37	18.32	1.43	2318.32	1.55	1.46
<b>p1</b>	2004.28	1.97	18140.70	1.09	1531.08	1.40	18.23	1.42	2322.20	1.56	1.46
<b>p2</b>	1954.80	1.92	18130.35	1.09	1477.33	1.35	18.15	1.41	2319.68	1.55	1.44
<b>TILE_3</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1596.33	1.57	17668.28	1.06	1670.60	1.52	18.90	1.47	2368.55	1.59	1.43
<b>p1</b>	1581.15	1.55	18141.30	1.09	1772.17	1.62	19.04	1.48	2372.60	1.59	1.45
<b>p2</b>	1575.67	1.55	18163.83	1.09	1879.10	1.71	18.96	1.48	2375.93	1.59	1.47
<b>TILE_4</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	2020.00	1.98	18111.65	1.09	1853.83	1.69	18.43	1.44	2332.55	1.56	1.52
<b>p1</b>	2033.17	2.00	18108.38	1.09	1751.08	1.60	18.27	1.42	2338.03	1.57	1.51
<b>p2</b>	2031.38	1.99	18091.03	1.09	1700.53	1.55	18.12	1.41	2344.10	1.57	1.49
<b>TILE_5</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1874.50	1.84	18178.85	1.09	1468.47	1.34	18.66	1.45	2147.62	1.44	1.41
<b>p1</b>	1917.15	1.88	18165.05	1.09	1396.20	1.27	18.60	1.45	2147.45	1.44	1.40
<b>p2</b>	1898.83	1.86	18132.62	1.09	1343.50	1.22	18.67	1.46	2148.07	1.44	1.39

<b>TILE_6</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1745.67	1.71	17701.40	1.07	1653.40	1.51	16.27	1.27	2194.18	1.47	1.39
<b>p1</b>	1777.22	1.74	18137.10	1.09	1636.40	1.49	16.20	1.26	2204.07	1.48	1.40
<b>p2</b>	1760.55	1.73	18139.15	1.09	1567.17	1.43	16.24	1.27	2203.12	1.48	1.38
<b>TILE_7</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1913.50	1.88	18132.30	1.09	1552.70	1.42	15.91	1.24	2193.30	1.47	1.40
<b>p1</b>	1861.75	1.83	18140.72	1.09	1456.83	1.33	15.17	1.18	2194.35	1.47	1.36
<b>p2</b>	1892.67	1.86	18148.72	1.09	1429.03	1.30	15.18	1.18	2195.50	1.47	1.36
<b>TILE_8</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1917.33	1.88	18117.03	1.09	1696.75	1.55	16.27	1.27	2160.40	1.45	1.42
<b>p1</b>	1909.55	1.87	17666.67	1.06	1767.80	1.61	16.78	1.31	2166.70	1.45	1.44
<b>p2</b>	1902.08	1.87	18112.22	1.09	1727.90	1.58	16.73	1.30	2170.40	1.45	1.43
<b>TILE_9</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1704.67	1.67	18106.80	1.09	1513.50	1.38	15.89	1.24	2180.22	1.46	1.35
<b>p1</b>	1657.05	1.63	18091.30	1.09	1645.15	1.50	15.79	1.23	2177.22	1.46	1.37
<b>p2</b>	1704.97	1.67	17631.30	1.06	1710.70	1.56	15.73	1.23	2175.22	1.46	1.38
<b>TILE_10</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1666.05	1.64	18077.25	1.09	1298.08	1.18	18.13	1.41	2326.35	1.56	1.36
<b>p1</b>	1641.47	1.61	17613.95	1.06	1255.53	1.14	17.95	1.40	2325.43	1.56	1.34
<b>p2</b>	1639.88	1.61	18084.38	1.09	1250.53	1.14	17.90	1.40	2324.57	1.56	1.34
<b>TILE_11</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1756.20	1.72	18072.42	1.09	1521.80	1.39	16.72	1.30	2338.90	1.57	1.40
<b>p1</b>	1747.22	1.71	18078.42	1.09	1519.75	1.39	16.85	1.31	2322.35	1.56	1.40
<b>p2</b>	1753.35	1.72	18077.10	1.09	1454.05	1.33	16.87	1.32	2310.45	1.55	1.38
<b>TILE_12</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	2031.33	1.99	17703.38	1.07	1491.05	1.36	18.78	1.46	2374.78	1.59	1.46
<b>p1</b>	2028.65	1.99	18112.92	1.09	1626.75	1.48	18.62	1.45	2382.93	1.60	1.49
<b>p2</b>	2037.10	2.00	18110.25	1.09	1728.40	1.58	18.51	1.44	2381.72	1.60	1.51
<b>TILE_13</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	1962.08	1.93	18161.62	1.09	1334.03	1.22	17.14	1.34	2382.75	1.60	1.40
<b>p1</b>	1951.40	1.92	18138.40	1.09	1584.72	1.44	16.80	1.31	2386.65	1.60	1.45
<b>p2</b>	1938.67	1.90	18133.80	1.09	1649.10	1.50	16.96	1.32	2385.15	1.60	1.46
<b>TILE_14</b>	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
<b>p0</b>	2020.47	1.98	18145.90	1.09	1352.38	1.23	16.91	1.32	2411.07	1.62	1.42
<b>p1</b>	2007.53	1.97	18108.38	1.09	1496.10	1.36	16.93	1.32	2405.07	1.61	1.44
<b>p2</b>	2000.67	1.96	18092.55	1.09	1422.28	1.30	16.78	1.31	2404.85	1.61	1.42

TILE_15	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	Actual	Ratio	GM
p0	1752.75	1.72	18100.40	1.09	1275.28	1.16	16.88	1.32	2178.70	1.46	1.33
p1	1751.58	1.72	18065.78	1.09	1538.75	1.40	16.99	1.32	2209.85	1.48	1.39
p2	1754.33	1.72	18068.80	1.09	1763.58	1.61	16.96	1.32	2204.35	1.48	1.43
p0_score:	22.57										
p1_score:	22.72										
p2_score:	22.70										
Unreviewed_VMmark_Score:	22.70										

## Configuration

Server and Network	
Server Manufacturer and Model	Dell PowerEdge R905
Processor Vendor and Model	Quad-Core AMD Opteron 8393 SE
Processor Speed (GHz)	3.1GHz
Number of Sockets/Cores per Socket	4 Sockets / 4 Cores per Socket (16 Cores Total)
Primary Cache	128KB I + 128KB D on chip per core
Secondary Cache	2MB
Other Cache	6MB
Memory	128 GB (16x8GB PC2-5300 667MHz Registered ECC DDR2 DIMMs)
Disk Subsystem Type	SAS(OS), FC SAN(VMs)
Number of Disk Controllers	NA
Number of Host Bus Adapters	2
Host Bus Adapter Vendors and Models	1x Dell PowerEdge Expandable RAID Controller (PERC) 6/i 1x QLogic Corp QLE2462 Dual Port
Number of Network Controllers	4
Network Controller Vendors and Models	Broadcom NetXtreme II BCM5708 (onboard)
Network Switch Vendors and Models	Dell PowerConnect 6248
Network Speed	1000Base-T
Other Hardware	None
Other Software	None
Hardware Availability Date	05/18/2009
Software Availability Date	06/30/2009
Virtualization Software	
Vendor, Product, Version, and Build	VMware ESX version 4.0 build 159706

Virtualization Type	Hardware
Supplemental Software	None
Virtualization Software Availability Date	06/30/2009
<b>Storage</b>	
Array Vendor, Model, and Firmware Version	3 x Dell/EMC CX3-40f, version 03.26.040.5.025
Fibre Channel Switch Vendors and Models	Brocade SilkWorm 3200 Brocade SilkWorm 3800
Disk Space Used	992 GB for VMs
Array Cache Size	8GB per array
Number and Size of LUNs	16 LUNs, each ~300 GB
RAID Type	RAID0
Number of Members per RAID Set	10
Disk Vendor, Model, and Speed	Hitachi HUS151P7/Seagate STT73455 15K
<b>Clients</b>	
Number of Clients	16
System Model(s)	client0: PowerEdge 1750 client1: PowerEdge 1750 client2: PowerEdge 1750 client3: PowerEdge 1750 client4: PowerEdge 1850 client5: PowerEdge 1650 client6: PowerEdge 1650 client7: PowerEdge 1650 client8: PowerEdge 1650 client9: PowerEdge 1650 client10: PowerEdge 1850 client11: PowerEdge 1850 client12: PowerEdge 1850 client13: PowerEdge 1850 client14: PowerEdge 1850 client15: PowerEdge 1850
Processor Vendor(s) and Model(s)	Intel Xeon
Processor Speed(s) (GHz)	client0: 3.06 client1: 3.06 client2: 3.20 client3: 3.20 client4: 2.80 client5: 1.40 client6: 1.40 client7: 1.40

	client8: 1.40 client9: 1.40 client10: 3.40 client11: 3.60 client12: 3.60 client13: 3.60 client14: 3.60 client15: 3.60
Number of Sockets/Cores per Socket	client0: 2 Sockets / 1 Core per Socket (2 Cores Total) client1: 2 Sockets / 1 Core per Socket (2 Cores Total) client2: 2 Sockets / 1 Core per Socket (2 Cores Total) client3: 2 Sockets / 1 Core per Socket (2 Cores Total) client4: 1 Socket / 2 Cores per Socket (2 Cores Total) client5: 2 Sockets / 1 Core per Socket (2 Cores Total) client6: 2 Sockets / 1 Core per Socket (2 Cores Total) client7: 2 Sockets / 1 Core per Socket (2 Cores Total) client8: 2 Sockets / 1 Core per Socket (2 Cores Total) client9: 2 Sockets / 1 Core per Socket (2 Cores Total) client10: 2 Sockets / 1 Core per Socket (2 Cores Total) client11: 2 Sockets / 1 Core per Socket (2 Cores Total) client12: 2 Sockets / 1 Core per Socket (2 Cores Total) client13: 2 Sockets / 1 Core per Socket (2 Cores Total) client14: 2 Sockets / 1 Core per Socket (2 Cores Total) client15: 2 Sockets / 1 Core per Socket (2 Cores Total)
Memory	2 GB except client10, which had 8 GB
Network Controller Vendor and Model	Intel PRO/1000 XT Network Connection (1650), Broadcom NetXtreme Gigabit Ethernet (1750), Intel PRO/1000 MT Network Connection (1850)
Operating System, Version, and Service Pack	Microsoft Windows Server 2003 Enterprise Edition SP2
Other Hardware	None
Other Software	None

h2>Notes for Workload

### Server and Network Notes

- BIOS settings:  
 Virtualization Technology = Enabled  
 Internal USB port = Off (default On)
- Array settings:  
 Storage Processor cache High/Low watermark - 40/20 (default 80/60)
- Network Settings:  
 Broadcom NICs (vnic0,1,2,3) bound to vSwitch0,1,2,3 respectively  
 Service console and Standby attached to vSwitch0  
 JavaServer, MailServer, and FileServer VMs attached to vSwitch1  
 Database VMs attached to vSwitch2  
 WebServer VMs attached to vSwitch3
- Storage Notes:  
 For all VMs, each tile was stored on its own LUN

## Virtualization Software Notes

- Hardware support for both CPU and MMU virtualization enabled on all VMs (default Automatic)
- EnableNaviReg set to 0 (default 1)
- Disk.SchedNumReqOutstanding was set to 128 (default 32)
- Net.EtherswitchHashSize was set to 4 (default 1)
- BufferCache.SoftMaxDirty was set to 85 (default 15)
- IRQ.RoutingPolicy was set to 0 (Default 2)
- VMFS3.MaxHeapSizeMB was set to 64 (default 80)
- All VMs' hardware upgraded to version 7
- Ethernet Adapter type was set to VMXNET3 for all VMs
- Logging was disabled for all VMs (default enabled)
- IDE and Floppy devices were removed on all VMs (default enabled)
- iptables and firewall services disabled at boot

## Operating System Notes

- Microsoft Windows Server 2003 virtual machines were updated to Service Pack 2, and KB951072-v2 was applied
- SUSE Linux Enterprise Server 10 virtual machines were updated to Service Pack 2

## Software Notes

## Client Notes

- KB951072-v2 was applied

## Other Notes

---

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit [www.vmware.com/products/vmmark](http://www.vmware.com/products/vmmark).

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark™ is a product of [VMware, Inc.](http://www.vmware.com) VMmark utilizes SPECjbb®2005 and SPECweb®2005, which are available from the [Standard Performance Evaluation Corporation \(SPEC®\)](http://www.spec.org).