

VMware®VMmark®V2.1.1 Results

Vendor and Hardware Platform: Fujitsu PRIMERGY RX500 S7
 Virtualization Platform: VMware ESX 4.1.0 U2 Build 502767
 VMware vCenter Server: VMware vCenter Server 4.1.0 U2 build 491557

**VMmark V2.1.1 Score =
18.68 @ 18 Tiles**

Number of Hosts: 2	Uniform Hosts [yes/no]: yes	Total sockets/core/threads in test: 8 Sockets / 64 Cores / 128 Threads
	Tested By: Fujitsu	Test Date: 06-13-2012
Performance Section Performance	Configuration Section Configuration	Notes Section Notes for Workload

Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.07	0.98	87.70	4629.00	1.00	204.13	3322.32	1.51	99.29	2399.85	1.58	110.20	1714.00	1.62	117.78	1.30
p1	329.25	1.00	94.00	4652.73	1.00	205.38	3271.40	1.49	102.31	2261.68	1.49	115.34	1670.00	1.58	122.51	1.28
p2	329.15	1.00	94.00	4638.45	1.00	215.74	3260.65	1.48	102.36	2267.70	1.49	114.99	1585.45	1.50	123.64	1.27
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.43	0.98	91.10	4658.07	1.00	194.66	3181.95	1.45	107.25	2294.62	1.51	119.27	1709.95	1.62	126.97	1.28
p1	324.50	0.98	94.00	4618.50	1.00	234.78	3220.70	1.46	104.91	2234.07	1.47	117.69	1552.35	1.47	127.54	1.25
p2	324.00	0.98	94.00	4625.85	1.00	228.41	3160.47	1.44	108.63	2271.57	1.50	121.27	1597.67	1.51	131.10	1.26
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.95	0.99	119.75	4640.88	1.00	200.03	3306.50	1.50	100.13	2292.62	1.51	112.81	1701.22	1.61	119.41	1.29
p1	329.43	1.00	138.25	4635.15	1.00	210.80	3314.38	1.51	99.13	2321.07	1.53	110.48	1641.25	1.55	117.20	1.29
p2	327.75	0.99	181.00	4613.88	0.99	236.39	3197.78	1.45	106.29	2397.70	1.58	117.46	1736.10	1.64	124.28	1.30
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.75	0.98	97.00	4627.62	1.00	201.76	3368.65	1.53	95.72	2356.93	1.55	106.88	1661.95	1.57	113.92	1.30
p1	323.35	0.98	94.00	4635.20	1.00	220.75	3274.97	1.49	101.16	2380.97	1.57	111.41	1709.42	1.62	117.89	1.30
p2	322.57	0.98	105.50	4614.30	0.99	231.81	3267.70	1.49	101.70	2363.38	1.56	113.05	1773.97	1.68	118.53	1.30
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.88	0.98	94.00	4674.48	1.01	192.25	3172.75	1.44	108.26	2192.62	1.44	121.65	1539.12	1.45	130.37	1.25
p1	330.40	1.00	94.00	4646.15	1.00	201.91	3119.00	1.42	112.01	2312.07	1.52	124.44	1653.67	1.56	133.50	1.28
p2	328.70	1.00	100.00	4621.05	1.00	223.33	3063.28	1.39	115.44	2104.97	1.39	130.21	1484.97	1.40	138.23	1.22
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	332.07	1.01	106.00	4668.00	1.01	195.88	3299.12	1.50	99.44	2410.45	1.59	109.10	1753.53	1.66	112.57	1.32
p1	327.38	0.99	120.97	4623.55	1.00	198.97	3272.03	1.49	101.88	2348.88	1.55	114.37	1673.62	1.58	122.23	1.29

p2	329.43	1.00	114.00	4623.90	1.00	220.84	3175.68	1.44	107.87	2194.30	1.44	121.98	1610.42	1.52	130.11	1.26
TILE_6	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.25	0.99	116.95	4655.82	1.00	206.47	3226.20	1.47	105.06	2418.80	1.59	116.14	1728.55	1.63	125.19	1.30
p1	325.30	0.99	148.25	4598.75	0.99	248.61	3223.20	1.47	105.21	2224.20	1.46	119.31	1631.72	1.54	127.60	1.26
p2	320.98	0.97	163.25	4562.52	0.98	304.45	3194.95	1.45	107.05	2212.82	1.46	119.76	1553.92	1.47	128.55	1.24
TILE_7	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.57	0.99	94.00	4651.98	1.00	193.32	3351.38	1.52	97.21	2333.43	1.54	109.16	1711.53	1.62	117.15	1.30
p1	326.80	0.99	107.25	4640.50	1.00	212.82	3284.32	1.49	100.80	2356.80	1.55	113.61	1613.03	1.52	120.80	1.28
p2	327.20	0.99	129.00	4613.48	0.99	234.37	3223.30	1.47	105.20	2339.30	1.54	115.34	1716.28	1.62	125.42	1.29
TILE_8	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.45	0.99	94.00	4636.50	1.00	202.13	3379.25	1.54	95.81	2444.97	1.61	107.10	1664.40	1.57	114.12	1.31
p1	325.10	0.98	94.00	4605.95	0.99	227.38	3264.15	1.48	102.48	2281.68	1.50	113.91	1664.97	1.57	123.36	1.28
p2	329.85	1.00	94.00	4595.93	0.99	241.15	3221.62	1.46	104.72	2315.10	1.52	117.03	1716.28	1.62	125.05	1.29
TILE_9	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.65	0.99	88.42	4651.25	1.00	198.79	3227.45	1.47	104.53	2240.53	1.48	117.19	1566.70	1.48	126.37	1.26
p1	324.35	0.98	86.00	4637.32	1.00	217.10	3181.57	1.45	106.98	2389.93	1.57	117.47	1712.42	1.62	126.20	1.29
p2	326.10	0.99	94.00	4611.65	0.99	235.01	3197.12	1.45	106.23	2217.93	1.46	119.41	1618.62	1.53	128.75	1.26
TILE_10	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	331.52	1.00	94.33	4642.70	1.00	197.99	3266.70	1.49	101.80	2363.30	1.56	112.63	1695.62	1.60	119.12	1.30
p1	322.12	0.98	94.00	4629.85	1.00	227.69	3256.10	1.48	103.99	2325.35	1.53	116.96	1723.22	1.63	124.97	1.29
p2	327.35	0.99	94.00	4610.02	0.99	231.09	3211.72	1.46	106.51	2214.30	1.46	120.54	1539.67	1.46	130.42	1.25
TILE_11	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.15	0.99	101.00	4655.27	1.00	193.62	3312.85	1.51	98.97	2484.53	1.64	109.24	1792.30	1.69	116.53	1.33
p1	321.27	0.97	96.50	4623.60	1.00	223.50	3307.80	1.50	99.72	2291.93	1.51	112.53	1677.12	1.59	120.67	1.28
p2	326.20	0.99	94.00	4602.02	0.99	249.57	3189.28	1.45	107.73	2193.43	1.44	121.81	1524.45	1.44	132.11	1.24
TILE_12	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.80	1.00	98.00	4644.88	1.00	213.01	3144.50	1.43	109.75	2248.18	1.48	123.71	1589.65	1.50	132.64	1.26
p1	327.70	0.99	95.00	4618.65	1.00	217.40	3149.80	1.43	109.46	2187.05	1.44	122.36	1588.03	1.50	133.63	1.25
p2	323.65	0.98	94.00	4589.32	0.99	253.52	2987.65	1.36	121.44	2135.45	1.41	135.38	1492.08	1.41	147.24	1.21
TILE_13	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.30	0.99	94.25	4664.35	1.00	188.75	3309.30	1.50	99.83	2327.20	1.53	110.49	1710.47	1.62	118.15	1.30
p1	324.73	0.98	94.00	4635.12	1.00	213.32	3260.85	1.48	101.88	2293.20	1.51	112.91	1617.05	1.53	120.55	1.27
p2	326.55	0.99	94.00	4607.93	0.99	231.60	3115.50	1.42	112.40	2234.10	1.47	125.49	1651.30	1.56	134.59	1.26
TILE_14	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	323.68	0.98	94.22	4639.30	1.00	193.90	3273.68	1.49	101.70	2297.75	1.51	113.14	1689.10	1.60	121.00	1.29
p1	330.20	1.00	94.00	4636.93	1.00	207.84	3183.03	1.45	107.86	2311.57	1.52	118.71	1632.08	1.54	127.98	1.28

p2	326.73	0.99	94.00	4616.38	0.99	256.56	3191.55	1.45	107.75	2214.82	1.46	120.93	1602.42	1.51	131.72	1.26
TILE_15	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.00	0.99	95.58	4651.55	1.00	188.83	3375.00	1.53	95.39	2385.40	1.57	105.22	1751.97	1.66	112.72	1.32
p1	326.35	0.99	94.00	4639.07	1.00	204.90	3297.25	1.50	100.34	2383.05	1.57	111.75	1779.80	1.68	118.41	1.31
p2	325.02	0.98	94.00	4608.95	0.99	224.84	3237.70	1.47	104.15	2248.55	1.48	116.85	1558.45	1.47	127.38	1.26
TILE_16	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.90	0.98	107.75	4644.07	1.00	196.98	3248.22	1.48	103.47	2344.03	1.54	115.25	1748.28	1.65	122.19	1.30
p1	323.62	0.98	104.00	4652.10	1.00	209.46	3214.43	1.46	105.12	2219.65	1.46	119.03	1637.78	1.55	126.46	1.27
p2	325.20	0.98	103.75	4628.65	1.00	216.38	3204.95	1.46	106.42	2205.05	1.45	120.68	1540.22	1.46	130.28	1.25
TILE_17	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.40	0.99	104.70	4661.43	1.00	193.77	3377.78	1.54	95.43	2416.78	1.59	108.28	1795.80	1.70	115.75	1.33
p1	330.70	1.00	99.50	4646.18	1.00	200.28	3356.62	1.53	96.36	2324.07	1.53	109.42	1627.08	1.54	118.10	1.29
p2	326.43	0.99	94.50	4611.88	0.99	229.06	3243.80	1.48	103.30	2323.95	1.53	116.26	1643.97	1.55	125.16	1.28
p0_score:	23.33															
p1_score:	23.06															
p2_score:	22.71															

Infrastructure_Operations_Scores:	vmotion	svmotion	deploy
Completed_Ops_PerHour	15.50	11.00	5.00
Avg_Seconds_To_Complete	48.14	44.30	311.20
Failures	0.00	0.00	0.00
Ratio	0.97	1.22	1.25
Number_Of_Threads	1	1	1

Summary	Run_Is_Compliant	Number_Of_Compliance_Issues(0)*	Median_Phase(p1)
Unreviewed_VMmark2_Applications_Score	23.06		
Unreviewed_VMmark2_Infrastructure_Score	1.14		
Unreviewed_VMmark2_Score	18.68		

Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESX 4.1.0 U2 Build 502767 / 10-27-2011
Datacenter Management Software Vendor, Product, Version, and Build /	VMware vCenter Server 4.1.0 U2 Build 491557 / 10-27-2011

Availability Date (MM-DD-YYYY)	
Supplemental Software	none
Servers	
Quantity	2
Server Manufacturer and Model	Fujitsu PRIMERGY RX500 S7
Processor Vendor and Model	Eight-core Intel Xeon E5-4650
Processor Speed (GHz)	2.70
Total Sockets/Total Cores/Total Threads	4 Sockets / 32 Cores / 64 Threads
Primary Cache	32KB I + 32KB D on chip per core
Secondary Cache	256KB I+D on chip per core
Other Cache	20MB I+D on chip per chip L3
BIOS Version	V00.63
Memory Size (in GB, Number of DIMMs)	512GB, 32
Memory Type and Speed	16GB DIMMs 2Rx4 L DDR3-1600 R ECC
Disk Subsystem Type	FC SAN
Number of Disk Controllers	1 (disabled)
Disk Controller Vendors and Models	Intel Patsburg SAS/SATA SCU
Number of Host Bus Adapters	1
Host Bus Adapter Vendors and Models	Dual-channel Emulex LPe12002
Number of Network Controllers	2
Network Controller Vendors and Models	Integrated Intel I350 Dual Port 1GbE Adapter Intel 82580 Quad Port 1GbE Adapter (1 port used) Fujitsu D2755 Dual Port 10GbE Adapter
Other Hardware	none
Other Software	none
Hardware Availability Date (MM-DD-YYYY)	10-01-2012
Software Availability Date (MM-DD-YYYY)	10-27-2011
Network	
Network Switch Vendors and Models	Fujitsu PRIMERGY BX600 GbE Switch Blade 30/12, CISCO 4900M
Network Speed	1Gbps for SUT management, Prime Client and VMotion, 10Gbps for remaining clients and all VMs
Storage	

Array Vendors, Models, and Firmware Versions	8xFujitsu ETERNUS DX80, Firmware version V10L20-0000 1xFujitsu ETERNUS DX80S2, Firmware version V10L16-0000
Fibre Channel Switch Vendors and Models	Brocade 5100
Disk Space Used	5872GB
Array Cache Size	2GB
Total Number of Physical Disks Used	192
Total Number of Enclosures/Pods/Shelves Used	16
Number of Physical Disks Used per Enclosure/Pod/Shelf	Details in section Storage Notes
Total Number of Storage Groups Used	10
Number of LUNs Used	53
LUN Size and Number of Disks Per LUN	Details in section Storage Notes
RAID Type	0
Number of Members per RAID Set	Details in section Storage Notes
Disk Vendors, Models, and Speeds	4xSeagate, ST3450856SS, 15krpm; 168xSeagate, ST3300656SS, 15krpm; 20xSTEC Zeus SSD, Z16IZF2D-100UCT-FUJ

Datacenter Management Server

System Model	Fujitsu PRIMERGY BX620S4
Processor Vendor and Model	Intel Xeon X5470
Processor Speed (GHz)	3.33
Total Sockets/Total Cores/Total Threads	2 Sockets / 4 Cores / 8 Threads
Memory	4GB
Network Controller(s) Vendors and Models	3xDual Port Broadcom NetXtreme, 5 Ports disabled
Operating System, Version, and Service Pack	Microsoft(R) Windows(R) Server 2003 R2 Enterprise x64 Edition, SP2
Other Hardware	none
Other Software	none

Clients

Number of Clients	1 physical client (Prime Client) used as a dedicated Benchmark Controller 1 physical client (ESX server) used for 10 virtual clients
System Model(s)	Prime Client: Fujitsu PRIMERGY BX620S4 ESX server : Fujitsu PRIMERGY RX600S6

Processor Vendor(s) and Model(s)	Prime Client: Intel Xeon X5470 ESX server : Intel Xeon E7-4870
Processor Speed(s) (GHz)	Prime Client: 3.33 ESX server : 2.4
Total Sockets/Total Cores/Total Threads	Prime Client: 2 Sockets / 4 Cores / 4 Threads ESX server : 4 Sockets / 40 Cores / 80 Threads
Memory per Client	Prime Client: 4 GB ESX server : 512 GB
Network Controller(s) Vendors and Models	Prime Client: 3xDual Port Broadcom NetXtreme, 4 Ports disabled ESX server : 2xDual Port Broadcom NetXtreme, 3 Ports unused, Fujitsu D2755 Dual Port 10GbE Adapter
Operating System, Version, and Service Pack	Prime Client : Microsoft(R) Windows(R) Server 2003 R2 Enterprise Edition (32-bit), SP2 ESX server : ESX 4.1.0 U2 Build 502767 Virtual clients: Microsoft(R) Windows(R) Server 2008 Enterprise Edition (64-bit), SP2
Other Hardware	ESX server: 1xDual-channel Emulex LPe12002, 1xFujitsu ETERNUS DX80 with 24x300GB disks
Other Software	none

Notes for Workload

Virtualization Software Notes

- Floppy and CDROM removed for all VMs (default enabled)
- Firewall disabled for the Console OS (default enabled)
- Hardware version 7 used for all VMs (default 7)
- Logging disabled for all VMs (default enabled)
- Logical CPU layout changed for all VMs (except Standby) to one socket with multiple cores (default: multiple sockets with one core per socket)
- SCSI adapter type PVSCSI used for all Standby VMs (default LSI Logic parallel)
- SCSI adapter type PVSCSI used for all Mailserver VMs (default LSI Logic SAS)
- VMXNET3 enabled for all VMs (default VMXNET2)
- Changes in esx.conf:
 - /adv/Cpu/CoschedCrossCall = 0 (default 1)
 - /adv/Cpu/HaltingIdleMsecPenalty = 0 (default 100)
 - /adv/Irq/RoutingPolicy = 0 (default 2)
 - /adv/Mem/BalancePeriod = 0 (default 15)
 - /adv/Mem/SamplePeriod = 0 (default 60)
 - /adv/Mem/ShareScanGHZ = 0 (default 4)
 - /adv/Mem/VMOverheadGrowthLimit = 0 (default 4)
 - /adv/Misc/TimerMinHardPeriod = 2000 (default 100)
 - /adv/Misc/WorldletHTSharing = 45 (default 90)
 - /adv/Net/MaxNetifRxQueueLen = 500 (default 100)
 - /adv/Net/MaxNetifTxQueueLen = 1000 (default 500)
 - /adv/Net/NetTxWorldlet = 0 (default 2)
 - /adv/Numa/LTermFairnessInterval = 0 (default 5)
 - /adv/Numa/PageMigEnable = 0 (default 1)
 - /adv/Numa/RebalancePeriod = 60000 (default 2000)
 - /adv/Numa/SwapInterval = 1 (default 3)
 - /adv/Numa/SwapLoadEnable = 0 (default 1)
 - /adv/Numa/SwapLocalityEnable = 0 (default 1)

/vmkernel/module/ixgbe.o/options = "VMDQ=1,1" (defaults 8,8)

/vmkernel/module/lpfc820.o/options = "lpfc_lun_queue_depth=64 lpfc_cr_count=3 lpfc_cr_delay=1" (defaults 31,1,0)

Server Notes

- Server BIOS settings:
 - Adjacent Cache Line Prefetch: Disabled (default enabled)
 - Energy Performance: Performance (default Energy Efficient)
 - Frequency Floor Override: Disabled (default enabled)
 - Hardware Prefetcher: Disabled (default enabled)
 - Onboard SAS/SATA SCU: Disabled (default enabled)
 - Serial 1: Disabled (default enabled)
 - Turbo Boost Technology: Enabled (Intel Turbo Boost up to 3.3GHz, default enabled)
- Emulex HBA BIOS settings:
 - defaults

Networking Notes

- One dedicated VLAN for the systems under test, vCenter Server and Benchmark Controller (SUT-VLAN)
- One dedicated VLAN for the VMs and Clients (Load-VLAN)
- vSwitch Configuration:
 - vSwitch0 on vmnic0 (1Gb) for Service Console
 - vSwitch1 on vmnic1 (1Gb) for VMotion
 - vSwitch2 on vmnic6 (10Gb) for all Olio VMs
 - vSwitch3 on vmnic7 (10Gb) for all DS2 VMs
 - vSwitch4 on vmnic2 (1Gb) for all other VMs and Deploy VM

Storage Notes

- ETERNUS DX80[0] (1 shelf, total 4 disks)
 - RAID set 0: (4 disks)
 - LUN 0: Boot/Console OS for SUT1 (11GB)
 - LUN 1: Boot/Console OS for SUT2 (11GB)
- ETERNUS DX80[1] (2 shelves, total 24 disks)
 - RAID set 0: (6 disks)
 - LUN 1: All even numbered Standby VMs (110GB)
 - LUN 2: All odd numbered Standby VMs (110GB)
 - RAID set 1: (6 disks)
 - LUN 3: Source Deploy Template (50GB)
 - RAID set 2: (6 disks)
 - LUN 4: Target Storage VMotion (50GB)
 - RAID set 3: (6 disks)
 - LUN 5: Target Deploy Template (50GB)
- ETERNUS DX80[2] (2 shelves, total 24 disks)
 - RAID set 0: (8 disks)
 - LUN 1: For Tile 0 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)
 - LUN 2: For Tile 0 OlioDB (20GB)

RAID set 1: (8 disks)

LUN 3: For Tile 6 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 4: For Tile 6 OlioDB (20GB)

RAID set 2: (8 disks)

LUN 5: For Tile 12 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 6: For Tile 12 OlioDB (20GB)

- ETERNUS DX80[3] (2 shelves, total 24 disks)

RAID set 0: (8 disks)

LUN 1: For Tile 1 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 2: For Tile 1 OlioDB (20GB)

RAID set 1: (8 disks)

LUN 3: For Tile 7 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 4: For Tile 7 OlioDB (20GB)

RAID set 2: (8 disks)

LUN 5: For Tile 13 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 6: For Tile 13 OlioDB (20GB)

- ETERNUS DX80[4] (2 shelves, total 24 disks)

RAID set 0: (8 disks)

LUN 1: For Tile 2 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 2: For Tile 2 OlioDB (20GB)

RAID set 1: (8 disks)

LUN 3: For Tile 8 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 4: For Tile 8 OlioDB (20GB)

RAID set 2: (8 disks)

LUN 5: For Tile 14 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 6: For Tile 14 OlioDB (20GB)

- ETERNUS DX80[5] (2 shelves, total 24 disks)

RAID set 0: (8 disks)

LUN 1: For Tile 3 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 2: For Tile 3 OlioDB (20GB)

RAID set 1: (8 disks)

LUN 3: For Tile 9 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 4: For Tile 9 OlioDB (20GB)

RAID set 2: (8 disks)

LUN 5: For Tile 15 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 6: For Tile 15 OlioDB (20GB)

- ETERNUS DX80[6] (2 shelves, total 24 disks)

RAID set 0: (8 disks)

LUN 1: For Tile 4 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 2: For Tile 4 OlioDB (20GB)

RAID set 1: (8 disks)

LUN 3: For Tile 10 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 4: For Tile 10 OlioDB (20GB)

RAID set 2: (8 disks)

LUN 5: For Tile 16 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)

LUN 6: For Tile 16 OlioDB (20GB)

- ETERNUS DX80[7] (2 shelves, total 24 disks)
 - RAID set 0: (8 disks)
 - LUN 1: For Tile 5 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)
 - LUN 2: For Tile 5 OlioDB (20GB)
 - RAID set 1: (8 disks)
 - LUN 3: For Tile 11 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)
 - LUN 4: For Tile 11 OlioDB (20GB)
 - RAID set 2: (8 disks)
 - LUN 5: For Tile 17 DS2WebA, DS2WebB, DS2WebC, Mailserver, Olioweb and first VHD from DS2DB (240GB)
 - LUN 6: For Tile 17 OlioDB (20GB)
- ETERNUS DX80S2 (1 shelf, total 20 SSDs)
 - RAID set 0: (2 SSDs)
 - LUN 1: For Tile 0,10 second VHD from DS2DB (80GB)
 - RAID set 1: (2 SSDs)
 - LUN 2: For Tile 1,11 second VHD from DS2DB (80GB)
 - RAID set 2: (2 SSDs)
 - LUN 3: For Tile 2,12 second VHD from DS2DB (80GB)
 - RAID set 3: (2 SSDs)
 - LUN 4: For Tile 3,13 second VHD from DS2DB (80GB)
 - RAID set 4: (2 SSDs)
 - LUN 5: For Tile 4,14 second VHD from DS2DB (80GB)
 - RAID set 5: (2 SSDs)
 - LUN 6: For Tile 5,15 second VHD from DS2DB (80GB)
 - RAID set 6: (2 SSDs)
 - LUN 7: For Tile 6,16 second VHD from DS2DB (80GB)
 - RAID set 7: (2 SSDs)
 - LUN 8: For Tile 7,17 second VHD from DS2DB (80GB)
 - RAID set 8: (2 SSDs)
 - LUN 9: For Tile 8 second VHD from DS2DB (80GB)
 - RAID set 9: (2 SSDs)
 - LUN 10: For Tile 9 second VHD from DS2DB (80GB)

Datacenter Management Server Notes

None

Operating System Notes

Mailserver VMs: Microsoft Windows 2008 R2 Enterprise 64-bit.

Software Notes

Mailserver VMs: Microsoft Exchange 2007 Enterprise x64 Edition updated with SP3.

Client Notes

Prime Client was running VMware vSphere PowerCLI 4.1 build 264274.

All client drivers were run on virtual machines that were each defined with 4 virtual cpus, 4GB of memory, 1 vmxnet3 network, and 32GB of disk space.

Other Notes

One Client used as a dedicated Benchmark Controller. This system was connected to the SUT- and the Load-VLAN.

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit www.vmware.com/products/vmmark.

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of [VMware, Inc.](http://www.vmware.com).